

300 E. Mineral Ave., Suite 10 Littleton, CO 80122-2631 303/781-1167 Fax 303/781-8211

August 2, 2004

Fluid Minerals Group **Bureau of Land Management** Vernal Field Office 170 South 500 East Vernal, Utah 84078

RE: Application for Permit to Drill-Dominion Exploration & Production, Inc. HCU 14-34F, Surface Location: 829' FSL, 1,958' FEL, SW/4 SE/4, Target Location: 700' FSL, 1,950' FWL, SE/4 SW/4, Section 34, T10S, R20E, SLB&M, Uintah County, Utah

Dear Fluid Minerals Group:

On behalf of Dominion Exploration & Production, Inc. (Dominion), Buys & Associates, Inc. respectfully submits the enclosed original and two copies of the Application for Permit to Drill (APD) for the above referenced directional well. Included with the APD is the following supplemental information:

Exhibit "A" - Survey plats, layouts and photos of the proposed well site;

Exhibit "B" - Proposed location maps with access and utility corridors;

Exhibit "C" - Production site layout;

Exhibit "D" - Drilling Plan with Directional Drilling Proposal;

Exhibit "E" - Surface Use Plan;

Exhibit "F" - Typical BOP and Choke Manifold diagram.

Please accept this letter as Dominion's, written request for confidential treatment of all information contained in and pertaining to this application.

Thank you very much for your timely consideration of this application. Please feel free to contact myself or Carla Christian of Dominion at 405-749-5263 if you have any questions or need additional information.

Sincerely,

Jon Hamilton **Don Hamilton** Agent for Dominion

cc: Diana Whitney, Division of Oil, Gas and Mining Amanda Mart, Bureau of Indian Affairs Carla Christian, Dominion Marty Buys, Buys & Associates, Inc.

DIV. OF OIL, GAS & MINING

FRLE GOPLY

CONFIDENTIAL

Form 3160-3 (December 1990)

LICATE* SUBMIT IN T (Other instruction reverse side)

Form approved.

Budget Bureau No. 1004-0136 Expires: December 31, 1991

O	0	1

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

5. LEASE DESIGNATION	AND SERIAL NO.
<u>U-79130</u>	

									0.77150		
	APPLICATION FOR PERMIT TO DRILL OR DEEPEN									6. IF INDIAN, ALLOTTEE O	
la. TYPE OF WORK										Ute Indian Tri	
	DRII	LIL 🔯	DEEP	EN						Hill Creek Uni	- •
b. TYPE OF WELL					SINGLE .		MULTIPLE			8. FARM OR LEASE NAME,	
METT	GAS WELL	OTHER			ZONE	\overline{X}	ZONE			HCU 14-34F	
2. NAME OF OPERATOR	2. NAME OF OPERATOR 9. API WELL NO.										
Do	ominion Ex	xploration &	Production, Inc							43-0473	
3. ADDRESS AND TELE	PHONE NO.									10. FIELD AND POOL, OR V	VILDCAT
14	000 Quail	Springs Parl	kway, Suite 600.	Okla	ahoma City, O	K_	73134, 405-	·749-5	263	Natural Buttes	
4. LOCATION OF WELL At surface	(Report location	clearly and in accord	ance with any State require	ments.*)					11. SEC.,T.,R.,M., OR BLK. A	
		829' FSL, 1	,958' FEL		SW/4 SE/4	ţ				Section 34,	
At proposed prod. zone		700' FSL, I	,950' FWL		SE/4 SW/4	<u> </u>				T10S, R20E, S	
14 DISTANCE IN MILE	14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*									12. COUNTY OR PARISH	13. STATE
		13.18 miles	southeast of Ou	ray,	Utah					Uintah ACRES ASSIGNED	Utah
15. DISTANCE FROM PR LOCATION TO NEAR				16. NO	O. OF ACRES IN LEAS	SE				S WELL	
PROPERTY OR LEAS (Also to nearest drig, un	E LINE, FT.	7001	ļ		640				40	acres	
18. DISTANCE FROM PR		<u>700'</u>		19. PR	ROPOSED DEPTH					OR CABLE TOOLS	
LOCATION TO NEAD	REST WELL,										
APPLIED FOR, ON TI		25'			8,050'					otary	
21. ELEVATIONS (Show	whether DF,RT,	GR,etc.)							22.	APPROX. DATE WORK WILL	START*
		5,340	GR						İ	January 1, 2005	
23.			PROPOSED CAS	ING A	AND CEMENTIN	IG PI	ROGRAM				
SIZE OF HOLE	GRADE, SE	ZE OF CASING	WEIGHT PER FOO	T	SETTING DEPTH	I			QUANTI	TY OF CEMENT	
17-1/2"	13-3/8" H	I-40 ST&C	48# 500'			T	450 sks "C" Cement with additives (see Drilling Plan)				
12-1/4"	9-5/8" J-5	5/8" J-55 LT&C 36# 2,800' 300 sacks Lead and 390 sacks) sacks Tail (see Drilling Plan)				
7-7/8"	5-1/2" M	av-80 LT&C	17#		8,050'		90 sacks Lead a	nd 600	sacks Tail (se	ee Drilling Plan)	

Bond Information:

Bond coverage is provided by Travelers Casualty and Surety Company of America, Bond #76S 63050 0330

Other Information:

Drilling Plan and Surface Use Plan are attached.

Dominion requests that this complete application for permit to drill be held confidential.

RECEIVED

Surf. 615557 X 39.89901 BHL 615137 X 39.89845 44172137 -109.64828

AUG 0 4 2004

Federal Approval of this Action is Necessary


DIV. OF OIL, GAS & MINING

ORIGINAL

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any

4. SIGNED Don	Hamilton	Don Hamilton	Agent for Don	ninion dat	August 2, 2004
(This space for Fede	ral or State office use) 43-047-3	5875	APPROVAL DATE		
Application approcessor Approved By	oval does not warrant or or approval (ir any:	(1/()/)	legal or equitable title to those rig BRADLEY LE_ENVIRONMENTAL	G. HILL	TE 88-17-04
		*Se	ee Instructions On	Reverse Side	

T10S, R20E, S.L.B.&M.



= SECTION CORNERS LOCATED.

LATITUDE = 39.53'56.04" (39.898900)


LONGITUDE = 109'38'55.94" (109.648872)

DOMINION EXPLR. & PROD., INC.

Well location, HCU #14-34F, located as shown in the SW 1/4 SE 1/4 of Section 34, T10S, R20E, S.L.B.&M. Uintah County Utah.

BASIS OF ELEVATION

SPOT ELEVATION AT THE SOUTHWEST CORNER OF SECTION 20, T10S, R20E, S.L.B.&M. TAKEN FROM THE BIG PACK MTN. NW QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE QUAD. (TOPOGRAPHIC MAP)PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5251 FEET.



CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF

REGISTERED, LAND, SURVEYOR STATE OF UTAH A

Revised: 04-19-04 D.R.B.

UINTAH ENGINEERING & LAND SURVEYING 85 SOUTH 200 EAST - VERNAL UTAH 84078

(435) 789-1017

SCALE 1" = 1000'		DATE SURVEYED: DATE DRAWN: 03-09-04 03-30-04				
PARTY B.B. T.H.	D.R.B.	REFERENCES G.L.O. PLA	ΛΤ			
WEATHER COOL		FILE DOMINION EXP	LR. & PROD., INC			

DRILLING PLAN

APPROVAL OF OPERATIONS

Attachment for Permit to Drill

Name of Operator:

Dominion Exploration & Production

Address:

14000 Quail Springs Parkway, Suite 600

Oklahoma City, OK 73134

Well Location:

HCU 14-34F

SHL: 829' FSL & 1958' FEL Section 34-10S-20E

BHL: 700' FSL & 1950' FWL Section 34-10S-20E

Uintah County, UT

1. GEOLOGIC SURFACE FORMATION

Uintah

2. <u>ESTIMATED DEPTHS OF IMPORTANT GEOLOGIC MARKERS</u>

<u>Formation</u>	<u>Depth</u>
Wasatach Tongue	3,855
Uteland Limestone	4,190
Wasatch	4,330'
Chapita Wells	5,150°
Uteland Buttes	6,300
Mesaverde	7,150

3. <u>ESTIMATED DEPTHS OF ANTICIPATED WATER. OIL</u>, <u>GAS OR MINERALS</u>

<u>Formation</u>	<u>Depth</u>	Type
Wasatch Tongue	3,855	Oil
Uteland Limestone	4,190'	Oil
Wasatch	4,330	Gas
Chapita Wells	5,150'	Gas
Uteland Buttes	6,300°	Gas
Mesaverde	7,150	Gas

4. PROPOSED CASING PROGRAM

All casing used to drill this well will be new casing.

Type	<u>Size</u>	Weight	<u>Grade</u>	Conn.	<u>Top</u>	<u>Bottom</u>	<u>Hole</u>
Surface	13-3/8"	48.0 ppf	H-40	STC	0,	500'	17-1/2"
Intermediate	9-5/8"	36.0 ppf	J-55	LTC	0,	2,800	12-1/4"
Production	5-1/2"	17.0 ppf	MAV-80	LTC	0.	8,050	7-7/8"

5. OPERATOR'S MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL

Surface hole: No BOPE will be utilized.

Intermediate hole: To be drilled using a diverter stack with rotating head to divert flow from rig floor.

<u>Production hole</u>: Prior to drilling out the intermediate casing shoe, 3,000 psi or greater BOP equipment will be installed. The pipe rams will be operated at least once per day from intermediate casing to total depth. The blind rams will be tested once per day from intermediate casing to total depth if operations permit.

DRILLING PLAN

APPROVAL OF OPERATIONS

A diagram of the planned BOP equipment for normal drilling operations in this area is attached. As denoted there will be two valves and one check valve on the kill line, two valves on the choke line, and two adjustable chokes on the manifold system. The BOP "stack" will consist of two BOP rams (1 pipe, 1 blind) and one annular type preventer, all rated to a minimum of 3,000 psi working pressure.

The BOP equipment will be pressure tested prior to drilling below the intermediate casing shoe. All test pressures will be maintained for fifteen (15) minutes without any significant pressure decrease. Clear water will be circulated into the BOP stack and lines prior to pressure testing. The following test pressures will be used as a minimum for various equipment items.

1.	Annular BOP	1,500 psi
2.	Ram type BOP	3,000 psi
3.	Kill line valves	3,000 psi
4.	Choke line valves and choke manifold valves	3,000 psi
5.	Chokes	3,000 psi
6.	Casing, casinghead & weld	1,500 psi
7.	Upper kelly cock and safety valve	3,000 psi
8.	Dart valve	3,000 psi

MUD SYSTEMS

- An air or an air/mist system may be used to drill to drill the surface hole until water influx becomes too great.
- KCL mud system will be used to drill well.

Depths	Mud Weight (ppg)	Mud System
0' - 500'	8.4	Air foam mist, no pressure control
500' - 2.800'	8.6	Fresh water, rotating head and diverter
2.800' - 8.050'	8.6	Fresh water/2% KCL/KCL mud system

7. BLOOIE LINE

- An automatic igniter will not be installed on blooie line. The blooie will have a contant ignition source.
- A "target tee" connection will be installed on blooic line for 90° change of directions for abrasion resistance.
- "Target tee" connections will be a minimum of 50' from wellhead.
- The blooie line discharge will be a minimum of 100' from the wellhead.

AUXILIARY EQUIPMENT TO BE USED 8.

- a. Kelly cock.
- b. Full opening valve with drill pipe connection will be kept on floor. Valve will be used when the kelly is not in string.

TESTING. LOGGING, AND CORING PROGRAMS TO BE FOLLOWED 9.

- A drillstem test in the Wasatch Tongue is possible.
- One electric line wire-log will be run from total depth to intermediate casing.
- The gamma ray will be left on to record from total depth to intermediate casing.
- Other log curves (resistivities, porosity, and caliper) will record from total depth to intermediate casing.
- A dipmeter, percussion cores, or rotary cores may be run over selected intervals.

ANTICIPATED ABNORMAL PRESSURES OR TEMPERATURES EXPECTED

- Expected BHP 1,500-2,000 psi (lower than normal pressure gradient).
- No abnormal temperature or pressures are anticipated.
- The formations to be penetrated do not contain known H2S gas.

11. WATER SUPPLY

- No water pipelines will be laid for this well.
- No water well will be drilled for this well.
- Drilling water for this will be hauled on the road(s) shown in Attachment No. 3.
- Water will be hauled from: Water Permit # 43-10447 Section 9, Township 8 South, Range 20 East

DRILLING PLAN

APPROVAL OF OPERATIONS

CEMENT SYSTEMS 12.

Surface Cement:

Drill 17-1/2" hole to 500' and cement 13-3/8" to surface with 450 sks class "C" cement with 2% CaCl2 and 1/4 #/sk. Poly-E-Flakes (volume includes 40% excess). Top out if necessary with Top Out cement listed below.

- Intermediate Casing Cement:
 - Drill 12-1/4" hole to 2,800'±, run and cement 9-5/8" to surface.
 - Pump 20 bbls lightly weighted water spacer followed by 5 bbls fresh water. Displace with any available water.
 - Casing to be run with: a) guide shoe b) insert float c) three (3) centralizers, one on each of first 3 joints d) stop ring for plug two joints off bottom e) bottom three joints thread locked f) pump job with bottom plug only.

Cement to surface not required due to surface casing set deeper than normal.

					<u>Hole</u>	Cement	
<u>Type</u> Lead Tail	<u>Sacks</u> 300 390	Interval 0'-2,000' 2,000'-2,800'	Density 11.0 ppg 15.6 ppg	<u>Yield</u> 3.82 CFS 1.20 CFS	<u>Volume</u> 658 CF 268 CF	<u>Volume</u> 1,152 CF 469 CF	Excess 75% 75%
1 411	370	- ,000,					

Lead Mix:

Halliburton Prem Plus V blend. Blend includes Class "C" cement, gel, salt, gilsonite, EX-1 and HR-7.

Slurry yield:

Slurry weight: 3.82 cf/sack

11.00 #/gal.

Water requirement: 22.95 gal/sack Compressives @ 130°F: 157 psi after 24 hours

Tail Mix:

Class "G" Cement, 1/4 lb/sk Cellophane Flakes + 2% bwoc Calcium Chloride + 44.3% fresh water.

1 hr. 5 min. (a) 90 °F. Pump Time: Compressives @, 95 °F: 24 Hour is 4,700 psi

- c. Production Casing Cement:
 - Drill 7-7/8" hole to 8,050'±, run and cement 5 1/2".
 - Cement interface is at 3,700', which is typically 500'-1,000' above shallowest pay.
 - Pump 20 bbl Mud Clean II unweighted spacer, followed by 20 Bbls fresh H20 spacer.
 - Displace with 3% KCL.

					11016	Comone	
Type	Sacks	Interval	Density	Yield Yield	<u>Volume</u>	Volume	<u>Excess</u>
Lead	90	3,7 00'-4,5 00'	11.5 ppg	3.12 CFS	139 CF	277 CF	100%
Tail	600	4.500'-8.050	13.0 ppg	1.75 CFS	525 CF	1050 CF	100%

Note: Caliper will be run to determine exact cement volume.

Lead Mix:

Halliburton Prem Plus V blend. Blend includes Class "C" cement, gel, salt, gilsonite, EX-1 and HR-7.

3.12 cf/sack

Slurry weight:

Hala

11.60 #/gal.

Cement

Slurry yield: Water requirement:

17.71 gal/sack

Compressives @ 130°F: 157 psi after 24 hours

Tail Mix:

Halliburton HLC blend (Prem Plus V/JB flyash). Blend includes Class "G" cement, KCl, EX-1, Halad 322,

& HR-5.

1.75 cf/sack

Slurry weight:

13.00 #/gal.

Slurry yield:

9.09 gal/sack

Water requirement: Compressives @ 165°F: 905 psi after 24 hours

13. ANTICIPATED STARTING DATE AND DURATION OF THE OPERATIONS

Starting Date:

January 01, 2005


Duration:

14 Days





HCU 14-34F UINTAH COUNTY UTAH



Ryan Energy Planning Report



Field: UTAH

Map System: US State Plane Coordinate System 1983

Geo Datum: GRS 1980 Sys Datum: Mean Sea Level Map Zone:

Coordinate System: Geomagnetic Model: Utah, Central Zone

1

Page:

Site Centre igrf2000

Site: **UINTAH COUNTY**

Site Position: Geographic From: Position Uncertainty:

Northing: Easting:

7266643.10 ft 2233340.22 ft Latitude: Longitude: North Reference: Grid Convergence:

Slot Name:

40 14 58.000 N 109 22 32.000 W

True 1.36 deg

Well: HCU 14-34F

Position Uncertainty:

Ground Level:

Well Position:

+N/-S 0.00 ft Northing: 0.00 ft Easting:

0.00 ft

0.00 ft

0.00 ft

7266643.10 ft 2233340.22 ft

Latitude: Longitude:

Drilled From:

Tie-on Depth:

Above System Datum:

58.000 N 40 14 109 22 32.000 W

Surface

Wellpath: ORIGINAL HOLE

SITE Current Datum: Magnetic Data: 7/8/2004 Field Strength: Vertical Section:

53343 nT Depth From (TVD)

8050.00

0.00 ft Height +N/-S

Declination: Mag Dip Angle: +E/-W ft ft 0.00 0.00

0.00 ft Mean Sea Level 12.23 deg 66.34 deg Direction deg

264.63

Plan Section Information

	(1)(3) (1)(2)(3)	45m 667	TVD T			ings S Tagsis Madigiji	e dealaí Reguladon	《美国教育》	TFO deg	Target
0.00	0.00	264.63	0.00	0.00	0.00	0.00	0.00	0.00	0.00	<u></u>
550.00	0.00	264.63	550.00	0.00	0.00	0.00	0.00	0.00	0.00	
1148.50	24.00	264.63	1131.15	-11.56	-122.99	4.01	4.01	0.00	264.63	
3799.05	24.00	264.63	3552.55	-112.45	-1196.33	0.00	0.00	0.00	0.00	
4599.05	0.00	264.63	4329.36	-127.91	-1360.72	3.00	-3.00	0.00	180.00	
4599.69	0.00	264.63	4330.00	-127.91	-1360.72	0.00	0.00	0.00	0.00	TARGET2
8319.69	0.00	264.63	8050.00	-127.91	-1360.72	0.00	0.00	0.00	264.63	

SURFACE USE PLAN

CONDITIONS OF APPROVAL

Attachment for Permit to Drill

Name of Operator:

Dominion Exploration & Production

Address:

14000 Quail Springs Parkway, Suite 600

Oklahoma City, OK 73134

Well Location:

HCU 14-34F

SHL: 829' FSL & 1958' FEL Section 34-10S-20E 700' FSL & 1950' FWL Section 34-10S-20E BHL:

Uintah County, UT

The dirt contractor will be provided with an approved copy of the surface use plan of operations before initiating construction.

The onsite inspection for the referenced well was conducted on Friday, July 25, 2004 at approximately 12:50 pm. In attendance at the onsite inspection were the following individuals:

Ken Sechrest

Foreman

Dominion E & P, Inc.

Kermit Wapsock

Oil and Gas Technician

Energy and Minerals

Kim Fritz

Environmental Protection Spec.

Uintah & Ouray Agency - BIA

David Weston Harley Jackson Professional Engineer

Uintah Engineering and Land Surveying

Foreman

Jackson Construction

Erik LaRose

Foreman

LaRose Construction

Don Hamilton

Permitting Agent

Buys & Associates, Inc.

1. **Existing Roads:**

- The proposed well site is located approximately 13.18 miles southeast of Ouray, UT. a.
- Directions to the proposed well site have been attached at the end of Exhibit B. b.
- The use of roads under State and County Road Department maintenance are necessary to c. access the Hill Creek Unit. However, an encroachment permit is not anticipated since no upgrades to the State or County Road system are proposed at this time.
- All existing roads will be maintained and kept in good repair during all phases of operation. d.
- Vehicle operators will obey posted speed restrictions and observe safe speeds commensurate e. with road and weather conditions.
- Since no improvements are anticipated to the State, County, Tribal or BLM access roads no f. topsoil striping will occur.
- An off-lease federal Right-of-Way is not anticipated for the access road or utility corridor g. since both are located within the existing federal unit boundary.

2. Planned Access Roads:

- From the proposed HCU 16-34F an access is proposed trending east approximately 1,020' to a. the proposed well site. The access consists of entirely new disturbance and crosses no drainages. A road design plan is not anticipated at this time.
- The proposed access road will consist of a 14' travel surface within a 30' disturbed area. b.
- Proposed access will utilize entirely Ute Indian Tribe lands in which a right-of-way is being c. approved at this time. BLM approval to construct and utilize the proposed access road is requested with this application.
- A maximum grade of 10% will be maintained throughout the project with no cuts and fills d. required to access the well.
- No turnouts are proposed since the access road is only 1,020' long and adequate site distance e. exists in all directions.
- No culverts are anticipated. Adequate drainage structures will be incorporated into the road. f.
- No surfacing material will come from federal or Indian lands. g.
- No gates or cattle guards are anticipated at this time. h.
- Surface disturbance and vehicular travel will be limited to the approved location access road. i.
- All access roads and surface disturbing activities will conform to the standards outlined in the j. Bureau of Land Management and Forest Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, (1989).
- The operator will be responsible for all maintenance of the access road including drainage k. structures.

3. Location of Existing Wells:

Following is a list of existing wells within a one mile radius of the proposed well: a.

> None i. Water wells ii. Injection wells None

None

iii. Disposal wells

iv. Drilling wells None

v. Temp. shut-in wells None vi. Producing wells 2

Abandon wells vii.

b. Exhibit B has a map reflecting these wells within a one mile radius of the proposed well.

Location of Production Facilities: 4.

All permanent structures will be painted a flat, non-reflective Desert Brown to match the a. standard environmental colors. All facilities will be painted within six months of installation. Facilities required to comply with the Occupational Safety and Health Act (OSHA) may be excluded.

- b. Site security guidelines identified in 43 CFR 3163.7-5 and Onshore Oil and Gas Order No. 3 will be adhered to.
- c. A gas meter run will be constructed and located on lease within 500 feet of the wellhead. Meter runs will be housed and/or fenced. All gas production and measurement shall comply with the provisions of 43 CFR 3162. 7-3, Onshore Oil and Gas Order No. 5, and American Gas Association (AGA) Report No. 3.
- d. A tank battery will be constructed on this lease, it will be surrounded by a dike of sufficient capacity to contain the storage capacity of the largest tank. All loading lines and valves will be placed inside the berm surrounding the tank battery. All liquid hydrocarbons production and measurement shall conform to the provisions of 43 CFR 3162.7-3 and Onshore Oil and Gas Order No. 4 and Onshore Oil and Gas Order No. 5 for natural gas production and measurement.
- e. Any necessary pits will be properly fenced to prevent any wildlife and livestock entry.
- f. All access roads will be maintained as necessary to prevent erosion and accommodate year-round traffic. The road will be maintained in a safe useable condition.
- g. The site will require periodic maintenance to ensure that drainages are kept open and free of debris, ice, and snow, and that surfaces are properly treated to reduce erosion, fugitive dust, and impacts to adjacent areas.
- h. A gas pipeline is associated with this application and is being applied for at this time. The proposed gas pipeline corridor will leave the southeast side of the well site and traverse 1,020' east to the proposed 4" pipeline corridor at the HCU 16-34F.
- i. The gas pipeline will be a 4" steel surface line within a 20' wide utility corridor. The use of the proposed well site and access roads will facilitate the staging of the pipeline construction.

 A new pipeline length of approximately 1,020' is associated with this well.
- j. Dominion intends on installing the pipeline on the surface by welding many joints into long lengths, dragging the long lengths into position and then completing a final welding pass to join the long lengths together. Dominion intends on connecting the pipeline together utilizing conventional welding technology.

5. <u>Location and Type of Water Supply:</u>

a. The location and type of water supply has been addressed as number 11 within the previous drilling plan information.

6. Source of Construction Material:

- a. The use of materials will conform to 43 CFR 3610.2-3.
- b. No construction materials will be removed from Ute Tribal or BLM lands.
- c. If any gravel is used, it will be obtained from a state approved gravel pit.

7. Methods of Handling Waste Disposal:

- a. All wastes associated with this application will be contained and disposed of utilizing approved facilities.
- b. Drill cuttings will be contained and buried on site.
- c. The reserve pit will be located outboard of the location and along the southwest side of the pad.
- d. The reserve pit will be constructed so as not to leak, break, or allow any discharge.
- e. The reserve pit will be lined with 12 mil minimum thickness plastic nylon reinforced liner material. The liner will overlay a felt liner pad only if rock is encountered during excavation. The pit liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. Pit walls will be sloped no greater than 2:1. A minimum 2-foot freeboard will be maintained in the pit at all times during the drilling and completion operation.
- f. The reserve pit has been located in cut material. Three sides of the reserve pit will be fenced before drilling starts. The fourth side will be fenced as soon as drilling is completed, and shall remain until the pit is dry. After the reserve pit has dried, all areas not needed for production will be rehabilitated.
- g. No chemicals subject to reporting under SARA Title III (hazardous materials) in an amount greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completion of the well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling, testing, or completion of the well.
- h. Trash will be contained in a trash cage and hauled away to an approved disposal site as necessary but no later than at the completion of drilling operations. The contents of the trash container will be hauled off periodically to the approved Uintah County Landfill near Vernal, Utah.
- i. Produced fluids from the well other than water will be produced into a test tank until such time as construction of production facilities is completed. Any spills of oil, gas, salt water or other produced fluids will be cleaned up and removed.
- j. After initial clean-up, a 400 bbl tank will be installed to contain produced waste water. This water will be transported from the tank to an approved Dominion disposal well for disposal.
- k. Produced water from the production well will be disposed of at the RBU 13-11F or RBU 16-19F disposal wells in accordance with Onshore Order #7.
- 1. Any salts and/or chemicals, which are an integral part of the drilling system, will be disposed of in the same manner as the drilling fluid.
- m. Sanitary facilities will be on site at all times during operations. Sewage will be placed in a portable chemical toilet and the toilet replaced periodically utilizing a licensed contractor to transport by truck the portable chemical toilet so that its contents can be delivered to the Vernal Wastewater Treatment Facility in accordance with state and county regulations.

8. Ancillary Facilities:

a. Garbage Containers and Portable Toilets are the only ancillary facilities proposed in this application.

9. Well Site Layout: (See Exhibit B)

- a. The well will be properly identified in accordance with 43 CFR 3162.6.
- b. Access to the well pad will be from the southeast.
- c. The pad and road designs are consistent with BLM and Tribal specification
- d. A pre-construction meeting with responsible company representative, contractors, Tribal Representatives and the BLM will be conducted at the project site prior to commencement of surface-disturbing activities. The pad and road will be construction-staked prior to this meeting.
- e. The pad has been staked at its maximum size of 355' X 200'; however it will be constructed smaller if possible, depending upon rig availability. Should the layout change, this application will be amended and approved utilizing a sundry notice.
- f. All surface disturbing activities, will be supervised by a qualified, responsible company representative who is aware of the terms and conditions of the APD and specifications in the approved plans.
- g. All cut and fill slopes will be such that stability can be maintained for the life of the activity.
- h. Diversion ditches will be constructed as shown around the well site to prevent surface waters form entering the well site area.
- i. The site surface will be graded to drain away from the pit to avoid pit spillage during large storm events.
- j. The stockpiled topsoil (first 6 inches or maximum available) will be stored in a windrow on the uphill side of the location to prevent any possible contamination. All topsoil will be stockpiled for reclamation in such a way as to prevent soil loss and contamination.
- k. Pits will remain fenced until site cleanup.
- The existing range fence that presently crosses the proposed well pad will be rerouted to the south to avoid the well pad.
- m. The blooie line will be located at least 100 feet from the well head.
- n. Water injection may be implemented if necessary to minimize the amount of fugitive dust.

10. Plans for Restoration of the Surface:

- a. Site reclamation for a producing well will be accomplished for portions of the site not required for the continued operation of the well.
- b. The Operator will control noxious weeds along access road use authorizations, pipeline route

authorizations, well sites, or other applicable facilities by spraying or mechanical removal. A list of noxious weeds may be obtained from the BLM or the appropriate County Extension Office. On Ute Tribal and BLM administered land, it is required that a Pesticide Use Proposal be submitted and approved prior to the application of herbicides, pesticides or possibly hazardous chemicals.

- c. Upon well completion, any hydrocarbons in the pit shall be removed in accordance with 43 CFR 3162.7-1. Once the reserve pit is dry, the plastic nylon reinforced liner shall be torn and perforated before backfilling of the reserve pit. The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours.
- d. The cut and fill slopes and all other disturbed areas not needed for the production operation will be top soiled and re-vegetated. The stockpiled topsoil will be evenly distributed over the disturbed area.
- e. Prior to reseeding the site, all disturbed areas, including the access road, will be scarified and left with a rough surface. The site will then be seeded and/or planted as prescribed by the BIA. The BIA recommended seed mix will be detailed within their approval documents.

11. Surface and Mineral Ownership:

- a. Surface Ownership Ute Indian Tribe under the management of the Bureau of Indian Affairs Uintah and Ouray Agency, P.O. Box 130, 988 South 7500 East, Ft. Duchesne, Utah 84026
- b. Mineral Ownership Federal under the management of the Bureau of Land Management Vernal Field Office, 170 South 500 East, Vernal, Utah 84078; 435-781-4400.

12. Other Information:

- a. AIA Archaeological has conducted a Class III archeological survey. A copy of the report has been submitted under separate cover to the appropriate agencies by AIA Archaeological.
- b. Our understanding of the results of the onsite inspection are:
 - a. No Threatened and Endangered flora and fauna species were found during the onsite inspection.
 - b. No drainage crossings that require additional State or Federal approval are being crossed.


13. Operator's Representative and Certification


Title	Name	Office Phone
Company Representative (Roosevelt)	Mitchiel Hall	1-435-722-4521
Company Representative (Oklahoma)	Carla Christian	1-405-749-5263
Agent for Dominion	Don Hamilton	1-435-637-4075

Certification:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exists; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Dominion Exploration & Production, Inc. and its contractors and subcontractors in conformity with this APD package and the terms and conditions under which it is approved. I also certify responsibility for the operations conducted on that portion of the leased lands associated with this application, with bond coverage being provided under Dominion's BLM bond. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Signature: Don Hamilton Date: 8-2-2004





DOMINION EXPLR. & PROD., INC.

HCU #15-34F & HCU #14-34F LOCATED IN UINTAH COUNTY, UTAH SECTION 34, T10S, R20E, S.L.B.&M.




PHOTO: VIEW FROM CORNER #5 TO LOCATION STAKES

CAMERA ANGLE: NORTHEASTERLY




PHOTO: VIEW FROM BEGINNING OF PROPOSED ACCESS **FOR THE HCU #16-34F**

CAMERA ANGLE: SOUTHERLY





Uintah Engineering & Land Surveying S South 200 East Vernal, Utah 84078 435-789-1017 uels@uelsinc.com


LOCATION PHOTOS


MONTH DAY TAKEN BY: B.B. | DRAWN BY: P.M. | REVISED: 00-00-00

РНОТО










DOMINION EXPLR. & PROD., INC. HCU #15-34F & HCU #14-34F SECTION 34, T10S, R20E, S.L.B.&M.


PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 14.0 MILES TO THE JUNCTION OF STATE HIGHWAY 88; EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 17.0 MILES TO OURAY, UTAH; PROCEED IN A SOUTHERLY, THEN SOUTHEASTERLY DIRECTION APPROXIMATELY 13.5 MILES ON THE SEEP RIDGE ROAD TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN RIGHT AND PROCEED IN A SOUTHWESTERLY, THEN NORTHWESTERLY DIRECTION APPROXIMATELY 2.4 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN LEFT AND PROCEED IN A SOUTHWESTERLY, THEN SOUTHERLY DIRECTION APPROXIMATELY 0.7 MILES TO THE BEGINNING OF THE PROPOSED ACCESS FOR THE HCU #16-34F TO THE SOUTH; FOLLOW ROAD FLAGS IN A SOUTHERLY DIRECTION APPROXIMATELY 0.25 MILES TO THE BEGINNING OF THE PROPOSED ACCESS TO THE SOUTHWEST; FOLLOW ROAD FLAGS IN A SOUTHWESTERLY, THEN NORTHWESTERLY DIRECTION APPROXIMATELY 0.2 MILES TO THE PROPOSED LOCATION.

TOTAL DISTANCE FROM VERNAL, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 48.05 MILES.




\FLOWISCP

BOP STACK




CHOKE MANIFOLD



WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 08/04/2004	API NO. ASSIGNED: 43-047-35875
AID RECEIVED. 00/04/2004	AFI NO. ASSIGNED: 43-047-33875
WELL NAME: HCU 14-34F	
OPERATOR: DOMINION EXPL & PROD (N1095)	
CONTACT: DON HAMILTON	PHONE NUMBER: 435-650-1886
PROPOSED LOCATION: SWSE 34 100S 200E SURFACE: 0829 FSL 1958 FEL SUBOTTOM: 0700 FSL 1950 FWL UINTAH NATURAL BUTTES (630) LEASE TYPE: 1 - Federal LEASE NUMBER: U-79130 SURFACE OWNER: 2 - Indian PROPOSED FORMATION: MVRD	INSPECT LOCATN BY: / / Tech Review Initials Date Engineering Geology Surface LATITUDE: 39.89901 LONGITUDE: 109.64828
COALBED METHANE WELL? NO	LONGITUDE: 109.64828
Plat Bond: Fed[1] Ind[] Sta[] Fee[] (No. 76S630500330) Potash (Y/N) Oil Shale 190-5 (B) or 190-3 or 190-13 Water Permit (No. 43-10447) RDCC Review (Y/N) (Date:) Fee Surf Agreement (Y/N)	LOCATION AND SITING: R649-2-3. Unit HILL CREEK R649-3-2. General Siting: 460 From Qtr/Qtr & 920' Between Wells R649-3-3. Exception Drilling Unit Board Cause No: 197-// Eff Date: \$-/2-00 Siting: Suspends General Other R649-3-11. Directional Drill
STIPULATIONS: 1- Edera C 2- DIL S	Leprova O



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office P.O. Box 45155 Salt Lake City, Utah 84145-0155

IN REPLY REFER TO: 3160 (UT-922)

August 10, 2004

Memorandum

To: Assistant District Manager Minerals, Vernal District

From: Michael Coulthard, Petroleum Engineer

Subject: 2004 Plan of Development Hill Creek Unit

Uintah County, Utah.

Pursuant to email between Diana Whitney, Division of Oil, Gas and Mining, and Mickey Coulthard, Utah State Office, Bureau of Land Management, the following wells are planned for calendar year 2004 within the Hill Creek Unit, Uintah County, Utah.

API# WELL NAME LOCATION

(Proposed PZ Mesaverde)

43-047-35870 HCU 13-32F Sec 32 T10S R20E 0740 FSL 2231 FWL BHL Sec 32 T10S R20E 0800 FSL 0600 FWL

43-047-35872 HCU 14-32F Sec 32 T10S R20E 0720 FSL 2216 FWL

43-047-35873 HCU 3-32F Sec 32 T10S R20E 0617 FNL 2459 FWL

43-047-35874 HCU 11-32F Sec 32 T10S R20E 2350 FNL 2508 FWL BHL Sec 32 T10S R20E 1950 FSL 1650 FWL

43-047-35871 HCU 12-32F Sec 31 T10S R20E 2080 FNL 0855 FEL BHL Sec 32 T10S R20E 2300 FSL 0600 FWL

43-047-35875 HCU 14-34F Sec 34 T10S R20E 0829 FSL 1958 FEL BHL Sec 34 T10S R20E 0700 FSL 1950 FWL

This office has no objections to permitting the wells at this time.

/s/ Michael L. Coulthard

Dominion Exploration & Production, Inc. 14000 Quail Springs Parkway, #600, Oklahoma City, OK 73134-2600



Attn: Diana Whitney

Utah Division of Oil, Gas & Mining 1594 West North Temple, Suite 1210 Salt Lake City, Utah 84114-5801

Reference:

Exception to Location & Sitting of Well

HCU 14-34F, Surface Location 829' FSL & 1958' FEL, Sec.34-10S-20E

Bottom Location 700' FSL & 1950' FWL, Sec. 34-10S-20E

Uintah County, Utah

Dear Ms. Whitney:

Dominion Exploration & Production, Inc. is requesting an exception to Rule 649-3-11, for the above referenced well, due to the directional drilling. Dominion Exploration & Production, Inc. is the only owner within a 460' radius from all points along the intended well bore.

If you should require additional information please feel free to contact me at (405) 749-5263.

Sincerely,

Dominion Exploration & Production, Inc.

Mustian

Carla Christian

Regulatory Specialist

Enclosure

RECEIVED
AUG 1 3 2004

DIV. OF OIL, GAS & MINING



State of Utah

Department of Natural Resources

ROBERT L. MORGAN Executive Director

Division of Oil, Gas & Mining

LOWELL P. BRAXTON
Division Director

OLENE S. WALKER
Governor

GAYLE F. McKEACHNIE
Lieutenant Governor

August 17, 2004

Dominion Exploration & Production, Inc 14000 Quail Springs Parkway, Suite 600 Oklahoma City, OK 73134

Re:

Hill Creek Unit 14-34F Well, Surface Location 829' FSL, 1958' FEL, SW SE, Sec. 34, T. 10 South, R. 20 East, Bottom Location 700' FSL, 1950' FWL, SE SW, Sec. 34, T. 10 South, R. 20 East, Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. § 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-35875.

Sincerely,

John R. Baza Associate Director

pab Enclosures

cc: Uintah County Assessor

Bureau of Land Management, Vernal District Office

Operator:	Dominion Exploration & Production, Inc				
Well Name & Number	Hill Creek Unit 14-34F				
API Number:	43-047-35875				
Lease:	U-79130				
Surface Location: SW SE	Sec. 34 T. 10 South R. 20 East				
Bottom Location: SE SW	Sec. 34 T. 10 South R. 20 East				

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

Contact Carol Daniels at (801) 538-5284.

Notify the Division prior to commencing operations to plug and abandon the well.

• Contact Dan Jarvis at (801) 538-5338

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- 4. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.
- 5. In accordance with Utah Admin. R.649-3-11, Directional Drilling, the operator shall submit a complete angular deviation and directional survey report to the Division within 30 days following completion of the well.
- 6. In accordance with Order in Cause No. 190-5(b) dated October 28, 1982, the Operator shall comply with requirements of Rules R649-3-31 and R649-3-27 pertaining to Designated Oil Shale Areas. Additionally, the operator shall ensure that the surface and/or production casing is properly cemented over the entire oil shale interval as defined by Rule R649-3-31. The Operator shall report the actual depth the oil shale is encountered to the Division.

Form 3160-	-3
(December	1990)

SUBMIT IN TRIPLICATE*

Form approved. Budget Bureau No. 1004-0136 Expires: December 31, 1991

_	_	
n	Λ	77
	11	1
**	* *	

EASE DESIGNATION AND SERI	AL NO
U-79130	

V V I	BUR	U-79130					
`	APPLICATION I	OR PERMIT	TO DRILL OF	R DEEPEN		6. IF INDIAN, ALLOTTEE O Ute Indian Trib	
Ia. TYPE OF WORK	DRILL 🗓	DEEPI	en 🗆		-	7. UNIT AGREEMENT NAM Hill Creek Uni	t
b. TYPE OF WELL OIL WELL	GAS WELL 🔯 OTHER		SINGLE ZONE	MULTIPLE TO D		8. FARM OR LEASE NAME, HCU 14-34F	WELL NO.
2. NAME OF OPERATOR DO	ominion Exploration &	Production, Inc.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	AUG - 3 2004	Transport and the control of the con	9. API WELL NO. 43.647.3	35875
3. ADDRESS AND TELE	000 Quail Springs Par	kway, Suite 600,	Oklahoma City, OK	-	2 <u>63</u> _	10. Field and pool, or w Natural Buttes	/ILDCAT
LOCATION OF WELL At surface At proposed prod. zone	(Report location clearly and in accord	lance with any State required 1,958' FEL	SW/4 SE/4			Section 34,	
	700' FSL, s and direction from neare	1,950' FWL EST TOWN OR POST OFFI	SE/4 SW/4			T10S, R20E, S	LB&M 13. STATE
	13.18 miles	southeast of Our	ray, Utah			Uintah	Utah
15. DISTANCE FROM PR LOCATION TO NEAR PROPERTY OR LEAS (Also to nearest drig. un	ROPOSED* REST SE LINE, FT.		16. NO. OF ACRES IN LEASE		то тні	ACRES ASSIGNED S WELL ACRES	
18. DISTANCE FROM PR LOCATION TO NEAL DRILLING, COMPLE APPLIED FOR, ON TI	OPOSED REST WELL, ETED, OR		19. PROPOSED DEPTH		20. ROTARY	OR CABLE TOOLS	,
25						APPROX DATE WORK WILLS	START*
5,340' GR						January 1, 2005	
23.			ING AND CEMENTING	PROGRAM			
SIZE OF HOLE GRADE, SIZE OF CASING WEIGHT PER FO			T SETTING DEPTH		QUANTITY OF CEMENT		
17-1/2"	13-3/8" H-40 ST&C	3-3/8" H-40 ST&C 48#		450 sks "C" Cement with additives (see Drilling Plan)			
12-1/4"	9-5/8" J-55 LT&C	36#	2,800'	300 sacks Lead and 390 sacks Tail (see Drilling Plan)			
7-7/8"	5-1/2" Mav-80 LT&C	17#	8,050'	90 sacks Lead and 600 s	acks Tail (se	ee Drilling Plan)	

Bond Information:

Bond coverage is provided by Travelers Casualty and Surety Company of America, Bond #76S 63050 0330

Other Information:

Drilling Plan and Surface Use Plan are attached.

Dominion requests that this complete application for permit to drill be held confidential.

RECEIVED APR 0 1 2005

DIV. OF OIL, GAS & MINING ORIGINAL

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any

24.	SIGNED Don	Hamilton	Don Hamilton	TITLE	Agent for Dominion	DATE_	August 2, 2004	
_	(This space for Federal	or State office use)						
	PERMIT NO.				APPROVAL DATE			_
	Application approva	al does not warrant or co	1/pareno7	is legal or eq	uitable title to those rights in the subject leas	e which would entitle	the applicant to conduct operations the applicant to conduct operations the conduct operations the applicant to the applicant to conduct operations the applicant to conduct operations the applicant to conduct operations the applicant to conduct to the applicant to conduct to conduct to conduct to the applicant to conduct to	

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency or the

UDOGM

COAs Page 1 of 6 Well No.: HCU 14-34F

CONDITIONS OF APPROVAL APPLICATION FOR PERMIT TO DRILL

Company/Operator:

Dominion E&P Inc.

Well Name & Number: Hill Creek Unit 14-34F

API Number:

43-047-35875

Lease Number:

U-79130

Location:

<u>SESW</u> Sec. <u>34</u> T.<u>10S</u> R. <u>20E</u>

Agreement:

River Bend Unit

For more specific details on notification requirements, please check the Conditions of Approval for Notice to Drill and Surface Use Program.

CONDITIONS OF APPROVAL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

A. <u>DRILLING PROGRAM</u>

1. <u>Estimated Depth at Which Oil, Gas, Water, or Other Mineral Bearing Zones are Expected to be</u>
Encountered

Report <u>ALL</u> water shows and water-bearing sands to John Mayers of this office **prior to setting the next casing string or requesting plugging orders**. Faxed copies of State of Utah form OGC-8-X are acceptable. If noticeable water flows are detected, submit samples to this office along with any water analyses conducted.

All usable water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

COAs Page 2 of 6 Well No.: HCU 14-34F

2. <u>Pressure Control Equipment</u>

The BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No. 2 for equipment and testing requirements, procedures, etc., for a <u>3M</u> system and individual components shall be operable as designed. Chart recorders shall be used for all pressure tests.

Test charts, with individual test results identified, shall be maintained on location while drilling and shall be made available to a BLM representative upon request.

3. <u>Casing Program and Auxiliary Equipment</u>

All waiting on cement times must be adequate to achieve 500 psi compressive strength at the casing shoe prior to drilling out.

4. <u>Mud Program and Circulating Medium</u>

None

5. Coring, Logging and Testing Program

A cement bond log (CBL) will be run from the production casing shoe to the top of cement or the intermediate casing shoe which ever is deeper. The CBL shall be utilized to determine the bond quality for the production casing

Please submit to this office, in LAS format, an electronic copy of all logs run on this well This submission will replace the requirement for submittal of paper logs to the BLM.

Daily drilling and completion progress reports shall be submitted to this office on a weekly basis.

6. Notifications of Operations

Operator shall report production data to MMS pursuant to 30 CFR 216.5 using form MMS/3160.

The date on which production is commenced or resumed will be construed for oil wells as the date on which liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which liquid hydrocarbons are first produced into a permanent storage facility, whichever first occurs; and, for gas wells as the date on which associated liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which gas is first measured through permanent metering facilities, whichever first occurs.

Should gas be vented or flared without approval beyond the authorized test period, the operator may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted and the operator shall be required to compensate the lessor for that portion of the gas vented or flared without approval which is determined to have been avoidably lost.

COAs Page 3 of 6 Well No.: HCU 14-34F

7. Other Information

All loading lines will be placed inside the berm surrounding the tank battery. All off-lease storage, off-lease measurement, or commingling onlease or off-lease will have prior written approval from the AO.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries and tested for meter accuracy at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with Onshore Oil & Gas Order No. 4 for liquid hydrocarbons and Onshore Oil & Gas Order No. 5 for natural gas measurement.

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2.

Section 102(b)(3) of the Federal Oil and Gas Royalty Management Act of 1982, as implemented by the applicable provisions of the operating regulations at Title 43 CFR 3162.4-1(c), requires that "not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160-5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed."

If you fail to comply with this requirement in the manner and time allowed, you shall be liable for a civil penalty of up to \$10,000 per violation for each day such violation continues, not to exceed a maximum of 20 days. See Section 109(c)(3) of the Federal Oil and Gas Royalty Management Act of 1982 and the implementing regulations at Title 43 CFR 3162.4-1(b)(5)(ii).

APD approval is valid for a period of one (1) year from the signature date. An extension period may be granted, if requested, prior to the expiration of the original approval period.

In the event after-hours approvals are necessary, you must contact one of the following individuals:

Kirk Fleetwood

(435) 828-7874

BLM FAX Machine (435) 781-4410

Petroleum Engineer

Michael Lee

(435) 828-7875

Petroleum Engineer

COAs Page 4 of 6 Well No.: HCU 14-34F

EPA'S LIST OF NONEXEMPT EXPLORATION AND PRODUCTION WASTES

While the following wastes are nonexempt, they are not necessarily hazardous.

Unused fracturing fluids or acids

Gas plant cooling tower cleaning wastes

Painting wastes

Oil and gas service company wastes, such as empty drums, drum rinsate, vacuum truck rinsate,

sandblast media, painting wastes, spend solvents, spilled chemicals, and waste acids

Vacuum truck and drum rinsate from trucks and drums, transporting or containing nonexempt waste

Refinery wastes

Liquid and solid wastes generated by crude oil and tank bottom reclaimers

Used equipment lubrication oils

Waste compressor oil, filters, and blowdown

Used hydraulic fluids

Waste solvents

Waste in transportation pipeline-related pits

Caustic or acid cleaners

Boiler cleaning wastes

Boiler refractory bricks

Incinerator ash

Laboratory wastes

Sanitary wastes

Pesticide wastes

Radioactive tracer wastes

Drums, insulation and miscellaneous solids.

COAs Page 5 of 6 Well No.: HCU 14-34F

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

Dominion Exploration and Production, Inc. (Dominion) will assure the Ute Tribe that any/all contractors and subcontractors have acquired a current Tribal Business License and have updated "Access Permits" prior to construction. All Dominion personnel, contractors and subcontractors will have these permits in their vehicles at all times. Companies that have not complied with this COA will be in violation of the Ute Tribal Business License Ordinance, and will be subject to fines and penalties.

Dominion employees, representatives, and/or authorized personnel (subcontractors) shall not carry firearms on their person or in their vehicles while working on the Uintah and Ouray Indian Reservation.

Dominion employees and/or authorized personnel (subcontractors) in the field will have approved applicable APDs and/or ROW permits/authorizations on their person(s) during all phases of construction.

Dominion will notify the Ute Tribe and Bureau of Indian Affairs (BIA) in writing of any requested modification of APDs or Rights-Of Way (ROW). Dominion shall receive written notification of authorization or denial of the requested modification. Without authorization, Dominion will be subject to fines and penalties.

The Ute Tribe Energy & Minerals Department shall be notified in writing 48 hours in advance of any construction activity. The Ute Tribal office is open Monday through Thursday. A Tribal Technician is to routinely monitor construction. Dominion shall make arrangements with the Ute Energy & Minerals Department for all monitoring that will exceed regular working hours for Tribal Technicians. A qualified archaeologist accompanied by a Tribal Technician will monitor any trenching construction of the pipeline.

A corridor ROW, 60 feet wide and 993 feet long shall be granted for the pipeline and for the new access road. The new access road, planned pipeline and pad shall be shared by both wells. The constructed, travel width of the access road will be limited to 18 feet. Upon authorization by the Ute Tribe Energy & Minerals Department, the ROW may be wider where sharp curves; deep cuts and fills occur; or, where intersections with other roads are required.

Culverts and diversion ditches will be placed and constructed where needed. Road base gravel will be used where sandy soils make roadways and the drilling location hazardous for access or drilling operations.

Upon completion of the pertinent APD and ROWs, Dominion will notify the Ute Tribe Energy & Minerals Department for a Tribal Technician to verify the Affidavit of Completion.

Production waters, oil, and other byproducts shall not be placed on access roads or the well pad.

COAs Page 6 of 6 Well No.: HCU 14-34F

All vehicular traffic, personnel movement, construction and restoration operations will be confined to the areas examined and approved and to the existing roadways and/or evaluated access routes.

Dominion will implement "Safety and Emergency Plan" and ensure plan compliance.

Dominion shall stop construction activities and notify personnel from the Ute Tribe Energy & Minerals Department and BIA if cultural remains including paleontology resources (vertebrate fossils) are exposed or identified during construction. The Ute Tribe Department of Cultural Rights and Protection and the BIA will provide mitigation measures prior to allowing construction.

Dominion employees and/or authorized personnel (subcontractors) will not be allowed to collect artifacts and paleontology fossils. No significant cultural resources shall be disturbed.

Dominion will control noxious weeds on the well site and ROWs. Dominion will be responsible for noxious weed control if weeds spread from the project area onto adjoining land.

Reserve pits will be lined with an impervious synthetic liner. A fence will be constructed around the reserve pit until it is backfilled. Prior to backfilling the reserve pit, all fluids will be pumped from the pit into trucks and hauled, to approved disposal sites. When the reserve pits are backfilled, the surplus oil and mud, etc., will be buried a minimum of 3 feet below the surface of the soil.

A closed system will be used during production. This means that production fluids will be contained in leak-proof tanks. All production fluids will be disposed of at approved disposal sites.

Surface pipelines will be constructed to lay on the soil surface. The pipeline portion of the ROW will not be bladed or cleared of vegetation without authorization of the BIA. Surface pipelines shall be welded in place at well sites or on access roads. They shall be pulled into place and assembled with suitable equipment. Vehicles shall not use pipeline ROWs as access roads unless specifically authorized.

Buried pipelines shall be buried a minimum of 3 feet below the soil surface. After construction is completed the disturbed area shall be contoured to blend into the natural landscape and be reseeded between September 15 and November 1 of the year following construction with perennial vegetation seed mixture provided by the BIA or Ute Tribe.

Before the site is abandoned, Dominion will be required to restore the well site and ROWs to near their original state. The disturbed areas will be reseeded with desirable perennial vegetation.

Soil erosion will be mitigated, by reseeding all disturbed areas.

UNITED TATES DEPARTMENT THE INTERIOR BUREAU OF LAND MANAGEMENT

	FORM APPROVED
	OMB No. 1004-0135
_	Expires: November 30, 2000

			E	крие	5. IN	ove
_		_	_			_
	~					

SUNDRY NOTICES AND REPORTS ON WELLS		U-79130	
Do not use this form for proposals to drill or to re-enter an		6. If Indian, Allottee or Tribe N	lame
abandoned well. Use Form 3160-3 (APD) for such proposals	S.		
LA CARACTERITATION IN TRANSPORTATION OF THE STATE OF THE		7. If Unit or CA/Agreement, N	ame and/or No.
1. Type of Well		Hill Creek Unit	
Oil Well X Gas Well Other CONCIDENTIA	Λı	8. Well Name and No.	
2. Name of Operator	4	UO1144 24E	
2. Ivanie of Operator		HCU 14-34F 9. API Well No.	
Dominion Exploration & Production, Inc.			
3a. Address Suite 600 3b. Phone No. (incl	, i	43-047-35875	
14000 Quail Springs Parkway, OKC, OK 73134 (405) 749-52 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	263	10. Field and Pool, or Explorate	ory Area
4. Document of Well (1 totalge, Sec., 1., R., W., of Survey Description)		Natural Buttes	
829' FSL & 1958' FEL,SW SE Sec. 34-10S-20E		11. County or Parish, State	
029 1 3L & 1930 FEL,3VV 3E 3eC. 34-103-20E	ļ	Uintah, UT	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF N	NOTICE, REPO	ORT OR OTHER DATA	
TYPE OF SUBMISSION TYPE	E OF ACTION	·	
X Notice of Intent Acidize Deepen	Production (St	tart/Resume) Water Shut-C	Off
Altering Casing Fracture Treat	. Reclamation	Well Integrity	
Subsequent Report Casing Repair New Construction	Recomplete	. Other	
X Change Plans Plug and Abandon	Temporarily At	bandon	
Final Abandonment Notice Convert to Injection Plug Back	. Water Disposa	al	
Describe Proposed or Completed Operation (clearly state all pertinent details, including estimate	ed starting date of ar	ny proposed work and approxima	te duration thereof
If the proposal is to deepen, directionally or recomplete, horizontally, give subsurface, locations Attach, the Bond under which the work will be performed or provide, the Bond No. on file with following, completion of the involved operations. If the operation results in a multiple completic testing, has been completed. Final Abandonment Notices shall be filed only after all requirer determined that the site is ready for final inspection.)	BLM/BIARequing or recompletion.ir ments, including reck	ed subsequent reports shall be fin a new interval, a Form 3160- amation, have been completed a	led within. 30 days 4 shall be. filed once and the operator has
Dominion would like to change the bottom hole location from 700' Section 34-10S-20E. Luw 615205X 39.8		WL, to 700' FSL & 212	0' FWL, 170',
BHL 44171554 -109.	10000		
1010 441 1193 -109.	652484		
	Į.	The state of the s	No.
	i co	TY SENT TO OPERATOR	1
		: 7-12-0=	
	Inili	_CHO	
4. I hereby certify that the foregoing is true and correct	Total Services	State of the second of the second second	
Name (Printed/Typed) Carla Christian	Title	Regulatory Specialist	
	Fine	regulatory opecialist	
Signature (Cula Wusham	Date	6/30/2005	
ET 336 TAGES DHIS SPACEFORFEDERAL OR STAT	0,00000000000	SD CONTRACTOR	
pproved by	mid		
conditions of approval, if any, are attached. Approval of this notice does not warrant or	Title		Date
ertify that the applicant holds legal or equitable title to those rights in the subject lease hich would entitle the applicant to conduct operations thereon.	Office		
itle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any per inited States any false, fictitious or fraudulent statements or representations as to any mat	rson knowingly an ter within its jurisd	d willfully to make to any dep diction.	artment or agency of the
Utah Division of	F	RECEIVED	
ou one and Mining	•	· U [1 / []]	

Oil, Gas and Mining

Federal Approval Of This Action is Necessary

JUL 0 5 2005

DIV. OF OIL, GAS & MINING



Ryan Energy Technologies **Planning Report**



Company: Dominion E & P

Field: **Natural Buttes Field** Site: HCU 14-34F

HCU 14-34F Well: Wellpath: Original Hole Date: 6/27/2005

Time: 13:41:52 Co-ordinate(NE) Referencite: HCU 14-34F, True North

Vertical (TVD) Referenceest. KB @ 5356' 0.0 Section (VS) Reference: Site (0.00N,0.00E,263.87Azi)

Plan: Plan #1

Field: **Natural Buttes Field**

Uintah County, Utah

USA

Map SystemUS State Plane Coordinate System 1983

Geo Datum GRS 1980 Sys Datum: Mean Sea Level Map Zone:

Utah, Central Zone

Coordinate System: Site Centre Geomagnetic Model:

igrf2005

HCU 14-34F

Hill Creek Unit Sec. 34, T10S, R20E

Site Position: From:

Ground Level:

Geographic Position Uncertainty:

0.00 ft 5338.00 ft Northing: 7141154.37 ft Easting: 2158987.89 ft

Latitude: Longitude: North Reference:

Slot Name:

39 34.409 N 109 39 4.220 W True

Grid Convergence:

109 39 1.18 deg

34.409 N

4.220 W

Well: HCU 14-34F

0.00 ft Surface Position: +N/-S 0.00 ft Position Uncertainty: 0.00 ft

Reference Point: +N/-S +E/-W

0.00

0.00 ft 0.00 ft

Easting: 2158987.89 ft Northing: 7141154.37 ft Easting: 2158987.89 ft

Height

Northing: 7141154.37 ft

Measured Depth: 0.00 ft Vertical Depth: 0.00 ft

Latitude: Longitude:

Latitude:

Longitude:

39 109 Inclination: Azimuth:

34.409 N 39 4.220 W 0.00 deg 0.00 deg

Well Ref. Point

Wellpath: Original Hole

Current Datum: est. KB @ 5356' 6/27/2005 Magnetic Data:

Field Strength:

52904 nT

Vertical Section: Depth From (TVD)

+N/-S ft 0.00

0.00 ft

Declination: Mag Dip Angle: +E/-W ft

Drilled From:

Tie-on Depth:

Above System Datum: Mean Sea Level 11.88 deg 65.92 deg

0.00 ft

Direction deg 263.87

Plan:

Plan #1

Date Composed:

6/27/2005

Principal: Yes

Version: Tied-to:

0.00

From Well Ref. Point

Plan Section Information

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	DLS deg/100	Build ft deg/100t	Turn it deg/1001	TFO t deg	Target
0.00	0.00	263.87	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
550.00	0.00	263.87	550.00	0.00	0.00	0.00	0.00	0.00	263.87	
1067.58	20.70	263.87	1056.39	-9.88	-91.97	4.00	4.00	0.00	263.87	
3845.38	20.70	263.87	3654.81	-114.82	-1068.38	0.00	0.00	0.00	0.00	
4535.49	0.00	263.87	4330.00	-128.00	-1191.00	3.00	-3.00	0.00	180.00	
8255.49	0.00	263.87	8050.00	-128.00	-1191.00	0.00	0.00	0.00	263.87	

Section 1: Start Hold

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100f	Build t deg/100	Turn ft deg/100f	TFO t deg
0.00	0.00	263.87	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	263.87	100.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87
200.00	0.00	263.87	200.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87
300.00	0.00	263.87	300.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87
400.00	0.00	263.87	400.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87
500.00	0.00	263.87	500.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87
550.00	0.00	263.87	550.00	0.00	0.00	0.00	0.00	0.00	0.00	263.87

Section 2: Start Build 4.00

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+ E/-W ft	VS ft	DLS deg/100f	Build t deg/100t	Turn t deg/100ft	TFO deg	
600.00 700.00	2.00 6.00	263.87 263.87	599.99 699.73	-0.09 -0.84	-0.87 -7.80	0.87 7.85	4.00 4.00	4.00 4.00	0.00 0.00	0.00 0.00	



Ryan Energy Technologies **Planning Report**



Company: Dominion E & P

Field: Natural Buttes Field Site: HCU 14-34F Well:

HCU 14-34F Wellpath: Original Hole

Date: 6/27/2005 Time: 13:41:52

Co-ordinate(NE) Referen Site: HCU 14-34F, True North

Vertical (TVD) Referencesst. KB @ 5356' 0.0 Section (VS) Reference: Site (0.00N,0.00E,263.87Azi)

Plan #1

Section 2: Start Build 4.00

MD	Incl	Azim	TVD	+N/-S	+ E/-W	VS	DLS	Build	Turn	TFO	
ft	deg	deg	ft	ft	ft	ft	deg/100	ft deg/100	ft deg/100ft	deg	
800.00	10.00	263.87	798.73	-2.33	-21.64	21.76	4.00	4.00	0.00	0.00	
900.00	14.00	263.87	896.53	-4.55	-42.30	42.55	4.00	4.00	0.00	0.00	
1000.00	18.00	263.87	992.63	-7.49	-69.70	70.11	4.00	4.00	0.00	0.00	
1067.58	20.70	263.87	1056.39	-9.88	-91.97	92.50	4.00	4.00	0.00	0.00	

Section 3: Start Hold

MD	Incl	Azim	TVD	+N/-S	+E/-W	VS	DLS	Build	Turn	TFO	_
ft	deg	deg	ft	ft	ft	ft	deg/100	ft deg/100	ft deg/100ft	deg	
1100.00	20.70	263.87	1086.72	-11.11	-103.36	103.96	0.00	0.00	0.00	0.00	_
1200.00	20.70	263.87	1180.26	-14.89	-138.51	139.31	0.00	0.00	0.00	0.00	
1300.00	20.70	263.87	1273.80	-18.66	-173.66	174.66	0.00	0.00	0.00	0.00	
1400.00	20.70	263.87	1367.34	-22.44	-208.82	210.02	0.00	0.00	0.00	0.00	
1500.00	20.70	263.87	1460.89	-26.22	-243.97	245.37	0.00	0.00	0.00	0.00	
1600.00	20.70	263.87	1554.43	-30.00	-279.12	280.72	0.00	0.00	0.00	0.00	
1700.00	20.70	263.87	1647.97	-33.78	-314.27	316.08	0.00	0.00	0.00	0.00	
1800.00	20.70	263.87	1741.51	-37.55	-349.42	351.43	0.00	0.00	0.00	0.00	
1900.00	20.70	263.87	1835.06	-41.33	-384.57	386.78	0.00	0.00	0.00	0.00	
2000.00	20.70	263.87	1928.60	-45.11	-4 19.72	422.13	0.00	0.00	0.00	0.00	
2100.00	20.70	263.87	2022.14	-48.89	-454.87	457.49	0.00	0.00	0.00	0.00	
2200.00	20.70	263.87	2115.68	-52.66	-490.02	492.84	0.00	0.00	0.00	0.00	
2300.00	20.70	263.87	2209.23	-56.44	-525.17	528.19	0.00	0.00	0.00	0.00	
2400.00	20.70	263.87	2302.77	-60.22	-560.32	563.55	0.00	0.00	0.00	0.00	
2500.00	20.70	263.87	2396.31	-64.00	-595.47	598.90	0.00	0.00	0.00	0.00	
2600.00	20.70	263.87	2489.85	-67.77	-630.62	634.25	0.00	0.00	0.00	0.00	
2700.00	20.70	263.87	2583.40	-71.55	-665.77	669.60	0.00	0.00	0.00	0.00	
2800.00	20.70	263.87	2676.94	<i>-</i> 75.33	-700.92	704.96	0.00	0.00	0.00	0.00	
2900.00	20.70	263.87	2770.48	-79.11	-736.07	740.31	0.00	0.00	0.00	0.00	
3000.00	20.70	263.87	2864.02	-82.89	-771.22	775.66	0.00	0.00	0.00	0.00	
3100.00	20.70	263.87	2957.56	- 86.66	-806.37	811.01	0.00	0.00	0.00	0.00	
3200.00	20.70	263.87	3051.11	-90.44	<i>-</i> 841.52	846.37	0.00	0.00	0.00	0.00	
3300.00	20.70	263.87	3144.65	-94.22	-876.67	881.72	0.00	0.00	0.00	0.00	
3400.00	20.70	263.87	3238.19	-98.00	-911.82	917.07	0.00	0.00	0.00	0.00	
3500.00	20.70	263.87	3331.73	-101.77	-946.97	952.43	0.00	0.00	0.00	0.00	
3600.00	20.70	263.87	3425.28	-105.55	-982.12	987.78	0.00	0.00	0.00	0.00	
3700.00	20.70	263.87	3518.82	-109.33	-1017.27	1023.13	0.00	0.00	0.00	0.00	
3800.00	20.70	263.87	3612.36	-113.11	-1052.42	1058.48	0.00	0.00	0.00	0.00	
3845.38	20.70	263.87	3654.81	-114.82	-1068.38	1074.53	0.00	0.00	0.00	0.00	

Section 4: Start Drop -3.00

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+ E /- W ft	VS ft	DLS deg/100	Build ft deg/100	Turn ft deg/100	TFO ft deg	<u></u>
3900.00	19.06	263.87	3706.17	-116.81	-1086.85	1093.10	3.00	-3.00	0.00	180.00	
4000.00	16.06	263.87	3801.50	-120.03	-1116.85	1123.28	3.00	-3.00	0.00	180.00	
4055.45	14.40	263.87	3855.00	-121.59	-1131.33	1137.85	3.00	-3.00	0.00	-180.00	
4100.00	13.06	263.87	3898.28	-122.72	-1141.85	1148.42	3.00	-3.00	0.00	180.00	
4200.00	10.06	263.87	3996.23	-124.86	-1161.78	1168.47	3.00	-3.00	0.00	180.00	
4300.00	7.06	263.87	4095.11	-126.45	-1176.58	1183.36	3.00	-3.00	0.00	180.00	
4395.36	4.20	263.87	4190.00	-127.45	-1185.89	1192.72	3.00	-3.00	0.00	180.00	
4400.00	4.06	263.87	4194.62	-127.49	-1186.22	1193.05	3.00	-3.00	0.00	-180.00	
4500.00	1.06	263.87	4294.51	-127.96	-1190.67	1197.53	3.00	-3.00	0.00	180.00	
4535.49	0.00	263.87	4330.00	-128.00	-1191.00	1197.86	3.00	-3.00	0.00	-180.00	

Section 5: Start Hold

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100t	Build ft deg/100	Turn ft deg/100f	TFO t deg	
4600.00	0.00	263.87	4394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	
4700.00	0.00	263.87	4494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	
4800.00	0.00	263.87	4594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	
4900.00	0.00	263.87	4694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	
5000.00	0.00	263.87	4794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	- 1
5100.00	0.00	263.87	4894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87	



A Energy Technologies Planning Report



Page:

Company: Dominion E & P Field: Natural Buttes Field

Field: Natural Buttes Fiel Site: HCU 14-34F Well: HCU 14-34F Wellpath: Original Hole Date: 6/27/2005

Time: 13:41:52

Co-ordinate(NE) Referenchite: HCU 14-34F, True North

Vertical (TVD) Referencesst. KB @ 5356' 0.0 Section (VS) Reference: Site (0.00N,0.00E,263.87Azi)

ın: f

Section 5: Start Hold

MD	Incl	Azim	TVD	+N/-S	+E/-W	VS	DLS	Build	Turn	TFO
ft	deg	deg	ft	ft	ft	ft			ft deg/100	ft deg
5200.00	0.00	263.87	4994.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5300.00	0.00	263.87	5094.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5355.49	0.00	263.87	5150.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5400.00	0.00	263.87	5194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5500.00	0.00	263.87	5294.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5600.00	0.00	263.87	5394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5700.00	0.00	263.87	5494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5800.00	0.00	263.87	5594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
5900.00	0.00	263.87	5694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6000.00	0.00	263.87	5794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6100.00	0.00	263.87	5894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6200.00	0.00	263.87	5994.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6300.00	0.00	263.87	6094.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6400.00	0.00	263.87	6194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6500.00	0.00	263.87	6294.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6505.49	0.00	263.87	6300.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6600.00	0.00	263.87	6394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6700.00	0.00	263.87	6494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6800.00	0.00	263.87	6594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
6900.00	0.00	263.87	6694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7000.00	0.00	263.87	6794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7100.00	0.00	263.87	6894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7200.00	0.00	263.87	6994.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7300.00	0.00	263.87	7094.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7355.49	0.00	263.87	7150.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7400.00	0.00	263.87	7194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7500.00	0.00	263.87	7294.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7600.00	0.00	263.87	7394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7700.00	0.00	263.87	7494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
7800.00	0.00	263.87	7594.51		-1191.00	1197.86	0.00	0.00	0.00	263.87
7900.00	0.00	263.87	7694.51		-1191.00	1197.86	0.00	0.00	0.00	263.87
00.008	0.00	263.87	7794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
8100.00	0.00	263.87	7894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87
8200.00	0.00	263.87	7994.51		-1191.00	1197.86	0.00	0.00	0.00	263.87
8255.49	0.00	263.87	8050.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	263.87

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100	Build ft deg/100	Turn ft deg/100ft	Tool/Comment
0.00	0.00	263.87	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
100.00	0.00	263.87	100.00	0.00	0.00	0.00	0.00	0.00	0.00	
200.00	0.00	263.87	200.00	0.00	0.00	0.00	0.00	0.00	0.00	
300.00	0.00	263.87	300.00	0.00	0.00	0.00	0.00	0.00	0.00	
400.00	0.00	263.87	400.00	0.00	0.00	0.00	0.00	0.00	0.00	
500.00	0.00	263.87	500.00	0.00	0.00	0.00	0.00	0.00	0.00	
550.00	0.00	263.87	550.00	0.00	0.00	0.00	0.00	0.00	0.00	
600.00	2.00	263.87	599.99	-0.09	-0.87	0.87	4.00	4.00	0.00	
700.00	6.00	263.87	699.73	-0.84	-7.80	7.85	4.00	4.00	0.00	
800.00	10.00	263.87	798.73	-2.33	-21.64	21.76	4.00	4.00	0.00	
900.00	14.00	263.87	896.53	-4.55	-42.30	42.55	4.00	4.00	0.00	
1000.00	18.00	263.87	992.63	-7.49	-69.70	70.11	4.00	4.00	0.00	
1067.58	20.70	263.87	1056.39	- 9.88	-91.97	92.50	4.00	4.00	0.00	
1100.00	20.70	263.87	1086.72	-11.11	-103.36	103.96	0.00	0.00	0.00	
1200.00	20.70	263.87	1180.26	-14.89	-138.51	139.31	0.00	0.00	0.00	
1300.00	20.70	263.87	1273.80	-18.66	-173.66	174.66	0.00	0.00	0.00	
1400.00	20.70	263.87	1367.34	-22.44	-208.82	210.02	0.00	0.00	0.00	
1500.00	20.70	263.87	1460.89	-26.22	-243.97	245.37	0.00	0.00	0.00	
1600.00	20.70	263.87	1554.43	-30.00	-279.12	280.72	0.00	0.00	0.00	
1700.00	20.70	263.87	1647.97	-33.78	-314.27	316.08	0.00	0.00	0.00	



Ryan Energy Technologies **Planning Report**



Page:

Company: Dominion E & P Field: Natural Buttes Field

HCU 14-34F Site: Well: HCU 14-34F Wellpath: Original Hole Date: 6/27/2005

Time: 13:41:52

Co-ordinate(NE) Referencite: HCU 14-34F, True North Vertical (TVD) Referencesst. KB @ 5356' 0.0

Section (VS) Reference: Site (0.00N,0.00E,263.87Azi)

S	Survey	·									
	MD	Incl	Azim	TVD	+N/-S	+E/-W	vs	DLS	Build	Turn	Tool/Comment
_	ft	deg	deg	ft	ft	ft	ft	deg/100	ft deg/100	oft deg/100ft	
	1800.00 1900.00	20.70	263.87	1741.51	-37.55		351.43	0.00	0.00	0.00	
	2000.00	20.70	263.87	1835.06	-41.33	-384.57	386.78	0.00	0.00	0.00	
		20.70	263.87	1928.60	-45.11	-419.72	422.13	0.00	0.00	0.00	
	2100.00	20.70	263.87	2022.14	-48.89	-454.87	457.49	0.00	0.00	0.00	
2	2200.00	20.70	263.87	2115.68	-52.66	-490.02	492.84	0.00	0.00	0.00	
2	2300.00	20.70	263.87	2209.23	-56.44	-525.17	528.19	0.00	0.00	0.00	
2	2400.00	20.70	263.87	2302.77	-60.22	-560.32	563.55	0.00	0.00	0.00	
2	2500.00	20.70	263.87	2396.31	-64.00	-595.47	598.90	0.00	0.00	0.00	
2	2600.00	20.70	263.87	2489.85	-67.77	-630.62	634.25	0.00	0.00	0.00	
2	2700.00	20.70	263.87	2583.40	-71.55	-665.77	669.60	0.00	0.00	0.00	
١,	2800.00	20.70	263.87	2676.94	75.00	700.00	70400				
	900.00	20.70	263.87	2070.94	-75.33 -70.44	-700.92	704.96	0.00	0.00	0.00	
	300.00	20.70	263.87	2864.02	-79.11	-736.07	740.31	0.00	0.00	0.00	
	100.00	20.70	263.87		-82.89	-771.22	775.66	0.00	0.00	0.00	
1	200.00	20.70		2957.56	-86.66	-806.37	811.01	0.00	0.00	0.00	
"	200.00	20.70	263.87	3051.11	-90.44	-841.52	846.37	0.00	0.00	0.00	
	300.00	20.70	263.87	3144.65	-94.22	-876.67	881.72	0.00	0.00	0.00	
	400.00	20.70	263.87	3238.19	-98.00	-911.82	917.07	0.00	0.00	0.00	
	500.00	20.70	263.87	3331.73	-101.77	-946.97	952.43	0.00	0.00	0.00	
	600.00	20.70	263.87	3425.28	-105.55	-982.12	987.78	0.00	0.00	0.00	
3	700.00	20.70	263.87	3518.82	-109.33	-1017.27	1023.13	0.00	0.00	0.00	
3	800.00	20.70	263.87	3612.36	-113.11	-1052.42	1058.48	0.00	0.00	0.00	
	845.38	20.70	263.87	3654.81	-114.82	-1068.38	1074.53	0.00	0.00	0.00	
	900.00	19.06	263.87	3706.17	-116.81	-1086.85	1093.10	3.00	-3.00		
	000.00	16.06	263.87	3801.50	-120.03	-1116.85	1123.28	3.00		0.00	•
	055.45	14.40	263.87	3855.00	-121.59	-1131.33	1123.26		-3.00	0.00	14/
"			200.01	3033.00	-121.33	-1131.33	1137.00	3.00	-3.00	0.00	Wasatch Tongue
	100.00	13.06	263.87	3898.28	-122.72	-1141.85	1148.42	3.00	-3.00	0.00	
1	200.00	10.06	263.87	3996.23	-124.86	-1161.78	1168.47	3.00	-3.00	0.00	
	300.00	7.06	263.87	4095.11	-126.45	-1176.58	1183.36	3.00	-3.00	0.00	
	395.36	4.20	263.87	4190.00	-127.45	-1185.89	1192.72	3.00	-3.00	0.00	Uteland Limestone
44	400.00	4.06	263.87	4194.62	-127.49	-1186.22	1193.05	3.00	-3.00	0.00	
4	500.00	1.06	263.87	4294.51	-127.96	-1190.67	1197.53	3.00	-3.00	0.00	
45	535.49	0.00	263.87	4330.00	-128.00	-1191.00	1197.86	3.00	-3.00	0.00	Vertical Landing Point
46	00.00	0.00	263.87	4394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	vertical Landing Politi
47	700.00	0.00	263.87	4494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
48	300.00	0.00	263.87	4594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
40	900.00	0.00	263.87	4694.51	-128.00	1101.00	1407.00	0.00	0.00	0.00	
	00.00	0.00	263.87	4794.51	-128.00 -128.00	-1191.00	1197.86	0.00	0.00	0.00	
	100.00	0.00	263.87	4894.51	-128.00 -128.00	-1191.00 -1191.00	1197.86	0.00	0.00	0.00	
	200.00	0.00	263.87	4994.51	-128.00		1197.86	0.00	0.00	0.00	
	300.00	0.00	263.87	5094.51	-128.00	-1191.00 -1191.00	1197.86 1197.86	0.00 0.00	0.00	0.00	
								J.UU	0.00	0.00	
	355.49	0.00	263.87	5150.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	Chapita Wells
	00.00	0.00	263.87	5194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
	00.00	0.00	263.87	5294.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	Į.
	00.00	0.00	263.87	5394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
57	700.00	0.00	263.87	5494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
58	300.00	0.00	263.87	5594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
	00.00	0.00	263.87	5694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	1
	00.00	0.00	263.87	5794.51	-128.00	-1191.00	1197.86	0.00	0.00 a00.0		ļ
	00.00	0.00	263.87	5894.51	-128.00	-1191.00	1197.86			0.00	
	200.00	0.00	263.87	5994.51	-128.00	-1191.00	1197.86	0.00 0.00	0.00 0.00	0.00 0.00	
62	00.00	0.00									
	00.00	0.00	263.87	6094.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	Ī
	00.00	0.00	263.87	6194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	!
	00.00	0.00	263.87	6294.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	1
00	05.49	0.00	263.87	6300.00	-128.00	-1191.00	1197.86	0.00	0.00		Uteland Buttes



Ryan Energy Technologies **Planning Report**



Company: Dominion E & P

Natural Buttes Field HCU 14-34F Field: Site:

Well: HCU 14-34F Wellpath: Original Hole Date: 6/27/2005

Time: 13:41:52

Co-ordinate(NE) Referen Site: HCU 14-34F, True North Vertical (TVD) Referencesst. KB @ 5356' 0.0

Section (VS) Reference: Site (0.00N,0.00E,263.87Azi) Plan #1

Survey

MD ft	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W ft	VS ft	DLS deg/100t	Build ft deg/100f	Turn t deg/100ft	Tool/Comment
6600.00	0.00	263.87	6394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
6700.00	0.00	263.87	6494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
6800.00	0.00	263.87	6594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
6900.00	0.00	263.87	6694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7000.00	0.00	263.87	6794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7100.00	0.00	263.87	6894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7200.00	0.00	263.87	6994.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7300.00	0.00	263.87	7094.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7355.49	0.00	263.87	7150.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	Mesaverde
7400.00	0.00	263.87	7194.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	Wedaverde
7500.00	0.00	263.87	7294.51	-128 .00	-1191.00	1197.86	0.00	0.00	0.00	
7600.00	0.00	263.87	7394.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7700.00	0.00	263.87	7494.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7800.00	0.00	263.87	7594.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
7900.00	0.00	263.87	7694.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
8000.00	0.00	263.87	7794.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
8100.00	0.00	263.87	7894.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
8200.00	0.00	263.87	7994.51	-128.00	-1191.00	1197.86	0.00	0.00	0.00	
8255.49	0.00	263.87	8050.00	-128.00	-1191.00	1197.86	0.00	0.00	0.00	BHL

Targets

Name	Descript Dip.	ion Dir.	TVD ft	+N/-S ft	+E/-W ft	Map Northing ft	Map Easting ft	< Latitude Deg Min Sec	->< Longitude Deg Min Sec
Vertical Land -Plan hit ta			4330.00	-128.00	-1191.00	7141001.782	157799.79	39 54 33.144 N	109 39 19.505 W
BHL -Plan hit ta	J		8050.00	-128.00	-1191.00	7141001.782	157799.79	39 54 33.144 N	109 39 19.505 W

Formations

MD	TVD	Formations	Lithology	Dip Angle	Dip Direction
ft	TI.			deg	deg
4055.45	3855.00	Wasatch Tongue		0.00	0.00
4395.36	4190.00	Uteland Limestone		0.00	0.00
4535.49	4330.00	Wasatch		0.00	0.00
5355.49	5150.00	Chapita Wells		0.00	0.00
6505.49	6300.00	Uteland Buttes		0.00	0.00
7355.49	7150.00	Mesaverde		0.00	0.00



550

1056

1000

2000

4000

5000

6000

7000

8000-

8050

0° 0 MD Start Hold

0° 550 MD Start Build 4.00

1075

21° 3845 MD Start Drop 3.00 Wasatch Tongue

Wasatch

Chapita Wells

-Uteland Buttes

Mesaverde

0° 8255 MD TD

1000 Vertical Section at 263.87° [1000ft/in]


0° 4535 MD Start Hold

21 ° 1068 MD Start Hold

Plan #1

Dominion E & P

Well: HCU 14-34F Field: River Bend Unit Uintah Co. Utah Sec. 34, T10S, R20E



West(-)/East(+) [400ft/in] SECTION DETAILS

-400

	c Targe
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	00 60 63 66

WELL DETAILS

Name	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
HCU 14-34F	0.00	0.00	7141154.37	2158987.89	39°54'34,409N	109°39'04.220W	N/A

FORMATION TOP DETAILS

-1200

No.	TVDPath	MDPath	Formation
1	3855.00	4055.45	Wasatch Tongue
2	4190.00	4395.36	Uteland Limestone
3	4330.00	4535.49	Wasatch
4	5150.00	5355.49	Chapita Wells
5	6300.00	6505.49	Uteland Buttes
6	7150.00	7355.49	Mesaverde

WELLPATH DETAILS

Original Hole

Ref. Datum:	esi	est. KB @ 5356			
V.Section Angle	Origin +N/-S	Origin +E/-W	Starting From TVD		
263.87°	0.00	0.00	0.00		

REFERENCE INFORMATION

Co-ordinate (N/E) Reference: Site Centre HCU 14-34F, True North Vertical (TVD) Reference: est. KB @ 5356' 0.00 Section (VS) Reference: Site Centre (0.00N,0.00E) Measured Depth Reference: est. KB @ 5356' 0.00 Calculation Method: Minimum Curvature



Azimuths to True North Magnetic North: 11.88°

Magnetic Field Strength: 52904nT Dip Angle: 65.92° Date: 6/27/2005 Model: igrf2005

FIELD DETAILS

Natural Buttes Field Uintah County, Utah USA

Geodetic System: US State Plane Coordinate System 1983 Ellipsoid: GRS 1980 Zone: Utah, Central Zone Magnetic Model: igrf2005

System Datum: Mean Sea Level Local North: True North

SITE DETAILS

HCU 14-34F Hill Creek Unit Sec. 34, T10S, R20E

Site Centre Latitude: 39°54'34.409N Longitude: 109°39'04.220W

Ground Level: 5338.00
Positional Uncertainty: 0.00
Convergence: 1.18



UNITED STATES **BUREAU OF LAND MANAGEMENT**

	F	ORM A	PPR	OVE	D
	Ol	MB No.	100	4-013	35
_					_

OMB No. 1004-0135	
Expires: November 30, 2000	,

	Expires:	November	30,	
Lease Serial	No.			

	5. Lease Serial I
SUNDRY NOTICES AND REPORTS ON WELLS	U-79130

Do not use this form for proposals to drill or	6. If Indian, Allottee or Tribe Name		
abandoned well. Use Form 3160-3 (APD) for			
A TIME A STEBRITTON PROPERCATE A CONSOCIAS INSTITUCIONS	Sansavyase yldő;	7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well		Hill Creek Unit	
Oil Well X Gas Well Other On &	ICIOCAITIAI	8. Well Name and No.	
2. Name of Operator	IFIUENIIAL —	HCU 14-34F	
Parallela Fronto de O.B. do d. d.		9. API Well No.	
Dominion Exploration & Production, Inc. 3a. Address Suite 600 3	b. Phone No. (include area code)	43-047-35875	
14000 Quail Springs Parkway, OKC, OK 73134	(405) 749-5263	10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	(100) 1 10 0200	Natural Buttes	
		11. County or Parish, State	
829' FSL & 1958' FEL,SW SE Sec. 34-10S-20E		Uintah, UT	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE	NATURE OF NOTICE, R	EPORT OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION	ON	
X Notice of Intent	Deepen Production	on (Start/Resume)	
. Altering Casing	Fracture Treat Reclama	tion Well Integrity	
Subsequent Report Casing Repair	New Construction Recomp	ete X Other	
Change Plans		rily Abandon APD Expiration.	
Final Abandonment Notice Convert to Injection	Plug Back Di	sposal	
Describe Proposed or Completed Operation (clearly state all pertinent deta if the proposal is to deepen, directionally or recomplete, horizontally, give s Attach, the Bond under which the work will be performed or provide, the E following completion of the involved operations. If the operation results in testing has been completed Final Abandonment Notices shall be filed o determined that the site is ready for final inspection.)	subsurface. locations and measured Bond No on file with BLM/BIA R a. multiple completion or recomplet nly. after all requirements, includin	l and true, vertical depths of all pertinent markers and zones, equired subsequent reports shall be, filed within 30 days ion, in a new interval, a Form. 3160-4 shall be, filed once greclamation, have been completed, and the operator has	
The state APD for this well expires August 17, 2005			
COPY SENT TO OPERATOR Date: 9-1-00- Initials Callo	Approved Utah Divi Oil, Gas an Date: Q8- 9 By:	sion of d Mining	
14. I hereby certify that the foregoing is true and correct Name (PrintedTyped)			
Carla Christian	Titl	Regulatory Specialist	
Signature Coula Mustian	Da	te 8/02/2005	
A SECTION OF THE SPACETOR HERE	ALORSIAND OPPIC		
Approved by .	Title	Date	
Conditions of approval, if any, are attached. Approval of this notice does certify that the applicant holds legal or equitable title to those rights in twhich would entitle the applicant to conduct operations thereon.			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

> **RECEIVED** AUG 0 5 2005

Application for Permit to Drill Request for Permit Extension Validation (this form should accompany the Sundry Notice requesting permit extension)

API: 43-047-35875 Well Name: HCU 14-34F	
Location: Section 34-10S-20E, 829' FS	L & 1958' FEL
Company Permit Issued to: Domini Date Original Permit Issued: 8/17/20	
Date Original Fernit Issued: %17/20	U4
The undersigned as owner with legal in above, hereby verifies that the information approved application to drill, remains in the second	
Following is a checklist of some items verified.	related to the application, which should be
If located on private land, has the own agreement been updated? Yes⊡No⊡	
Have any wells been drilled in the vicing the spacing or siting requirements for	nity of the proposed well which would affect this location? Yes⊡ No⊠
Has there been any unit or other agree permitting or operation of this propose	ements put in place that could affect the d well? Yes□No☑
Have there been any changes to the a of-way, which could affect the propose	ccess route including ownership, or right- ed location? Yes□ No ☑
Has the approved source of water for o	drilling changed? Yes⊟ No⊠
Have there been any physical changes which will require a change in plans fro evaluation? Yes□No☑	s to the surface location or access route om what was discussed at the onsite
ls bonding still in place, which covers t	his proposed well? Yes⊠No⊡
Coula anistian	8/3/2005
Signature	Date
Title: Regulatory Specialist	
Representing: Dominion Exploration & Pr	oduction, Inc.
	RECEIVED

AUG 0 5 2005

Form 3160-5 (August, 1999)

UNITED STATES DEPARTMENT OF HE INTERIOR

FORM A
OMB No
Evniree Nov

FORM .	APPROVED
OMB N	o. 1004-0135

OMB No. 1004-0135	5
Expires: November 30, 2	กกกร

BUREAU C	OF LAND MANAGEN	MENT	6611		Expires: November 30, 2000	
		177		5. Lease Ser		
SUNDRY NOTICE	ES AND REPORTS	ON WELLS	uic 0 4 2	05U-791	30	
Do not use this form f	or proposals to drill o	or to re-enter an 🗜	100 0 = 20	6. If Indian,	Allottee or Tribe Name	
abandoned well. Use F	orm 3160-3 (APD) fo	r such proposals.		4 40 40		
THE STEEL STUBBLE TO NORTH DECK	TIE SOuter Britisielle	nistoji zavaka silik		7. If Unit or	CA/Agreement, Name and/or No.	
1. Type of Well				Hill	Creek Unit	
Oil Well X Gas Well	Other			8. Well Nam		
2. Name of Operator			·	HCI	U 14-34F	
Deminion Evaluation 9 Deadwation	la a			9. API Well	No.	
Dominion Exploration & Production, 3a. Address Suite 600		3b. Phone No. (includ	la arrag anda)	43-r	047-35875	
14000 Quail Springs Parkway, OKC		(405) 749-526	•	10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or		(403) 748-320	,5	Natural Buttes		
	Survey Becompaint					
				•	or Parish, State	
829' FSL & 1958' FEL,SW SE Sec.	34-10S-20E			Uint	tah, UT	
12. CHECK APPROPRIATE BO	OX(ES) TO INDICAT	E NATURE OF NO	OTICE, REPO	RT OR O	THER DATA	
TYPE OF SUBMISSION		TYPE	OF ACTION			
X Notice of Intent	Acidize	Deepen	Production (St	art/Resume)	Water Shut-Off	
	Altering Casing	Fracture Treat	Reclamation		Well Integrity	
Subsequent Report	Casing Repair	New Construction	. Recomplete		X Other	
	Change Plans	Plug and Abandon	Temporarily Al	Temporarily Abandon APD Expiration.		
Final Abandonment Notice			Water Disposa			
Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof.						

If the proposal is to deepen, directionally or recomplete, horizontally, give subsurface, locations and measured and true, vertical depths of all pertinent, markers and zones, Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

The state APD for this well expires August 17, 2005. Dominion is hereby requesting a one year extension.

CONDITIONS OF APPROVAL ATTACHED

1
Title Regulatory Specialist
Date 8/02/2005
CONDUCTORS OF THE PARTY OF THE
Petroleum Engineer Date
Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

> RECEIVED SEP 0 9 2005



Application for Permit to Drill Request for Permit Extension Validation

Validation
(this form should accompany the Sundry Notice requesting permit extension)

API:

43-047-35875

Well Name: HCU 14-34F Location: Section 34-10S-20E, 829' FSL & 1958' FEL Company Permit Issued to: Dominion Exploration & Production, Inc. Date Original Permit Issued: 8/17/2004				
The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision.				
Following is a checklist of some items related to the application, which should be verified.				
If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes□No□				
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes□No☑				
Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes□ No ☑				
Have there been any changes to the access route including ownership, or right-of-way, which could affect the proposed location? Yes□ No ☑				
Has the approved source of water for drilling changed? Yes⊡ No⊠				
Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes□No☑				
Is bonding still in place, which covers this proposed well? Yes ☑ No ☐				
Coula Mustian 8/3/2005				
Signature Date				
Title: Regulatory Specialist				
Representing: Dominion Exploration & Production, Inc.				

CONDITIONS OF APPROVAL

Dominion Exploration & Production Inc.

Notice of Intent APD Extension

Lease:

UTU-79130

Well:

HCU 14-34F

Location:

SWSE Sec 34-T10S-R20E

An extension for the referenced APD is granted with the following conditions:

- 1. The extension and APD shall expire on 08/17/06
- 2. No other extension shall be granted.

If you have any other questions concerning this matter, please contact Matt Baker of this office at (435) 781-4490

UNITED ATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FORM APPROVED	
OMB No. 1004-0135	

ONID 110. 1001	0155
Expires: November	30, 2000

5. Lease Seria	al No.
----------------	--------

Doubo	٠,		1.0.
U-7	91	30)

6.	If	Indian,	Allottee	or	Tribe	Name
----	----	---------	----------	----	-------	------

abandoned well. Use Form 3160-3 (APD) for such proposals		o. If Inglan, Another of Thee Na	anic
ABANGONEG WEN. CSC FORM 5100 5 (ALD) FOR SHEER PROPOSITION OF THE SHEET		7. If Unit or CA/Agreement, Na	me and/or No.
1. Type of Well		Hill Creek Unit	
Oil Well X Gas Well Other	FNTIAL	8. Well Name and No.	
2. Name of Operator	LIVITAL	HCU 14-34F	
•		9. API Well No.	
Dominion Exploration & Production, Inc.		43-047-35875	
3a. Address Suite 600 3b. Phone No. (included) 14000 Quail Springs Parkway, OKC, OK 73134 (405) 749-52	•	10. Field and Pool, or Explorate	ry Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	203	Natural Buttes	ry ruou
4. Doublet of Hote (Loomed, 2001, 1., 1., 1., 1., 1.)		11. County or Parish, State	
829' FSL & 1958' FEL,SW SE Sec. 34-10S-20E		Uintah, UT	
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF N	NOTICE, REPO	ORT OR OTHER DATA	
TYPE OF SUBMISSION TYPE	E OF ACTION		
Notice of Intent Acidize Deepen	Production (S	tart/Resume) Water Shut-O	ff ,
Altering Casing Fracture Treat	Reclamation	Well Integrity	
X Subsequent Report Casing Repair New Construction	Recomplete	X Other	:
Change Plans Plug and Abandon	Temporarily A	spud Well	
Final Abandonment Notice Convert to Injection Plug Back	Water Dispos	al	
following completion of the involved operations. If the operation results in a multiple completic testing has been completed. Final Abandonment Notices shall be filed only after all requires determined that the site is ready for final inspection.) Spud well 9/15/05. Ran 13 jts. 13 3/8", 40#, H-40, 8rd csg., set @ppg., 13 bbls cmt. To pit.	ments, including rec	lamation, have been completed a	and the operator has
14. I hereby certify that the foregoing is true and correct			
Name (Printed/Typed) Carla Christian	Title	Regulatory Specialist	•
Carla Crinistian	11110	regulatory opeoidile	
Signature Could Wushow	Date	11/22/2005	
THE THE SECTION SECTION STATES OF ST	ABADTER CID	n21ga (1.1.2)	<u> </u>
Approved by	Title		Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any pe	erson knowingly a	and willfully to make to any dep	partment or agency of the

RECEIVED NOV 2 8 2005

STATE OF UTAH

DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING

ENTITY ACTION FORM

Operator:

Dominion Exploration & Production, Inc.

Operator Account Number: N 1095

Address:

14000 Quail Springs Parkway, Suite 600

city Oklahoma City

zip 73134 state Ok

Phone Number: (405) 749-1300

Well 1

API Number	Well	Name	QQ	Sec	Twp	Rng	County
43-047-35875	HCU 14-34F		SWSE	34	108	20E	Uintah
Action Code	Current Entity Number	New Entity	S	pud Dat	te 🐇 💮		ity Assignment
AB	99999	12829	Ş	9/15/200	5	1	1/30/05

Comments: MURD = W5 MUD

CONFIDENTIAL

14/-11 0

API Number	Well I	Name	ପ୍ରପ	Sec	Twp	Rng County			
Action Code	Current Entity Number	New Entity Number		 Spud Da ≓	te :	En	tity Assignment Effective Date		
Comments:			<u> </u>						

Well 3

API Number	Well N	lame 🔭 💮 🗀	QQ	Sec	Twp	Rng	County County
Action Code	Current Entity Number	New Entity Number	S S	pud Dat	9		Lity Assignment Effective Date
Comments:							

ACTION CODES:

- A Establish new entity for new well (single well only)
- B Add new well to existing entity (group or unit well)
- C Re-assign well from one existing entity to another existing entity
- D Re-assign well from one existing entity to a new entity
- E Other (Explain in 'comments' section)

Carla Christian

Name (Please Print)

Signature

Regulatory Specialist

11/22/2005

Title

RECEIVED

NOV 2 8 2005

1. Type of Well

2. Name of Operator

3a. Address

14000 Quail Springs Parkway, OKC, OK 73134

829' FSL & 1958' FEL,SW SE Sec. 34-10S-20E

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Dominion Exploration & Production, Inc.

UNITE DEPARTMENT THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FC	ORM A	PPRO	OVEI)
ON	MB No.	1004	I-013	5

	TMENT THE INTE			OMB No. 1004-0135
BOILLI	O. O. BIN D. WIN VIOLIV	ILIVI		Expires: November 30, 2000 5. Lease Serial No.
	ICES AND REPORTS			U-79130
	m for proposals to drill o		6. If Indian, Allottee or Tribe Name	
	e Form 3160-3 (APD) fo			
SUBMITEIN TRIPLE	CAMPE Other hymicity	is monestrices (the		7. If Unit or CA/Agreement, Name and/or No.
e of Well				Hill Creek Unit
Oil Well X Gas Wel	l Other	OMETIDERE	41	8. Well Name and No.
ne of Operator	_=	UNHUENH	H	HCU 14-34F
inion Exploration & Producti	on Inc			9. API Well No.
dress Suite 6	· · · · · · · · · · · · · · · · · · ·	3b. Phone No. (include ar	rea code)	43-047-35875
00 Quail Springs Parkway, O		(405) 749-5263		10. Field and Pool, or Exploratory Area
ation of Well (Footage, Sec., T., R., M.,				Natural Buttes
				11. County or Parish, State
FSL & 1958' FEL,SW SE Se	c. 34-10S-20E			Uintah, UT
12. CHECK APPROPRIATE	BOX(ES) TO INDICATE	E NATURE OF NOTI	ICE, REPO	RT OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF	ACTION	
Notice of Intent	Acidize	Deepen	Production (St	art/Resume) Water Shut-Off
	Altering Casing	Fracture Treat	Reclamation	Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomplete	X Other
	Change Plans	Plug and Abandon	Temporarily At	pandon Drilling Operations
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposa	I
Attach the Bond under which the work following completion of the involved ope testing has been completed. Final Ab determined that the site is ready for final	will be performed or provide the will be performed or provide the erations. If the operation results in andonment Notices shall be filed inspection.)	subsulface locations and m Bond No. on file with BLM/I n a multiple completion or re only after all requirements,	measured and BIA. Require ecompletion in including recla	by proposed work and approximate duration thereof. true vertical depths of all pertinent markers and zones. and subsequent reports shall be filed within 30 days a new interval, a Form 3160-4 shall be filed once amation, have been completed and the operator has 300 sks "III" CBM Lite, 3.97 cuft/sk, 10.5
ppg, tailed w/390 sks class	G, 15.8 ppg, 1.15 yld, to 17#, M-80, LT&C csg.,	op out w/115 sks Cla set @ 8138'. Ceme	ass "G", 1 ented lead	5.8 ppg, 1.15 yld., cmt. To surface. l w/90 sks of Hi-Fill "V". 11.6 ppg. 3.12
eby certify that the foregoing is true an e (PrimedTyped)	d correct		1	
Carla Christian			Title	Regulatory Specialist
			11110	regulatory opecialist

14. I hereby certify that the foregoing is true and correct Name (PrimedTyped)	1		
Carla Christian	Title	Regulatory Specialist	
Signature Could Mustian	Date	01/06/2006	
THIS SPACE FOR FEDDRAL OR STAT	is (o) and (cip.)	Selection made and a selection	
Approved by	Title	Dat	te
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any per	son knowingly a	nd willfully to make to any departme	ent or agency of the

RECEIVED JAN 1 0 2006

From: Dominion E&P 94057496657 To: Utah Division of Oil, Gas & Mining

Utah Division of Oil, Gas & Mining

Date: 1/11/2006 Time: 1:40:32 PM

Page 1 of 4

FACSIMILE COVER PAGE

From: g

Sent:

To:

1/11/2006 at 1:08:30 PM

Pages:

4 (including Cover)

Subject:

HCU 14-34F

105 RZOE S-34

43-042-35825

COMPLETAL

RECEIVED JAN 1 1 2006







WELL CHRONOLOGY REPORT

WELL NAME: HCU 14-34F

DISTRICT: WESTERN

COUNTY & STATE: UINTAH

FIELD: NATURAL BUTTES 630

Event No: 1

LOCATION: 829' FSL 1958' FEL SEC 34 T 10S R 20E

CONTRACTOR:

WI %: 100.00

AFE#: 0503146

API#: 43-047-35875

UT

PLAN DEPTH: 8,100

SPUD DATE: 09/15/05

DHC: \$602,000

CWC: \$586,000

AFE TOTAL: \$1,188,000

FORMATION: WASATCH/MESAVERDE

EVENT DC: \$799,951.84

EVENT CC: \$202,721.00

EVENT TC: \$1,002,672.84

WELL TOTL COST: \$1,099,420

REPORT DATE: 01/03/06

MD: 8,171

TVD:8,016

DAYS: 18

MW:

VISC:

DAILY: DC: \$0.00

CC: \$176,461.00

TC:\$176,461.00

CUM: DC: \$799,951.84

CC: \$191,887.00

TC: \$991,838.84

DAILY DETAILS:

RECEIVED JAN 1 1 2006

DIV. OF OIL, GAS & MINING





WELL CHRONOLOGY REPORT

WELL NAME: HCU 14-34F

Event No: 1

DISTRICT: WESTERN

FIELD: NATURAL BUTTES 630

LOCATION: 829' FSL 1958' FEL SEC 34 T 10S R 20E

COUNTY & STATE: UINTAH

CONTRACTOR:

W! %: 100.00

AFE#: 0503146

API#: 43-047-35875

PLAN DEPTH: 8,100

SPUD DATE: 09/15/05

DHC: \$602,000

CWC: \$586,000

AFE TOTAL: \$1,188,000

FORMATION: WASATCH/MESAVERDE

EVENT DC: \$799,951.84

EVENT CC: \$202,721.00

EVENT TC: \$1,002,672.84

WELL TOTL COST: \$1,099,420

FRAC STAGE #1, PERFORATE AND FRAC STAGES #2 THUR #5. TURN WELL OVER TO PRODUCTION. 1-2-2006 HCU 14-34F. MIRU SCHLUMBERGER frac equipment, tested lines to 7000 psi. Held safety meeting with all personnel. Quality control on gel & breaker systems with on-site lab was verified. Frac'd Mesa Verde Interval # 1, 7941-72', 8080-86', 2 spf, 76 holes, with 63,739# 20/40 Ottawa sand. Pumped frac at an average rate of 36.2 bpm, using 238.2 mscf of N2 and 598 bbls of fluid. Average surface treating pressure was 4332 psi with sand concentrations stair stepping from 2.0 ppg to 6.0 ppg.

3496 gallons Pad YF120ST/N2 gel.

3509 gallons YF120ST/N2 pumped @ 2.0 ppg sand concentration. 2113 gallons YF120ST/N2 pumped @ 3.0 ppg sand concentration. 2117 gallons YF120ST/N2 pumped @ 4.0 ppg sand concentration.

2811 gallons YF120ST/N2 pumped @ 5.0 ppg sand concentration.

2572 gallons YF120ST/N2 pumped @ 5.0 ppg sand concentration. 7754 gallons WF110 slick water flush.

Total frac fluid pumped 598 bbls. N2 was cut during flush. Ru wire line, RIH and set 5K frac plug @ 7840'. RIH and perforate interval #2 @ 7514-20', 7567-73', 7699-7704', 7759-64', 3 spf, 70 holes. Fraced interval #2 w/ 71,889# 20/40 Ottawa sand. Pumped frac at an avg rate of 41.9 bpm, using 259.1 mscf of N2 and 595 bbls of fluid. Avg surface treating pressure was 4433 psi w/ sand concentrations stair stepping from 2.0 ppg to 6.0 ppg.

4190 gallons Pad YF120ST/N2 gel.

2839 gallons YF120ST/N2 pumped @ 2.0 ppg sand concentration.

2818 gallons YF120ST/N2 pumped @ 3.0 ppg sand concentration.

2818 gallons YF120ST/N2 pumped @ 4.0 ppg sand concentration. 2812 gallons YF120ST/N2 pumped @ 5.0 ppg sand concentration.

2258 gallons YF120ST/N2 pumped @ 6.0 ppg sand concentration.

7272 gallons WF110 slick water flush.

Total frac fluid pumped 595 bbls. N2 was cut during flush. RIH and set 5K frac plug @ 7200', perforate interval # 3 @ 7056-65', 6 spf, 55 holes. Fraced interval #3 w/ 27,737# 20/40 Ottawa sand. Screened out w/ 27,616# in formation, and 121# in the wellbore. Pumped frac at an avg rate of 24.2 bpm, using 113.4 mscf of N2 and 350 bbls of fluid. Avg surface treating pressure was 4351 psi w/ sand concentrations stair stepping from 2.0 ppg to 5.0 ppg.

2799 gallons Pad YF120ST/N2 gel.

1421 gallons YF120ST/N2 pumped @ 2.0 ppg sand concentration. 1416 gallons YF120ST/N2 pumped @ 4.0 ppg sand concentration. 2567 gallons YF120ST/N2 pumped @ 5.0 ppg sand concentration.

6528 gallons WF110 slick water flush.

Total frac fluid pumped 350 bbs. N2 was cut during flush. RIH and set 5K frac plug @ 6600', perforate interval # 4 @ 6439-51', 4 spf, 49 holes. Due to screen out and short flush, perfs would not break. RIH w/ dump bailer, spotted 9 gallons of acid over perfs, and formation broke causing a cross flow covering stage #4. Flowed well to the pit on a 24/64 choke for 1 hour. Fraced interval #4 w/ 31,016# 20/40 Ottawa sand. Pumped frac at an avg rate of 23.4 bpm, using 116.9 mscf of N2 and 428 bbls of fluid. Avg surface treating pressure was 4169 psi w/ sand concentrations stair stepping from 2.0 ppg to 5.0 ppg.

2800 gallons Pad YF115LG/N2 gel.

gallons pumped YF115LG/N2 @ 2.0 ppg sand concentration. gallons pumped YF115LG/N2 @ 4.0 ppg sand concentration. 1418 2122

gallons pumped YF115LG/N2 @ 5.0 ppg sand concentration. 2635

gallons WF110 slick water flush.

Total frac fluid pumped 428 bbls. N2 was cut during flush. RIH and set 5K frac plug @ 6340', perforate interval # 5 @ 6207-15', 6250-56', 4 spf, 58 holes. Fraced interval #5 w/ 41,702# 20/40 Ottawa sand. Pumped frac at an avg rate of 28.1 bpm, using 185.9 mscf of N2 and 357 bbls of fluid. Avg surface treating pressure was 2859 psi w/ sand concentrations stair stepping from 2.0 ppg to 5.0 ppg.

2795 gallons Pad YF115LG/N2 gel.

2120 gallons YF115LG/N2 pumped @ 2.0 ppg sand concentration.

2122 gallons YF115LG/N2 pumped @ 4.0 ppg sand concentration.

2108 gallons YF115LG/N2 pumped @ 5.0 ppg sand concentration.

1383 gallons WF110 slick water flush. Total frac fluid pumped 357 bbs. N2 was not cut during flush. Opened well to the pit on a 12/64 choke fluir hective bore. to production

JAN 1 1 2006





WELL CHRONOLOGY REPORT

WELL NAME: HCU 14-34F

DISTRICT: WESTERN

Event No: 1

FIELD: NATURAL BUTTES 630

LOCATION: 829' FSL 1958' FEL SEC 34 T 10S R 20E

CONTRACTOR:

WI %: 100.00

AFE #: 0503146

API#: 43-047-35875

PLAN DEPTH: 8,100

SPUD DATE: 09/15/05

DHC: \$602,000

CWC: \$586,000

AFE TOTAL: \$1,188,000

FORMATION: WASATCH/MESAVERDE

EVENT DC: \$799,951.84

EVENT CC: \$202,721.00

EVENT TC: \$1,002,672.84

WELL TOTL COST: \$1,099,420

REPORT DATE: 01/05/06

COUNTY & STATE: UINTAH

MD: 8,171

TVD: 8.016

DAYS: 19

MW:

VISC:

DAILY: DC: \$0.00 CC: \$0.00 TC:\$0.00

CUM: DC: \$799,951.84

CC: \$191,887.00

TC: \$991,838.84

DAILY DETAILS: FLOW REPORT WELL FLOWING TO PIT ON 18/64 CHOKE FCP 0, @ 7 PM REMOVE CHOKE WELL UNLOADED @ 2 AM REPLACE 18/64 CHOKE FCP 235, RECOVERED 519 BBLS FRAC FLUID RU FLOWLINE TURN TO SALES @

10 AM. ON 48/64 CHOKE EST. RATE 300 MCF.

REPORT DATE: 01/06/06

MD: 8,171

TVD:8,016

DAYS: 20

MW:

VISC:

DAILY: DC: \$0.00

CC: \$0.00

TC:\$0.00

CUM: DC: \$799.951.84

CC: \$191,887.00

TC: \$991,838.84

DAILY DETAILS: FLOW REPORT MADE 257 MCF, FCP 191, SLP 129, 3 OIL, 29 WTR. 48/64 CHOKE.

REPORT DATE: 01/07/06

MD: 8,171

TVD:8,016

DAYS: 19

MW:

VISC:

DAILY: DC: \$0.00

CC: \$10,834.00

TC:\$10.834.00

CUM: DC: \$799,951.84

CC: \$202,721.00

TC: \$1,002,672.84

DAILY DETAILS: FLOW REPORT MADE 730 MCF FCP 244, SLP 120, 0 OIL 137 WTR. 14/64 CHOKE. ROAD RIG AND EQUIPMENT FROM THE LCU 6-6G TO LOCATION AND RU SAME. FCP 300#, BLED WELL DN, AND CONTROL W/ 40 BBLS OF 2% KCL WATER. ND FRAC VALVE, NU BOPE, AND RU WORKING FLOOR. MU BHA, WELL STARTED FLOWING, UNABLE TO CONTROL WELL. FLOW WELL TO THE PIT ON A 24/64 CHOKE, RD RIG, NU WELL HEAD ON TOP

OF BOPE, AND TURN WELL OVER TO PRODUCTION.

REPORT DATE: 01/08/06

MD: 8,171

TVD:8,016

DAYS: 20

MW:

VISC:

DAILY: DC: \$0.00

CC: \$0.00

TC:\$0.00

CUM: DC: \$799,951.84

CC: \$202,721.00

TC: \$1,002,672.84

DAILY DETAILS: FLOW REPORT MADE 572 MCF FCP 380, SLP 126, 2 OIL 80 WTR. 48/64 CHOKE DN 16 HRS W/O RIG.

REPORT DATE: 01/09/06

MD: 8,171

TVD: 8,016

DAYS: 21

MW:

VISC:

CC: \$0.00

CUM: DC: \$799,951.84

CC: \$202,721.00

TC: \$1,002,672.84

TC:\$0.00 DAILY: DC: \$0.00 DAILY DETAILS: FLOW REPORT MADE 855 MCF FCP 196, SLP 138, 0 OIL 90 WTR. 48/64 CHOKE 24 HR PRD.

> RECEIVED JAN 1 1 2006

Form 3160-4 (August 1999) *

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB NO. 1004-0137

,	,		BUF	REAU OF LA	AND MAN	AGE	MENT				1	. 1			ber 30, 2000
	WEL	L CON	IPLE	TION OR	RECOM	PLE	ETION F	REPOR	RT AN	AD LOGI	CNTID	A F	5. Lease Ser		
										LUNFI)E[311r	11		U-7	79130
A. T		ээли п Г					-			AAnn	-	-	<u> </u>		
1a. Type of V	7	Oil Well				ther				-	•	le le	5. If Indian, A	llottee o	r Tribe Name
b. Type of C	Completion:	X	v Well	Work	Over		Deepen	Dif	ff.Resvr			Ļ			
		Other										- 1'			nent Name and No.
2 Name of	Operator														eek Unit
	Name of Operator 8. Lease Name and Well No. Dominion Exploration & Production, Inc. HCU 14-34F														
3. Address	OII Explora	lion & P	roduct	ion, mc.				lo-	Dhara						U 14-34F
	00 Ouell C-	uimaa Di		. 04- 000	\ O!-!- C	···	01/ 704/			No. (include	•	9). API Well N		7.05075
	00 Quail Sp of Well (Repo								4	105-749-13	00				7-35875
		n location (Jeany a	nu in accorda	nce with red	ięrai i	equiremen	(S)		DE	CEIV	드바	0. Field and f		•
At surface	e 82	29' FSL 8	k 1958	B' FEL, SW	SE					ITL	CLIV				
At top pro	od. Interval rep	orted belo	N							MA	R 2 0 20	nnd'	 Sec., T.,R. Survey or A 		
												- 17	2. County on I		34-10S-20E 113. State
At total de	epth 😙	III ESI	. 105 7	FWL, SE	CIAP	49	SFC	7/ 20	29/	DIV. OF O			2. County of a	ransn	I
14. Date Spu		. ,		. Reached	140	200		770	TI	DIV. OF O	IL, GAS &	MIN	Numan		UT
•		15. 6			"	o. Dai	e Complete	X			.*	- [7	7. Elevations	(DF, RK	.в, кт, GL)*
9/15/2	005		12/2	22/2005			D&A	R	eady to	prod. 4	/4/2006	- 1		534	0' GL
18. Total Dep	oth: MD	8172'	1	9. Plug Back	T.D.: M	<u> </u>	8100). Depth Bridg			1D		
та, тош дор	TVD	8017'	ľ	o. Thug buok		/D	794			. Depair bridg	e riug Set.		VD		
Ot. Time Flor	4 0 OH 41			(O. b 1)					Tan						<u> </u>
21. Type Elec				in (Submit cop Triple Com					į.	as well cored?			Ye	-	ubmit analysis)
				<i>)</i> .					l w	as DST run?	X	No	L Ye	s (Se	ubmit report)
			-	Cement Bo	na Log				Dia	rectional Surve	ey?		No	X_Ye	s (Submit copy)
23. Casing an	nd Liner Recor	d (Report a	all string	set in well)	T		Stage C	montes							
Hole Size	Size/Grade	Wt.(#/	ft)	Top (MD)	Bottom (I	MD)	Stage Co		6	of Sks & of Cement	Slurry Vol (BBL)		Cement Top)*	Amount Pulled
	3 3/8"	40#	S	Surface	526'				500 8		(552)	c	irc.		
	5/8"	36#	S	Surface	2783'				805 8				urface		
7 7/8" 5	1/2"	17#		Surface	8138'				790 5	Sx		E	st. TOC @	2200	
24. Tubing Re	nord														
Size	Depth Set (MD)	Packer	Depth (MD)	Size		Depth Se	et (MD)	Pack	ker Depth (MD) Siz	'e	Depth Se	t(MD)	Packer Depth (MD)
2 3/8" 8	029'							. (::=/					1 3374.00	х()	V donor Depar (MD)
25. Producing	Intervals						26. Perfora	ation Rec	ord						A
*	ormation			Тор	Bottom			Perforate		/al	Size		No. Holes		Perf.Status
A) Mesaver				941'	8086'		7941- 72,					<u> </u>	76		Open
B) Mesaver	de		/	514'	7764'		(7514- 20		73, 76	99- 04					
C) Uteland I	Ruttoe			056'	7065'		7759- 64) 7056- 65)					70		Open
D) Uteland I				439'	6451'		6439- 51	· · · · · · · · · · · · · · · · · · ·			····	-	55 49		Open
E) Chapita \				207'	6256'		6207- 15,	6250- 5	6	·			58	i	Open Open
 											·				Орон
27. Acid, Frac		nt, Cement	Squeez	e, Etc.											
De 7941' - 808	epth Interval	Eroo w/6	2 720#	20/40 0#==		20.2		10 1 5		ant and Type o					
7514' - 776										s of YF 120: s of YF 120:					
7056' - 706										s of YF 120					•
6439' - 645										s of YF 115I					·
6207' - 625										s of YF 115					
															
Produced	Test Date	Hours Tested		Test Production	Oil BBL	Gas MCF		Water BBL		Oil Gravity	Gas		Production Me	thod	
	1	.	0.4	- roduction		IVICE	05:	1	_	Corr. API	Gravity				
1/4/2006 Choke	3/1/200 Tbg.Press.	6 Csg.	24	24 Hr.	Oil	Co-	254	1:	5	Gas:Cil	Man Original		<u>l</u>	Fle	owing
Size	Flwg.	Press.		Rate	BBL	Gas MCF		Water BBL		Gas:Oil Ratio	Well Statu	5			
48	138		175	 →	0		254	1:	5				Pro	ducing	•
	ction - Interval			1		L		<u>'`</u>	- :	L			FIO	aucii iy	1
ate First	Test	Hours		Test	Oil	Gas		Water		Oil Gravity	Gas		Production Me	ethod	
Produced	Date	Tested		Production	BBL	MCF		BBL		Corr. API	Gravity				
<u> </u>	<u> L</u>				<u> </u>	<u> </u>		<u> </u>		<u> </u>			<u> </u>		
Soo inclination	ne and enacor	for addition	nal data	on roverto ci	40)									_	

28b Produ	ction - Interval	С	· · · · · · · · · · · · · · · · · · ·								
Date First	Test	Hours	Test	Oil	Gas	Water	Oil	Gravity	Gas	Production Meth	nod
Produced	Date	Tested	Production	BBL	MCF	BBL	Co	rr. API	Gravity		•
Choke	Tog.Press.	Csg.	24 Hr.	Oil	Gas	Water	Ga	s:Oil	Well Status	ــــــــــــــــــــــــــــــــــــــ	
Size	Flwg. Si	Press.	Rate —	BBL -	MCF,	BBL	Ra				
	ction - Interval ()				— <u>-</u> -					
Date First Produced	Test Date	Hours Tested	Test	Oil	Gas	Water		Gravity	Gas	Production Meth	od
		rested	Production —	BBL	MCF	BBL	Cor	r. API	Gravity		
Choke Size	Tbg.Press. Flwg. SI	Csg. Press.	24 Hr. Rate	Oil BBL	Gas MCF	Water BBL	Ga: Rat	s:Oil io	Well Status		
29. Dispostion		d, used for fue	el, vented, etc.)		1						
	Sold										
30. Summary Show all ir tests, inclu and recove	mportant zone	es of porosity	Aquiters): and contents there cushion used, time	eof: Cored e tool open	intervals and al , flowing and sh	I drill-stem aut-in pressures		31. Forma	ation (Log) Markei	rs	
Formati	ion	Тор	Bottom		Descritpion,	Contents, etc.			Name		Top Meas, Depth
	ł	1						Wasatc	h Tongue		3857'
	İ	1		1				Uteland	Limestone		4208'
				1		1 .		Wasata			4353'
				1				Chapita			5271'
								Uteland			6407'
	1							Mesave	rde		7068'
	1	j		İ							1
	-						J				İ
	j	I		1			j				
		1		1			l				
							i			·	
	l						1				ļ
				.]			I				
		I		1			į				
			·	<u> </u>							
32. Additional re	emarks (inclu	ide plugging r	rocedure)								
		ao piagging t	oroccutie,								
	· · · · · · · · · · · · · · · · · · ·										
33. Circle enclo											
	al/Mechanical			2. G	eologic Report	3.	DST Rep	ort	4. Directional S	urvey	
5. Sundry	Notice for plu	gging and cei	ment verification	6. C	ore Analysis	7.	Other:				
4. I hereby cert	tify that the fo	regoing and a	attached informatio	n is comple	ete and correct a	as determined fi	rom all av	ailable rec	ords (see attache	d instructions)*	
Name (pleas	se print)	Carla C	hristian				Title	Sr.Re	gulatory Spec	ialist	
C: :	C_{α}	10	la T.			· · · · · · · · · · · · · · · · · · ·					
Signature	<u> Cuu</u>	MY V	v (w)MC	m			Date	March	16, 2006		
itle 18 U.S.C. S	Section 1001 a	and Title 43 U	S.C. Section 121	2 make it a	crime for new	organ kanada at	a oned	£ !!			
ny false, fictitiou	us or fradulen	t statements	or representations	as to any n	natter within its	jurisdiction.	y and Will	rully to mai	te to any departm	ent or agency of	the United States



DIRECTIONAL & HORIZONTAL DRILLING SYSTEMS

DOMINION EXPLORATION & PRODUCTION

NATURAL BUTTES FIELD, UINTAH COUNTY, UTAH

(HILL CREEK UNIT) HCU 14-34F

SECTION 34, T10S, R20E

FINAL WELL REPORT



COMFIDENTIAL


AS DRILLED HCU 14-34F SECTION 34, T10S, R20E UINTAH COUNTY, UTAH



Completion (As Drilled)

Dominion E & P

Well: HCU 14-34F Field: River Bend Unit Uintah Co. Utah Sec. 34, T10S, R20E



Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	DLcg	TFace	VScc	Target
1	0.00	0.00	264.00	0.00	0.00	0.00	0.00	0.00	0.00	
ż	550.00	0.00	264.00	550.00	0.00	0.00	0.00	264.00	0.00	
3	1021.01	14.13	264.00	1016.25	-6.04	-57.47	3.00	264.00	57.79	
4	5335.94	14.13	264.00	5200.62	-116.15	-1105.09	0.00	0.00	1111.18	
5	6042.46	0.00	264.00	5900.00	-125.21	-1191.30	2.00	180.00	1197.86	
6	8092.46	0.00	264.00	7950.00	-125.21	-1191.30	0.00	264.00	1197.86	

WELL DETAILS

Name	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
HCU 14-34F	0.00	0.00	7141154.37	2158987.89	39°54'34.409N	109°39'04.220W	N/A

FORMATION TOP DETAILS

No. TVDPath MDPath Formation

1	3855.00	3948.33	Wasatch Tongue
2	4190.00	4293.78	Uteland Limestone
3	4330.00	4438.15	Wasatch
4	5150.00	5283.74	Chapita Wells
5	6300.00	6442.46	Uteland Buttes
6	7150.00	7292.46	Mesaverde

WELLPATH DETAILS

Original Hole

Rig: Ref. Datum:	es	L KB @ 5356	0.00ft
V.Section Angle	Origin +N/-S	Origin +E/-W	Starting From TV1
264.009	0.00	0.00	0.00

REFERENCE INFORMATION

Co-ordinate (N/E) Reference: Site Centre HCU 14-34F, True North Vertical (TVD) Reference: est. KB @ 5356' 0.00
Section (VS) Reference: Site Centre (0.00N,0.00E)
Measured Depth Reference: est. KB @ 5356' 0.00
Calculation Method: Minimum Curvature



zimuths to True North Ingnetic North: 11.88* Magnetic Field Strength: 52904nT

Ingretic Field gth: 52904nT Angle: 65.92* ste: 6/27/2005 odel: igrf2005

FIELD DETAILS

Natural Buttes Field Jintah County, Utah USA

Geodetic System: US State Plane Coordinate System 1983 Ellipsoid: GRS 1980 Zone: Utah, Central Zone

ignetic Model: igrt2005

System Datum: Mean Sea Level Local North: True North

Vertical Section at 264.00° [1000ft/in]

SITE DETAILS

HCU 14-34F Hill Creek Unit Sec. 34, T10S, R20E

Site Centre Latitude: 39°54'34.409N Longitude: 109°39'04,220W

Ground Level: 5338.00 ositional Uncertainty: 0.00 Convergence: 1.18



SURVEY REPORT - STANDARD

HCU 14-34F

SECTION 34, T10S, R20E

UINTAH COUNTY, UTAH



Ryan Energy Technologies Survey Report



Company: Dominion E & P Field: Natural Buttes Field Site:

HCU 14-34F HCU 14-34F Well: Wellpath: Original Hole Date: 1/5/2006 Time: 17:28:32

Page: Co-ordinate(NE) Reference: Site: HCU 14-34F, True North Vertical (TVD) Reference: est. KB @ 5356' 0.0 Section (VS) Reference: Site (0.00N,0.00E,264.00Azi)

Survey Calculation Method: Minimum Curvature Db: Sybase

Field:

Natural Buttes Field

Uintah County, Utah

USA

Map SystemUS State Plane Coordinate System 1983

Geo Datum GRS 1980 Sys Datum: Mean Sea Level Map Zone:

Utah, Central Zone

Coordinate System: Site Centre Geomagnetic Model: igrf2005

Site:

HCU 14-34F Hill Creek Unit

Sec. 34, T10S, R20E

Site Position: Geographic From:

Northing: 7141154.37 ft Easting: 2158987.89 ft

39 34.409 N Latitude: 109 39 Longitude:

4.220 W True

Position Uncertainty: Ground Level:

0.00 ft 5338.00 ft North Reference: Grid Convergence:

1.18 deg

HCU 14-34F Surface Position: +N/-S

0.00 ft Northing: 7141154.37 ft Latitude:

39 34.409 N 39 4.220 W 109

+E/-W 0.00 ft Position Uncertainty: 0.00 ft Reference Point: +N/-S

0.00 ft 0.00 ft +F/-W

Easting: 2158987.89 ft Longitude: Northing: 7141154.37 ft Latitude:

Slot Name:

39 54 34.409 N 109 39 4.220 W

Easting: 2158987.89 ft Measured Depth: 0.00 ft Vertical Depth: 0.00 ft

Longitude: Inclination: Azimath:

0.00 deg 0.00 deg

Wellpath: Original Hole

Current Datum: est. KB @ 5356' Magnetic Data:

6/27/2005 52904 nT Vertical Section: Depth From (TVD)

0.00 ft Height

0.00

Drilled From: Tie-on Depth: Above System Datum: Mean Sea Level

Well Ref. Point 0.00 ft

Declination: Mag Dip Angle: +E/-W

11.88 deg 65.92 deg Direction

+N/-S ft ft

deg

As Drilled

ft

Start Date:

12/19/2005

264.00

Company: Ryan Energy Technologies Tool:

Engineer: Tied-to:

0.00

Mitch Kennedy **User Defined**

Survey: As Dritled

Field Strength:

Survey:

MD #	Incl deg	Azim deg	TVD ft	+N/-S ft	+E/-W	VS ft	DLS dec/100	Build	Turn Oft deg/100ft	Tool/Comment	
ft							/ - 41/4				
550.00	0.00	264.00	550.00	0.00	0.00	0.00	0.00	0.00	0.00	KOP	
568.00	0.50	63.30	568.00	0.04	0.07	-0.07	2.78	2.78	0.00		
660.00	2.20	264.30	659.98	0.04	-1.33	1.32	2.91	1.85	-172.83		
756.00	6.70	256.20	755.67	-1.48	-8.60	8.71	4.72	4.69	-8.44		
852.00	11.10	253.00	850.49	-5.52	-22.89	23.34	4.61	4.58	-3.33		
946.00	13.90	253.50	942.25	-11.37	-42.37	43.33	2.98	2.98	0.53		
1027.00	15.10	257.00	1020.67	-16.51	-61.98	63.37	1.83	1.48	4.32		
1119.00	14.80	258.50	1109.56	-21.55	-85.17	86.96	0.53	-0.33	1.63		
1213.00	13.70	262.50	1200.67	-25.39	-107.97	110.04	1.57	-1.17	4.26		
1308.00	13.40	270.30	1293.03	-26.81	-130.14	132.23	1.95	-0.32	8.21		
1402.00	13.90	272.20	1384.38	-26.31	-152.31	154.23	0.71	0.53	2.02		
1497.00	13.20	261.60	1476.74	-27.46	-174.45	176.36	2.71	-0.74	-11.16		
1591.00	13.50	247.00	1568.23	-33.32	-195.17	197.58	3.59	0.32	-15.53		
1686.00	14.60	241.40	1660.39	-43.38	-215.89	219.24	1.84	1.16	-5.89		
1780.00	14.70	245.80	1751.34	-53.94	-237.17	241.51	1.19	0.11	4.68		
1876.00	14.20	251.20	1844.31	-62.73	-259.43	264.57	1.50	-0.52	5.62		
1969.00	14.90	260.90	1934.34	-68.30	-282.04	287.63	2.72	0.75	10.43		
2064.00	15.90	267.10	2025.93	-70.89	-307.10	312.82	2.03	1.05	6.53		
2158.00	18.20	266.90	2115.79	-72.34	-334.62	340.35	2.45	2.45	-0.21		
2252.00	16.20	262.70	2205.59	-74.80	-362.29	368.12	2.50	-2.13	-4.47		



Ryan Energy Technologies Survey Report



Company: Dominion E & P Field: Natural Buttes Field Site: HCU 14-34F Well: HCU 14-34F Wellpath: Original Hole

Page:

Date: 1/5/2006 Time: 17:28:32 Pa Co-ordinate(NE) Reference: Site: HCU 14-34F, True North Vertical (TVD) Reference: est. KB @ 5356*0.0 Section (VS) Reference: Site (0.00N,0.00E,264.00Azi) Survey Calculation Method: Minimum Curvature Di

Db: Sybase

Survey: As Drilled

Survey: A	28 - 27 - 27			1_32 8	2274 2222				78.0.2.	Teel/Comment
MD	Incl	Azim	TVD	+N/-S	+ E /-W	VS ft	DLS dec/1006	Build deg/100	Turn ft deg/100ft	Tool/Comment
g fit	deg	deg	ft	ft	ft					
2347.00	15.90	259.20	2296.89	-78.92	-388.22	394.34	1.07	-0.32	-3.68	
2439.00	15.50	260.00	2385.45	-83.41	-412.70	419.16	0.49	-0.43	0.87	
2534.00	16.00	266.70	2476.89	-86.37	-438.27	444.90	1.98	0.53	7.05	
2628.00	18.60	267.80	2566.64	-87.69	-466.19	472.81	2.79	2.77	1.17	
2828.00	21.20	271.10	2754.68	-88.22	-534.24	540.53	1.42	1.30	1.65	
2920.00	20.50	268.80	2840.66	-88.24	-566.97	573.09	1.17	-0.76	-2.50	
3015.00	17.90	267.10	2930.37	-89.33	-598.19	604.25	2.80	-2.74	-1.79	
3109.00	15.20	270.10	3020.47	-90.04	-624.95	630.93	3.01	-2.87	3.19	
3203.00	13.90	268.70	3111.45	-90.27	-648.56	654.44	1.43	-1.38	-1.49	
3298.00	13.50	265.00	3203.75	-91.50	-671.01	676.90	1.01	-0.42	-3.89	
				04 47	600.06	698.41	1.35	-0.84	-4.63	
3393.00	12.70	260.60	3296.28	-94.17	-692.36			0.22	-1.29	
3486.00	12.90	259.40	3386.97	-97.75	-712.65	718.97	0.36 1.03	0.22 0.95	-1.2 9 1.79	
3581.00	13.80	261.10	3479.40	-101.45	-734.27 -754.27	740.85	1.03 2.74	-2.66	-2.98	
3675.00	11.30	258.30	3571.15	-105.06	-754.37 -774.57	761.22	1.19	-2.00 -1.17	-2.96 1.28	
3769.00	10.20	259.50	3663.50	-108.44	-771.57	778.68	1.19	-1.17	1.20	
3863.00	9.70	261.80	3756.08	-111.09	-787.59	794.89	0.68	-0.53	2.45	
3958.00	11.60	273.30	3849.45	-111.68	-805.05	812.32	2.99	2.00	12.11	
4053.00	14.30	275.90	3942.03	-109.92	-826.26	833.23	2.91	2.84	2.74	
4147.00	14.90	275.00	4032.99	-107.68	-849.85	856.45	0.68	0.64	-0.96	
4242.00	14.50	273.40	4124.88	-105.91	-873.89	880.17	0.60	-0.42	-1.68	
4336.00	15.00	272.00	4215.79	-104.78	-897.79	903.83	0.65	0.53	-1.49	
4431.00	14.90	270.40	4307.57	-104.27	-922.29	928.14	0.45	-0.11	-1.68	
4525.00	14.90	269.20	4398.41	-104.35	-946.46	952.19	0.33	0.00	-1.28	
4620.00	14.30	269.40	4490.34	-104.65	-970.41	976.03	0.63	-0.63	0.21	
4714.00	14.40	268.90	4581.41	-104.99	-993.70	999.23	0.17	0.11	-0.53	
				405 70	4040.07	4000 45	0.66	0.52	-1.60	
4808.00	13.90	267.40	4672.56	-105.73	-1016.67	1022.15	0.66	-0.53 0.32	-1.60 -0.32	
4903.00	14.20	267.10	4764.72	-106.84	-1039.70	1045.18	0.32			
4998.00	14.00	264.10	4856.85	-108.61	-1062.77	1068.30	0.80	-0.21	-3.16 0.21	
5092.00	14.30	264.30	4948.00	-110.93	-1085.63	1091.28	0.32	0.32	0.21	
5187.00	13.80	263.40	5040.16	-113.40	-1108.56	1114.34	0.57	-0.53	-0.95	
5281.00	12.60	261.30	5131.68	-116.24	-1129.84	1135.80	1.37	-1.28	-2.23	
5376.00	11.00	260.70	5224.66	-119.27	-1149.02	1155.20	1.69	-1.68	-0.63	
5470.00	9.00	263.90	5317.23	-121.50	-1165.19	1171.50	2.21	-2.13	3.40	
5565.00	7.40	262.50	5411.26	-123.09	-1178.64	1185.05	1.70	-1.68	-1.47	
5659.00	5.50	262.70	5504.66	-124.45	-1189.11	1195.61	2.02	-2.02	0.21	
E7E 4 00	4.00		EE00 22	40E 4E	-1196.94	1203.46	1.64	-1.58	5.47	
5754.00	4.00	267.90	5599.33 5602.46	-125.15		1203.46	1.37	-1.28	-8.40	
5848.00	2.80	260.00	5693.16 5799.10	-125.67	-1202.48 -1205.74	1212.39	1.73	-1.26 -1.37	-29.68	
5943.00	1.50	231.80	5788.10	-126.84 132.65	-1205.74 -1213.41	1220.63	0.15	-0.15	0.65	
6433.00 8130.00	0.75 1.25	235.00 220.00	6278.00 7974.74	-132.65 -153.20	-1213.41	1243.65	0.13	0.03	-0.88	
	1.23	220.00								
8172.00	1.25	220.00	8016.73	-153.90	-1234.99	1244.31	0.00	0.00	0.00	TD (Projected)
					· · · · · · · · · · · · · · · · · · ·					

Annotation

MD ft	TVD ft			·	
550.00 8172.00	550.00 8016.73	KOP TD (Projected)			



Survey Report-Geographic HCU 14-34F SECTION 34, T10S, R20E UINTAH COUNTY, UTAH



Ryan Energy Technologies Survey Report - Geographic



Db: Sybase

Company: Dominion E & P **Natural Buttes Field** Field:

HCU 14-34F Site: **HCU 14-34F** Well: Wellpath: Original Hole

Time: 17:30:01 Date: 1/5/2006

Co-ordinate(NE) Reference: Site: HCU 14-34F, True North est. KB @ 5356 0.0 Vertical (TVD) Reference: Site (0.00N,0.00E,264.00Azi) Section (VS) Reference:

Survey Calculation Method: Minimum Curvature

Field:

Natural Buttes Field Uintah County, Utah

USA

Map SystemUS State Plane Coordinate System 1983

Geo Datum GRS 1980 Sys Datum: Mean Sea Level Map Zone:

Utah, Central Zone

Site Centre Coordinate System: igrf2005 Geomagnetic Model:

HCU 14-34F Site:

Hill Creek Unit

Sec. 34, T10S, R20E

Site Position: Geographic From: Position Uncertainty: Ground Level:

Northing: 7141154.37 ft 2158987.89 ft Easting:

Latitude: 109 Longitude:

34.409 N 39 54 39 4.220 W

North Reference: Grid Convergence: True 1.18 deg

Surface Position: +N/-S

Position Uncertainty:

Reference Point: +N/-S

HCU 14-34F

+E/-W

+E/-W

0.00 ft Northing: 7141154.37 ft 0.00 ft 0.00 ft

0.00 ft

0.00 ft

0.00 ft

5338.00 ft

Easting: 2158987.89 ft Northing: 7141154.37 ft

Latitude: Longitude:

Slot Name:

39 34.409 N 39 109 4.220 W

Latitude: Easting: 2158987.89 ft Longitude: Inclination:

34.409 N 39 109 39 4.220 W 0.00 deg 0.00 deg

Measured Depth: 0.00 ft Vertical Depth: 0.00 ft

Azimuth:

Drilled From:

Wellpath: Original Hole Current Datum: est. KB @ 5356' Magnetic Data:

Field Strength:

6/27/2005 52904 nT Height 0.00 ft Tie-on Depth: Above System Datum: Mean Sea Level Declination:

0.00 ft 11.88 deg

Well Ref. Point

Mag Dip Angle: +E/-W

65.92 deg Direction deg

12/19/2005

ft 0.00

ft 0.00

+N/-S

ft 0.00

264.00

Start Date:

As Drilled Company: Ryan Energy Technologies

Vertical Section: Depth From (TVD)

Tool:

Survey:

Engineer: Tied-to:

Mitch Kennedy **User Defined**

Survey: As Drilled

MD	Incl	Azim	TVD	+N/-S	+E/-W	Map Northing	Map Easting	C- La Deg Mi	titude> a Sec		Long Min	
ft	deg	deg	ft	ft	ft	ft	ft				1	
550.00	0.00	264.00	550.00	0.00	0.00	7141154.37	2158987.89	39 54	34.409 N		39	4.220 V
568.00	0.50	63.30	568.00	0.04	0.07	7141154.40	2158987.96	39 54	34.409 N		39	4.219 V
660.00	2.20	264.30	659.98	0.04	-1.33	7141154.38	2158986.57	39 54	34.409 N	109	39	4.237 V
756.00	6.70	256.20	755.67	-1.48	-8.60	7141152.71	2158979.32	39 54	34.394 N		39	4.330 V
852.00	11.10	253.00	850.49	-5.52	-22.89	7141148.38	2158965.13	39 54	34.354 N	109	39	4.514 V
946.00	13.90	253.50	942.25	-11.37	-42.37	7141142.12	2158945.77	39 54	34.297 N	109	39	4.764 V
1027.00	15.10	257.00	1020.67	-16.51	-61.98	7141136.58	2158926.27	39 54	34.246 N	109	39	5.015 V
1119.00	14.80	258.50	1109.56	-21.55	-85.17	7141131.06	2158903.19	39 54	34.196 N	109	39	5.313 V
1213.00	13.70	262.50	1200.67	-25.39	-107.97	7141126.75	2158880.47	39 54	34.158 N	109	39	5.606 V
1308.00	13.40	270.30	1293.03	-26.81	-130.14	7141124.88	2158858.34	39 54	34.144 N	109	39	5.890 V
1402.00	13.90	272.20	1384.38	-26.31	-152.31	7141124.91	2158836.16	39 54	34.149 N	109	39	6.175 V
1497.00	13.20	261.60	1476.74	-27.46	-174.45	7141123.31	2158814.05	39 54	34.138 N	109	39	6.459 V
1591.00	13.50	247.00	1568.23	-33.32	-195.17	7141117.02	2158793.45	39 54	34.080 N	109	39	6.725 V
1686.00	14.60	241.40	1660.39	-43.38	-215.89	7141106.53	2158772.95	39 54	33.980 N	109	39	6.991 V
1780.00	14.70	245.80	1751.34	-53.94	-237.17	7141095.53	2158751.89	39 54	33.876 N	109	39	7.264 V
1876.00	14.20	251.20	1844.31	-62.73	-259.43	7141086.29	2158729.82	39 54	33.789 N		39	7.550 V
1969.00	14.90	260.90	1934.34	-68.30	-282.04	7141080.25	2158707.33	39 54	33.734 N		39	7.840 V
2064.00	15.90	267.10	2025.93	-70.89	-307.10	7141077.15	2158682.33	39 54	33.708 N		39	8.161 V
2158.00	18.20	266.90	2115.79	-72.34	-334.62	7141075.13	2158654.84	39 54	33.694 N		39	8.514 V
2252.00	16.20	262.70	2205.59	-74.80	-362.29	7141072.10	2158627.23	39 54	33.670 N	109	39	8.870 V



Ryan Energy Technologies Survey Report - Geographic



Company: Dominion E & P Field: Natural Buttes F Natural Buttes Field

HCU 14-34F HCU 14-34F Site: Well: Wellpath: Original Hole Date: 1/5/2006 Time: 17:30:01

Page:

Co-ordinate(NE) Reference: Site: HCU 14-34F, True North
Vertical (TVD) Reference: est. KB @ 5356 0.0
Section (VS) Reference: Site (0.00N,0.00E,264.00Azi)
Survey Calculation Method: Minimum Curvature Di

Db: Sybase

Survey:	As	Drilled

Mile Reg	y. 765 Di						Map	Map	< Î.	atitude>	· < I	aneitud	_
18 deg deg ft ft ft ft ft ft ft ft ft ft ft ft ft	n 1	[ma]	A =1==	77/D	+N/_S	+87.00							
247.00			7.7										
2349.00 15.50 260.00 2365.45 -83.41 412.70 7141082.44 2183877.01 39 54 33.586 N 109 39 2534.00 16.00 286.70 2476.89 -86.37 4382.77 7141058.95 2185851.50 39 54 33.565 N 109 39 2628.00 18.00 2771.10 2754.68 -86.22 -534.24 7141057.06 2158523.61 39 54 33.556 N 109 39 2628.00 21.20 2771.10 2754.68 -86.22 -534.24 7141055.12 215845.50 39 54 33.556 N 109 39 1305.00 17.90 267.10 2930.37 -83.33 -598.19 7141052.69 2158531.68 39 54 33.552 N 109 39 1305.00 17.90 267.10 2930.37 -83.33 -598.19 7141052.69 2158391.68 39 54 33.527 N 109 39 1305.00 15.20 270.10 3020.47 -00.04 -624.95 7141051.43 215834.94 39 54 33.519 N 109 39 1309.00 15.20 270.10 3020.47 -00.04 -624.95 7141051.43 2158341.34 39 54 33.519 N 109 39 1309.00 15.20 270.10 3020.47 -046.56 7141051.43 2158341.34 39 54 33.519 N 109 39 1309.00 15.20 250.00 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.505 N 109 39 1305.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.505 N 109 39 1305.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158218.92 39 54 33.406 N 109 39 1305.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158218.92 39 54 33.406 N 109 39 1305.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158218.92 39 54 33.406 N 109 39 1305.00 13.80 261.10 3479.40 -101.45 -734.27 7141037.76 2158255.88 39 54 33.406 N 109 39 13767.00 11.30 263.30 3571.15 -105.06 -754.37 7141037.76 2158255.88 39 54 33.3406 N 109 39 13767.00 10.20 259.50 3663.50 -108.44 -771.57 714103.00 2158218.73 39 54 33.357 N 109 39 13769.00 10.20 259.50 3663.50 -108.44 -771.57 714103.00 2158218.73 39 54 33.357 N 109 39 13769.00 11.50 277.30 3949.45 -111.68 -805.05 7141027.03 2158165.32 39 54 33.350 N 109 39 13769.00 11.50 277.30 3949.45 -111.68 -805.05 7141027.03 2158165.33 39 54 33.357 N 109 39 14417.00 14.50 275.00 403.299 -107.68 -805.65 7141027.03 2158165.33 39 54 33.357 N 109 39 14417.00 14.50 275.00 403.299 -107.68 -805.65 7141027.03 2158165.30 39 54 33.357 N 109 39 14417.10 14.50 275.00 403.299 -107.68 -805.65 7141027.03 2158165.30 39 54 33.357 N 109 39 14417.10 14.50					···	472							
2239.00 15.50 260.00 2354.5	00 1	5 90	259 20	2296.89	-78.92	-388.22	7141067.44	2158601.39	39 54		109 3	9.20	2 W
2524.00 16.00 266.70 2476.89 -68.37 -438.27 7141059.95 2158551.50 39 54 33.555 N 109 39 12828.00 21.20 271.10 2754.68 -88.22 -534.24 7141055.12 215825.61 39 54 33.557 N 109 39 12828.00 21.20 271.10 2754.68 -88.22 -534.24 7141055.12 215845.60 39 54 33.537 N 109 39 1305.00 17.00 267.10 2393.07 -89.33 -588.19 7141054.3 215824.89 39 54 33.557 N 109 39 1305.00 17.00 267.40 2303.07 -90.04 -824.95 7141054.3 2158348.69 39 54 33.557 N 109 39 1305.00 15.20 270.10 3020.47 -90.04 -824.95 7141051.43 2158348.69 39 54 33.519 N 109 39 13203.00 13.50 268.70 311.45 -90.27 -88.56 7141051.43 2158348.69 39 54 33.519 N 109 39 13203.00 13.50 268.70 311.45 -90.27 -88.56 7141051.43 2158349.49 39 54 33.519 N 109 39 13369.00 13.50 268.70 316.45 -90.27 -88.56 7141051.43 2158349.59 39 54 33.519 N 109 39 13383.00 12.70 260.60 3296.28 -94.17 -892.36 7141051.31 2158247.41 39 54 33.519 N 109 39 13486.00 12.00 259.40 3368.97 -97.75 -712.65 7141031.49 1258277.41 39 54 33.478 N 109 39 13675.00 11.30 258.30 3571.15 -105.06 -754.37 7141031.77 2158255.88 39 54 33.478 N 109 39 13675.00 11.20 258.30 3571.15 -105.06 -754.37 714103.77 2158255.88 39 54 33.371 N 109 39 13675.00 11.20 259.50 3663.50 -106.44 -771.57 714103.77 2158255.88 39 54 33.371 N 109 39 1365.00 11.60 273.30 3849.45 -110.89 -80.50 7141027.03 2158216.73 39 54 33.371 N 109 39 14417.00 14.90 275.00 4032.99 -107.68 -848.95 7141027.99 215804.04 39 54 33.345 N 109 39 14447.00 14.90 270.40 4307.57 -104.78 -805.55 7141027.99 2158014.03 39 54 33.345 N 109 39 14430.00 14.90 270.40 4307.57 -104.78 -805.55 7141027.99 2158014.03 39 54 33.345 N 109 39 14405.00 14.40 288.90 4581.41 -104.99 -893.70 714103.00 2158016.73 39 54 33.345 N 109 39 14405.00 14.90 270.40 4307.57 -104.78 -805.55 7141027.99 2158116.00 39 54 33.345 N 109 39 14405.00 14.90 270.40 4307.57 -104.78 -805.55 -90.50 270.40 4307.57 -104.78 -805.55 -90.50 270.40 4307.57 -104.78 -805.55 -90.50 270.40 4307.57 -104.78 -805.55 -90.50 270.00 421.50 270.00 421.50 270.00 421.50 270.00 421.50 270.00 421.50 270.00 421.50 270.00 421.50 270.00 421.50					-83.41	-412.70	7141062.44	2158577.01	39 54	33.585 N	109 3	9.51	7 W
2828.00							7141058.95	2158551.50	39 54	33.555 N	109 3	9.84	5 W
2828.00								2158523.61	39 54		109 3	9 10.20	IS W
2820.00								2158455.60	39 54	33.537 N	109 3	9 11.07	'6 V
3015.00 17.90 267.10 2930.37 -89.33 -598.19 7141052.69 2158391.68 39 54 33.578 N 109 39 1 3109.00 15.20 270.10 3020.47 -90.04 -624.95 7141051.43 2158364.94 39 54 33.578 N 109 39 1 3298.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.519 N 109 39 1 3393.00 12.70 260.60 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.517 N 109 39 1 3893.00 12.70 260.60 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.517 N 109 39 1 3893.00 12.90 259.40 3386.97 -97.75 -712.65 7141045.91 2158277.41 39 54 33.443 N 109 39 1 3891.00 13.80 261.10 3479.40 -101.45 -734.27 7141045.91 2158277.41 39 54 33.443 N 109 39 1 3768.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 3768.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 3895.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.3371 N 109 39 1 3443.00 14.90 275.00 4032.99 -107.68 -849.85 714102.60 72158185.32 39 54 33.3371 N 109 39 1 4447.00 14.90 275.00 4032.99 -107.68 -849.85 714102.915 2158140.45 39 54 33.322 N 109 39 1 4430.00 14.90 275.00 4032.99 -107.68 -849.85 714102.915 2158140.45 39 54 33.336 N 109 39 1 4430.00 14.90 270.40 4307.57 -104.27 -922.99 7141031.06 2158067.95 39 54 33.378 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.99 7141031.06 2158067.95 39 54 33.378 N 109 39 1 4432.00 14.00 269.00 4307.57 -104.27 -922.99 7141031.06 2158067.95 39 54 33.378 N 109 39 1 4431.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.06 2157996.57 39 54 33.378 N 109 39 1 4431.00 14.40 268.90 4581.41 -104.99 -993.70 714102.80 2157905.00 39 54 33.378 N 109 39 1 5187.00 13.80 267.40 4672.56 -105.73 -106.64 -1093.70 714102.80 2157905.00 39 54 33.336 N 109 39 1 5187.00 13.80 267.40 4672.56 -105.73 -104.65 -970.41 714102.80 2157905.00 39 54 33.358 N 109 39 1 5187.00 13.80 267.40 450.56 511.66 -105.73 -104.65 -970.41 714102.80 2157905.00 39 54 33.358 N 109 39 1 5187.00 13.80 267.40 450.56 511.66 -105.73 -104.65 -970.41 714102.80 2157905.00 39 54 33.358 N 109 39 1 5187.00	_	- 1.40	2	2.000									
3109.00 15.20 270.10 3020.47 90.04 624.95 7141051.43 2158348.49 39 54 33.517 N 109 39 1 3203.00 13.90 268.70 3111.45 90.27 648.56 7141050.71 2158341.34 39 54 33.517 N 109 39 1 33298.00 13.50 265.00 3203.75 91.50 671.01 7141049.02 2158341.34 39 54 33.517 N 109 39 1 3399.00 12.70 260.60 3296.28 94.17 692.36 7141045.91 2158277.41 39 54 33.505 N 109 39 1 3868.00 12.90 259.40 3386.97 97.75 712.65 7141041.91 2158277.41 39 54 33.406 N 109 39 1 39763.00 13.80 261.10 3479.40 101.45 734.27 7141037.76 2158255.88 39 54 33.406 N 109 39 1 39769.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 3969.00 11.30 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 39856.00 11.60 273.30 3849.45 -111.68 805.05 7141027.03 2158025.73 39 54 33.331 N 109 39 1 4447.00 14.90 275.00 4032.99 -107.68 849.85 7141029.15 2158163.52 39 54 33.305 N 109 39 1 4447.00 14.90 275.00 4032.99 -107.68 849.85 7141029.15 2158140.45 39 54 33.322 N 109 39 1 4437.00 14.90 275.00 4032.99 -107.68 849.85 7141029.15 2158140.45 39 54 33.345 N 109 39 1 4436.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.05 2158067.95 39 54 33.373 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.05 2158067.95 39 54 33.378 N 109 39 1 4431.00 14.90 270.40 4508.41 -104.65 -970.41 7141028.60 2158067.95 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 2158067.95 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 2158067.95 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 2158067.95 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 215795.62 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 215795.62 39 54 33.378 N 109 39 1 4400.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.60 215795.62 39 54 33.378 N 109 39 1 4400.00 14.00 267.00 267.00 467.25 106.84 109.90 -106.64 1009.70 7141028.60 215795.82 39 54 33.378 N 109 39 1 5400.00 10.00 267.00 267.00 267.00 267.00 267													
3203.00 13.90 288.70 3111.45 -90.27 -648.56 7141050.71 2158341.34 39 54 33.517 N 109 39 1 3298.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.505 N 109 39 1 3393.00 12.70 260.60 3296.28 -94.17 -692.36 7141045.91 2158277.41 39 54 33.478 N 109 39 1 3486.00 12.90 258.40 3366.97 -97.75 -712.65 7141041.91 2158277.41 39 54 33.478 N 109 39 1 3581.00 13.80 261.10 3479.40 -101.45 -734.27 7141037.76 2158255.88 39 54 33.406 N 109 39 1 3675.00 11.30 258.30 3571.15 -105.06 -754.37 7141037.76 2158255.88 39 54 33.478 N 109 39 1 3769.00 10.20 2595.00 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -805.05 7141028.07 2158218.73 39 54 33.305 N 109 39 1 4147.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.324 N 109 39 1 4447.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.325 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.72 -922.29 7141031.06 2158067.95 39 54 33.373 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158067.95 39 54 33.373 N 109 39 1 4525.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158067.95 39 54 33.373 N 109 39 1 4525.00 14.90 299.00 4581.41 -104.35 -946.46 7141028.08 215801.88 39 54 33.373 N 109 39 1 44714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.08 215801.88 39 54 33.371 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.08 215801.88 39 54 33.371 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.08 215801.88 39 54 33.371 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.08 2158796.57 39 54 33.371 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.08 2158796.57 39 54 33.371 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.08 2158796.57 39 54 33.371 N 109 39 1 4500.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.08 215796.57 39 54 33.328 N 109 39 1 5092.00 14.30 267.40 4672.56 -105.73 -106.67 7141028.08 215796.57 39 54 33.328 N 109 39 1 5092.00 14.30 263.00 570.60 5693.16 -105.67 -105.67							7141052.69						
3298.00 13.50 265.00 3203.75 -91.50 -671.01 7141049.02 2158318.92 39 54 33.505 N 109 39 1 3393.00 12.70 260.60 3296.28 -94.17 -692.36 7141045.91 2158277.61 39 54 33.478 N 109 39 1 3486.00 12.90 259.40 3386.97 -97.75 -712.65 7141041.91 2158277.61 39 54 33.443 N 109 39 1 3675.00 11.30 258.30 3571.15 -105.06 -754.37 7141033.76 2158255.88 39 54 33.461 N 109 39 1 3675.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.40 2158235.86 39 54 33.371 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -805.05 7141028.07 2158185.32 39 54 33.305 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -805.05 7141028.07 2158185.32 39 54 33.305 N 109 39 1 4053.00 14.30 275.90 3942.03 -109.92 -826.26 7141027.39 2158164.08 39 54 33.350 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141030.42 2158218.73 39 54 33.352 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.76 -897.79 7141030.42 2158163.33 39 54 33.362 N 109 39 1 4362.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.05 2158092.46 39 54 33.373 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.05 2158092.85 39 54 33.373 N 109 39 1 4420.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.06 2158043.79 39 54 33.377 N 109 39 1 4408.00 14.90 269.20 4398.41 -104.59 -993.70 7141028.06 2158043.79 39 54 33.377 N 109 39 1 4408.00 14.90 269.20 4398.41 -104.99 -993.70 7141028.06 2158043.79 39 54 33.377 N 109 39 1 4408.00 14.90 269.20 4398.41 -104.65 -970.41 7141028.06 2157950.62 39 54 33.371 N 109 39 1 4408.00 14.90 267.40 4676.72 -106.84 -1039.70 7141028.06 2157950.62 39 54 33.371 N 109 39 1 4408.00 14.90 267.40 4665.85 -108.61 -1062.77 7141028.06 2157950.62 39 54 33.371 N 109 39 1 4408.00 14.90 267.40 4665.85 -108.61 -1062.77 7141028.06 2157950.62 39 54 33.371 N 109 39 1 4408.00 14.90 267.40 4665.85 -108.61 -1062.77 7141028.06 2157950.62 39 54 33.350 N 109 39 1 4408.00 14.90 267.40 4665.85 -108.61 -1062.77 7141028.06 2157950.62 39 54 33.350 N 109 39 1 4408.00 14.90 267.00 5224.66 -119.27 -1140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140.00 140	.00 1	15.20	270.10	3020.47									
3393.00 12.70 260.60 3296.28 -94.17 -692.36 7141045.91 2158297.63 39 54 33.478 N 109 39 1 3486.00 12.90 259.40 3386.97 -97.75 -712.65 7141041.91 2158277.41 39 54 33.443 N 109 39 1 3581.00 13.80 261.10 3479.40 -101.45 -734.27 7141037.76 2158255.88 39 54 33.443 N 109 39 1 3769.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158235.86 39 54 33.371 N 109 39 1 3863.00 9.70 261.80 3756.08 -111.09 -767.59 7141027.03 2158203.83 39 54 33.371 N 109 39 1 3863.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.371 N 109 39 1 3863.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.337 N 109 39 1 4053.00 14.30 275.90 342.03 -109.92 -826.26 7141027.03 2158185.32 39 54 33.305 N 109 39 1 4147.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.325 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141031.05 215804.85 39 54 33.362 N 109 39 1 4336.00 15.00 270.40 4307.57 -104.27 -922.29 7141031.05 2158067.95 39 54 33.373 N 109 39 1 4525.00 14.90 259.20 4398.41 -104.36 -946.46 7141030.42 2158016.38 39 54 33.378 N 109 39 1 4420.00 14.90 259.20 4398.41 -104.36 -946.46 7141030.47 2158043.79 39 54 33.378 N 109 39 1 4420.00 14.90 259.20 4398.41 -104.36 -946.46 7141030.47 2158043.79 39 54 33.378 N 109 39 1 4420.00 14.90 259.20 4398.41 -104.36 -946.46 7141030.47 2158043.79 39 54 33.378 N 109 39 1 4420.00 14.90 269.20 4398.41 -104.36 -946.46 7141030.47 2158043.79 39 54 33.378 N 109 39 1 4420.00 14.90 269.20 4398.41 -104.36 -946.46 7141030.47 2158043.79 39 54 33.378 N 109 39 1 4420.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4582.00 14.90 269.20 4398.00 14.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.371 N 109 39 1 4598.00 14.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.320 N 109 39 1 5092.00 14.30 264.10 4866.85 -108.61 -106.77 7141028.86 2157996.57 39 54 33.320 N 109 39 1 5092.00 14.30 264.10 4866.85 -108.61 -106.77 141027.65 2157973.63 39 54 33.320 N 109 39 1 5092.00 14.30 264.10 4866.8	.00 1	13.90	268.70	3111.45	-90.27								
3486.00	.00 1	13.50	265.00	3203.75	-91.50	-671.01	7141049.02	2158318.92	39 54	33.505 N	109 3	39 12.83	12 V
3486.00	00 1	12.70	260.60	2206.28	-04 17	-602 36	7141045 91	2158297 63	39 54	33.478 N	109 3	39 13.10)6 V
3881.00													
3675.00 11.30 258.30 3571.15 -105.06 -754.37 7141033.74 2158235.86 39 54 33.371 N 109 39 1 3769.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.337 N 109 39 1 3863.00 9.70 261.80 3756.08 -111.68 -905.05 7141027.03 2158202.77 39 54 33.311 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -905.05 7141027.03 2158164.08 39 54 33.305 N 109 39 1 4053.00 14.30 275.90 4932.99 -107.68 -849.85 7141029.15 2158164.08 39 54 33.322 N 109 39 1 4147.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.325 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141031.02 2158164.08 39 54 33.362 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158067.95 39 54 33.373 N 109 39 1 4525.00 14.90 269.20 4398.41 -104.35 -946.46 7141031.05 2158067.95 39 54 33.374 N 109 39 1 4525.00 14.30 269.40 4490.34 -104.65 -970.41 7141024.08 2158067.95 39 54 33.374 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.95 -993.70 7141028.08 2157996.57 39 54 33.374 N 109 39 1 4808.00 13.90 267.40 4672.56 -106.67 3 -106.67 7141029.69 2158019.86 39 54 33.374 N 109 39 1 4808.00 14.00 264.10 4856.85 -106.61 -1062.77 7141023.02 2157950.62 39 54 33.374 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157861.91 39 54 33.375 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157861.91 39 54 33.36N 109 39 1 5565.00 7.40 262.50 5411.26 -125.09 -110.84 7141008.42 2157861.91 39 54 33.36N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.42 2157860.70 39 54 33.28N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 2157860.70 39 54 33.200 N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 2157860.70 39 54 33.28N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 2157860.70 39 54 33.172 N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 2157860.70 39 54 33.172 N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 215786.67 39 54 33.172 N 109 39 1 5565.00 7.40 262.50 5411.26 -125.67 -120.48 7141008.94 2													
3769.00 10.20 259.50 3663.50 -108.44 -771.57 7141030.00 2158218.73 39 54 33.337 N 109 39 1 3863.00 9.70 261.80 3756.08 -111.09 -787.59 7141027.03 2158202.77 39 54 33.311 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -805.05 7141026.07 2158185.32 39 54 33.305 N 109 39 1 4053.00 14.30 275.90 3942.03 -109.92 -826.26 7141027.39 2158164.08 39 54 33.305 N 109 39 1 4147.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.345 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141030.42 2158116.38 39 54 33.362 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158092.46 39 54 33.378 N 109 39 1 4336.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158097.95 39 54 33.378 N 109 39 1 4625.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141029.69 2158019.86 39 54 33.378 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141028.08 2157975.63 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141026.06 2157950.62 39 54 33.371 N 109 39 1 4808.00 14.00 264.10 4856.85 -108.61 -1062.77 7141026.06 2157950.62 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.335 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157861.59 39 54 33.328 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157861.59 39 54 33.328 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157861.59 39 54 33.288 N 109 39 1 5281.00 12.60 263.90 5317.23 -121.50 -1165.19 7141006.94 2157812.05 39 54 33.280 N 109 39 1 5281.00 12.60 261.30 513.68 -116.24 -1129.84 714101.80 2157881.91 39 54 33.280 N 109 39 1 5281.00 12.60 261.30 5317.23 -121.50 -1165.19 7141006.94 2157812.05 39 54 33.280 N 109 39 1 5281.00 12.60 261.30 5316.6 -126.67 -1202.48 7141004.50 2157897.03 39 54 33.280 N 109 39 1 5281.00 12.60 260.00 5693.16 -125.67 -1202.48 7141004.50 215786.03 39 54 33.192 N 109 39 1 5281.00 1.50 231.80 5788.10 -126.84 -													
3863.00 9.70 261.80 3756.08 -111.09 -787.59 7141027.03 2158202.77 39 54 33.311 N 109 39 1 3958.00 11.60 273.30 3849.45 -111.68 -805.05 7141026.07 2158185.32 39 54 33.305 N 109 39 1 4053.00 14.30 275.00 4032.99 -107.68 -849.85 7141027.39 2158164.08 39 54 33.322 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141029.15 2158140.45 39 54 33.322 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158092.46 39 54 33.325 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158067.95 39 54 33.378 N 109 39 1 44262.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141026.06 2157950.62 39 54 33.337 N 109 39 1 4808.00 14.20 267.10 4764.72 -106.84 -1039.70 7141028.06 2157925.63 39 54 33.358 N 109 39 1 4908.00 14.30 264.30 4948.00 -110.93 -1065.63 7141021.82 2157927.59 39 54 33.351 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157807.79 39 54 33.352 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141026.06 215793.80 39 54 33.328 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141026.07 2157927.59 39 54 33.328 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141026.07 2157927.59 39 54 33.328 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157820.51 39 54 33.120 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157820.51 39 54 33.120 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157820.51 39 54 33.120 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157820.51 39 54 33.120 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157820.51 39 54 33.120 N 109 39 1 5564.00 1.50 233.00 5593.16 -125.67 -1202.48 7141004.50 2157793.80 39 54 33.120 N 109 39 1 5564.00 0.50 30 5593.16 -125.67 -1202.48													
3958.00 11.60 273.30 3849.45 -111.68 -905.05 7141026.07 2158185.32 39 54 33.305 N 109 39 1 4053.00 14.30 275.90 3942.03 -109.92 -826.26 7141027.39 2158164.08 39 54 33.322 N 109 39 1 4242.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.345 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141031.05 2158164.08 39 54 33.345 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158164.08 39 54 33.345 N 109 39 1 4336.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158067.95 39 54 33.373 N 109 39 1 4525.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141028.68 2158019.86 39 54 33.374 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2158019.86 39 54 33.374 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141028.68 2157996.57 39 54 33.371 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141028.06 2158079.59 39 54 33.335 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141028.08 2157927.59 39 54 33.335 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141010.80 2157881.91 39 54 33.280 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157881.91 39 54 33.280 N 109 39 1 5576.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.220 N 109 39 1 55659.00 5.50 262.70 5504.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.220 N 109 39 1 55659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141006.94 2157812.05 39 54 33.220 N 109 39 1 55843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141004.50 2157793.80 39 54 33.155 N 109 39 1 55430.00 1.50 231.80 5788.10 -126.84 -1205.74 7141004.50 2157785.02 39 54 33.155 N 109 39 1 55430.00 1.50 231.80 5788.10 -126.84 -1205.74 7141004.50 2157785.02 39 54 33.155 N 109 39 1 50430.00 1.50 231.80 5788.10 -126.84 -1205.74 7141004.50 2157785.02 39 54 33.155 N 109 39 1 30.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 21577756.92 39 54 33.155 N 109 39 1 30.00 1.25 220.00 7974.74 -153.20	.00 1	10.20	259.50	3663.50	-108.44	-11 1.31	7 14 1030.00	2130210.73	39 34	33.337 14	103 3	99 17.12	
3958.00	.00	9.70	261.80	3756.08	-111.09	-787.59	7141027.03	2158202.77	39 54				
14.30				3849.45	-111.68	-805.05	7141026.07	2158185.32	39 54			39 14.55	
1447.00 14.90 275.00 4032.99 -107.68 -849.85 7141029.15 2158140.45 39 54 33.345 N 109 39 1 4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141030.42 2158116.38 39 54 33.362 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158092.46 39 54 33.373 N 109 39 1 48525.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141029.69 2158019.86 39 54 33.374 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.374 N 109 39 1 4808.00 14.00 264.10 4764.72 -106.84 -1039.70 7141028.86 2157996.57 39 54 33.364 N 109 39 1 4898.00 14.00 264.10 4856.85 -108.61 -1062.77 7141028.86 2157997.59 39 54 33.335 N 109 39 1 5281.00 12.60 263.40 5040.16 -113.40 -110.85 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141018.08 2157860.70 39 54 33.288 N 109 39 1 55865.00 7.40 262.50 5411.26 -123.09 -1178.64 7141008.81 2157793.80 39 54 33.20 N 109 39 1 55754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141008.81 2157793.80 39 54 33.172 N 109 39 1 55848.00 2.80 267.90 5599.33 -125.67 -1202.48 7141008.67 2157795.69 2157795.03 39 54 33.374 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.365 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.365 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.365 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 1 30 54 33.364 N 109 39 54 33.378 N 109 39 54 33.378 N 109 39 54 33.378 N 109 39 54 33.378 N 109 39 54 33.378 N 109 39 54 33.378 N 109 39 54 33.368 N 109 39 54 33.368 N 109 39 54 33.368 N 109 39 54 3						-826.26	7141027.39	2158164.08	39 54	33.322 N	109 3		
4242.00 14.50 273.40 4124.88 -105.91 -873.89 7141030.42 2158116.38 39 54 33.362 N 109 39 1 4336.00 15.00 272.00 4215.79 -104.78 -897.79 7141031.05 2158092.46 39 54 33.373 N 109 39 1 4431.00 14.90 270.40 4307.57 -104.27 -922.29 7141031.06 2158067.95 39 54 33.378 N 109 39 1 4525.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141029.69 2158019.86 39 54 33.371 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.364 N 109 39 1 4903.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4903.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.351 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157861.70 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157861.70 39 54 33.208 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.208 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 215782.47 39 54 33.208 N 109 39 1 5655.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.120 N 109 39 1 5655.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.179 N 109 39 1 5648.00 2.80 260.00 5693.16 -125.67 -1202.48 7141008.93 2157785.03 39 54 33.172 N 109 39 1 5648.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5648.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157795.69 39 54 33.167 N 109 39 1 56433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140975.69 2157755.93 39 54 33.168 N 109 39 1 56433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140975.69 2157755.93 39 54 33.168 N 109 39 1 56433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140975.69 2157756.92 39 54 32.895 N 109 39 1 56433.00 0.75 235.00 6278.00 -132.6							7141029.15	2158140.45	39 54	33.345 N	109 3	39 15.12	27 \
4431.00							7141030.42	2158116.38	39 54	33.362 N	109 3	39 15.43	35 \
4431.00					44		7444004.00	0450000 40	20 54	22 272 N	400 3	39 15.74	12 V
4525.00 14.90 269.20 4398.41 -104.35 -946.46 7141030.47 2158043.79 39 54 33.377 N 109 39 1 4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141029.69 2158019.86 39 54 33.374 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.364 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141028.26 2157950.62 39 54 33.353 N 109 39 1 5092.00 14.30 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.351 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157860.70 39 54 33.208 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1176.64 7141006.94 215781.05 39 54 33.208 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157783.20 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.172 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157785.03 39 54 33.172 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157785.03 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157785.03 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157765.92 39 54 33.195 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157765.92 39 54 33.195 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157765.92 39 54 33.195 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.64 -1205.74 7141002.63 2157765.92 39 54 33.195 N 109 39 1 1100 1100 1100 1100 1100 1100													
4620.00 14.30 269.40 4490.34 -104.65 -970.41 7141029.69 2158019.86 39 54 33.374 N 109 39 1 4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.364 N 109 39 1 4993.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.167 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157793.80 39 54 33.175 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.167 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.167 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.167 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141002.63 2157778.27 39 54 33.165 N 109 39 1 5848.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 3130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
4714.00 14.40 268.90 4581.41 -104.99 -993.70 7141028.86 2157996.57 39 54 33.371 N 109 39 1 4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.364 N 109 39 1 4903.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157860.70 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141002.63 2157788.27 39 54 33.167 N 109 39 1 5843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 5843.00 0.75 235.00 6278.00 -132.65 -1213.41 7140096.67 2157756.92 39 54 33.098 N 109 39 1 5830.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
4808.00 13.90 267.40 4672.56 -105.73 -1016.67 7141027.65 2157973.63 39 54 33.364 N 109 39 1 4903.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.353 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141014.80 2157860.70 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157788.27 39 54 33.179 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.27 39 54 33.179 N 109 39 1 5848.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.175 N 109 39 1 5843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.175 N 109 39 1 5843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 5843.00 0.75 235.00 6278.00 -132.65 -1213.41 7140975.69 2157756.92 39 54 33.895 N 109 39 2													
4903.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.200 N 109 39 1 55659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 215778.27 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.172 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141003.87 215778.27 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 215778.27 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 215778.27 39 54 33.172 N 109 39 1 5843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157756.92 39 54 33.098 N 109 39 2 1 100 100 100 100 100 100 100 100 100	.00 1	14.40	268.90	4581.41	-104.99	-993.70	7141028.86	215/996.5/	39 54	33.371 N	109 3	39 16.97	3 1
4903.00 14.20 267.10 4764.72 -106.84 -1039.70 7141026.06 2157950.62 39 54 33.353 N 109 39 1 4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.200 N 109 39 1 55659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141006.94 2157812.05 39 54 33.172 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.172 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -126.574 7141003.63 2157785.03 39 54 33.175 N 109 39 1 5843.00 1.50 231.80 5788.10 -126.84 -1205.74 7141003.63 2157785.03 39 54 33.175 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141003.63 2157785.03 39 54 33.155 N 109 39 1 5943.00 1.55 235.00 6278.00 -132.65 -1213.41 7140975.69 2157756.92 39 54 33.098 N 109 39 2 1 100.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 33.985 N 109 39 2	00 1	13 90	267 40	4672 56	-105.73	-1016.67	7141027.65	2157973.63	39 54	33.364 N	109 3	39 17.26	38 N
4998.00 14.00 264.10 4856.85 -108.61 -1062.77 7141023.82 2157927.59 39 54 33.335 N 109 39 1 5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157860.70 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.208 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1198.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 6433.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2									39 54	33.353 N	109 3	39 17.56	34 \
5092.00 14.30 264.30 4948.00 -110.93 -1085.63 7141021.02 2157904.79 39 54 33.312 N 109 39 1 5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157860.70 39 54 33.288 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141004.50 2157783.80 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157788.27 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2									39 54	33.335 N	109 3	39 17.86	30 N
5187.00 13.80 263.40 5040.16 -113.40 -1108.56 7141018.08 2157881.91 39 54 33.288 N 109 39 1 5281.00 12.60 261.30 5131.68 -116.24 -1129.84 7141014.80 2157860.70 39 54 33.260 N 109 39 1 5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157776.92 39 54 33.098 N 109 39 2 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2									39 54	33.312 N	109 3	39 18.15	53 \
5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 21577785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2											109 3	39 18.44	۱7 ۱
5376.00 11.00 260.70 5224.66 -119.27 -1149.02 7141011.38 2157841.58 39 54 33.230 N 109 39 1 5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 21577785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
5470.00 9.00 263.90 5317.23 -121.50 -1165.19 7141008.81 2157825.47 39 54 33.208 N 109 39 1 5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 215788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2	.00 1	12.60											
5565.00 7.40 262.50 5411.26 -123.09 -1178.64 7141006.94 2157812.05 39 54 33.192 N 109 39 1 5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.172 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
5659.00 5.50 262.70 5504.66 -124.45 -1189.11 7141005.37 2157801.61 39 54 33.179 N 109 39 1 5754.00 4.00 267.90 5599.33 -125.15 -1196.94 7141004.50 2157793.80 39 54 33.172 N 109 39 1 5848.00 2.80 260.00 5693.16 -125.67 -1202.48 7141003.87 2157788.27 39 54 33.167 N 109 39 1 5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2	.00												
5754.00	.00			-									
5848.00	.00	5.50	262.70	5504.66	-124.45	-1189.11	7141005.37	2157801.61	39 54	33.179 N	109 3	39 19.48	51 \
5848.00	00	<i>4</i> 00	267.00	5500 33	-125 15	_1106 04	7141004 50	2157793 80	39 54	33.172 N	109 3	39 19.58	31 V
5943.00 1.50 231.80 5788.10 -126.84 -1205.74 7141002.63 2157785.03 39 54 33.155 N 109 39 1 6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
6433.00 0.75 235.00 6278.00 -132.65 -1213.41 7140996.67 2157777.49 39 54 33.098 N 109 39 1 8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
8130.00 1.25 220.00 7974.74 -153.20 -1234.40 7140975.69 2157756.92 39 54 32.895 N 109 39 2													
9172 00 1 25 220 00 8016 73 -153 90 -1234 99 7140974 98 2157756 35 39 54 32 888 N 109 39 2	.00	1.20	220.00	1917.17	- 100.20	1201.70	. 1-1007 0.00						
0112.00 1.20 220.00 0010.10 -100.00 -1204.00 1140014.00 2101100.00 00 04 02.00011 100 00 2	.00	1.25	220.00	8016.73	-153.90	-1234.99	7140974.98	2157756.35	39 54	32.888 N	109 3	39 20.07	O V

Annotation

MID ft	TVD ft		
550.00 172.00	550.00 8016.73	KOP TD (Projected)	



SURVEY REPORT - CLOSURE HCU 14-34F SECTION 34, T10S, R20E UINTAH COUNTY, UTAH



Ryan Energy Technologies Survey Report - Closure



Company: Dominion E & P Natural Buttes Field Field: HCU 14-34F Site:

Well: **HCU 14-34F** Wellpath: Original Hole Date: 1/5/2006 Time: 17:25:04 Co-ordinate(NE) Reference: Sits: HCU 14-34F, True North

est. KB @ 5356' 0.0 Site (0.00N,0.00E,264.00Azi) Vertical (TVD) Reference: Section (VS) Reference:

Survey Calculation Method: Minimum Curvature Db: Sybase

Natural Buttes Field Uintah County, Utah

USA

Map SystemidS State Plane Coordinate System 1983

Geo Datum GRS 1980 Sys Datum: Mean Sea Level Map Zone:

Utah, Central Zone

Coordinate System: Site Centre igrf2005 Geomagnetic Model:

Site:

HCU 14-34F Hill Creek Unit

Sec. 34, T10S, R20E

Site Position: Geographic From:

Northing: 7141154.37 ft 2158987.89 ft Easting:

Latitude:

34.409 N 39 54 109 39 4.220 W

0.00 ft

Longitude: North Reference:

True

Position Uncertainty: Ground Level:

5338.00 ft

Grid Convergence: Slot Name:

1.18 deg

HCU 14-34F

Well Position:

0.00 ft Northing: 7141154.37 ft 0.00 ft Easting: 2158987.89 ft

Latitude:

39 54 34.409 N

+F/-W

0.00 ft

Longitude:

109 39 4.220 W

Position Uncertainty:

+N/-S

Wellpath: Original Hole

Current Datum: est. KB @ 5356

0.00 ft Height

Drilled From: Tie-on Depth:

Well Ref. Point 0.00 ft Above System Datum: Mean Sea Level

6/27/2005

Magnetic Data: Field Strength: 52904 nT Vertical Section: Depth From (TVD) ft

ft

+N/-S ft 0.00

Declination: Mag Dip Augle:

11.88 deg 65.92 deg Direction

+E/-W ft deg

0.00

Survey Program for Definitive Wellpath Date: 1/5/2006 Actual From To

Validated: No Survey

Version:

Toolcode

0.00

Tool Name

264.00

Survey

ft

Survey		2728 C - 2 - 1	Carrier .	37/6	PAV	VS	DLS	ClsDist	ClsAzi	1. A	Comment
MD ft	Incl deg	Azim deg	TVD ft	N/S ft	E/W ft	ft :	deg/100ft	ft	deg	y 130	
550.00	0.00	264.00	550.00	0.00	0.00	0.00	0.00	0.00	0.00	KOP	
568.00	0.50	63.30	568.00	0.04	0.07	-0.07	2.78	0.08	63.30		
660.00	2.20	264.30	659.98	0.04	-1.33	1.32	2.91	1.33	271.74		
756.00	6.70	256.20	755.67	-1.48	-8.60	8.71	4.72	8.73	260.24		
852.00	11.10	253.00	850.49	-5.52	-22.89	23.34	4.61	23.54	256.44		
946.00	13.90	253.50	942.25	-11.37	-42.37	43.33	2.98	43.87	254.98		
1027.00	15.10	257.00	1020.67	-16.51	-61.98	63.37	1.83	64.14	255.08		
1119.00	14.80	258.50	1109.56	-21.55	-85.17	86.96	0.53	87.85	255.80		
1213.00	13.70	262.50	1200.67	-25.39	-107.97	110.04	1.57	110.92	256.77		
1308.00	13.40	270.30	1293.03	-26.81	-130.14	132.23	1.95	132.87	258.36		
1402.00	13.90	272.20	1384.38	-26.31	-152.31	154.23	0.71	154.57	260.20		
1497.00	13.20	261.60	1476.74	-27.46	-174.45	176.36	2.71	176.60	261.05		
1591.00	13.50	247.00	1568.23	-33.32	-195.17	197.58	3.59	197.99	260.31		
1686.00	14.60	241.40	1660.39	-43.38	-215.89	219.24	1.84	220.21	258.64		
1780.00	14.70	245.80	1751.34	-53.94	-237.17	241.51	1.19	243.23	257.19		
1876.00	14.20	251.20	1844.31	-62.73	-259.43	264.57	1.50	266.91	256.41		
1969.00	14.90	260.90	1934.34	-68.30	-282.04	287.63	2.72	290.19	256.39		
2064.00	15.90	267.10	2025.93	-70.89	-307.10	312.82	2.03	315.17	257.00		
2158.00	18.20	266.90	2115.79	-72.34	-334.62	340.35	2.45	342.35	257.80		
2252.00	16.20	262.70	2205.59	-74.80	-362.29	368.12	2.50	369.93	258.33		
2347.00	15.90	259.20	2296.89	-78.92	-388.22	394.34	1.07	396.16	258.51		
2439.00	15.50	260.00	2385.45	-83.41	-412.70	419.16	0.49	421.05	258.57		
2534.00	16.00	266.70	2476.89	-86.37	-438.27	444.90	1.98	446.70	258.85		



Ryan Energy Technologies Survey Report - Closure



Page:

Company: Dominion E & P Field: Natural Buttes F Natural Buttes Field

HCU 14-34F HCU 14-34F Site: Well: Wellpath: Original Hole

Date: 1/5/2006 Time: 17:25:04 Pa Co-ordinate(NE) Reference: Site: HCU 14-34F, True North Vertical (TVD) Reference: est KB @ 5356*0.0 Section (VS) Reference: Site (0.00N,0.00E,264.00Azi) Survey Calculation Method: Minimum Curvature Db

Db: Sybase

Survey			£11. • A	755/70	N/S	E/W	VS	DLS	ClsDist	ClsAzi	Commen
MD ft		Incl deg	Azim deg	TVD ft	nys ft	ft	ft	deg/100ft	ft	deg	
2628.	00	18.60	267.80	2566.64	-87.69	-466.19	472.81	2.79	474.37	259.35	
2828.		21.20	271.10	2754.68	-88.22	-534.24	540.53	1.42	541.47	260.62	
2920.	00	20.50	268.80	2840.66	-88.24	-566.97	573.09	1.17	573.80	261.15	
2920. 3015.		17.90	267.10	2930.37	-89.33	-598.19	604.25	2.80	604.82	261.51	
3109.		15.20	270.10	3020.47	-90.04	-624.95	630.93	3.01	631.40	261.80	
3203.		13.90	268.70	3111.45	-90.27	-648.56	654.44	1.43	654.81	262.08	
3298.		13.50	265.00	3203.75	-91.50	-671.01	676.90	1.01	677.22	262.24	
0000	00	40.70	260.60	3296.28	-94.17	-692.36	698.41	1.35	698.74	262.25	
3393.		12.70 12.90	259.40	3296.26	-97.75	-712.65	718.97	0.36	719.33	262.19	
3486		13.80	261.10	3479.40	-101.45	-734.27	740.85	1.03	741.25	262.13	
3581		11.30	258.30	3571.15	-105.06	-754.37	761.22	2.74	761.65	262.07	
3675. 3769		10.20	259.50	3663.50	-108.44	-771.57	778.68	1.19	779.15	262.00	
			004.00	0756 00	-111.09	-787.59	794.89	0.68	795.39	261.97	
3863		9.70	261.80	3756.08 3849.45	-111.68	-805.05	812.32	2.99	812.76	262.10	
3958		11.60	273.30	3942.03	-109.92	-826.26	833.23	2.91	833.54	262.42	
4053		14.30	275.90	3942.03 4032.99	-109.92	-849.85	856.45	0.68	856.64	262.78	
4147 4242		14.90 14.50	275.00 273.40	4032.99 4124.88	-107.00	-873.89	880.17	0.60	880.28	263.09	
					404.70	007.70	903.83	0.65	903.89	263.34	
4336		15.00	272.00	4215.79	-104.78	-897.79 -922.29	928.14		928.17	263.55	
4431		14.90	270.40	4307.57	-104.27 -104.35	-922.29 -946.46	952.19		952.20	263.71	
4525		14.90	269.20	4398.41 4490.34	-104.35 -104.65	-940.40 -970.41	976.03		976.03	263.85	
4620		14.30	269.40		-104.05	-993.70	999.23		999.23	263.97	
4714	1.00	14.40	268.90	4581.41	-104.55	-993.10	333.20				
4808	3.00	13.90	267.40	4672.56	-105.73	-1016.67	1022.15		1022.15	264.06	
4903		14.20	267.10	4764.72	-106.84	-1039.70	1045.18		1045.18	264.13	
4998		14.00	264.10	4856.85	-108.61	-1062.77	1068.30		1068.31	264.17	
5092	2.00	14.30	264.30	4948.00	-110.93	-1085.63	1091.28		1091.29	264.17	
5187	7.00	13.80	263.40	5040.16	-113.40	-1108.56	1114.34	0.57	1114.35	264.16	
5281	.00	12.60	261.30	5131.68	-116.24	-1129.84	1135.80		1135.80	264.13	
5376	3.00	11.00	260.70	5224.66	-119.27	-1149.02	1155.20		1155.20	264.07	
5470		9.00	263.90	5317.23	-121.50	-1165.19	1171.50		1171.50	264.05	
5565		7.40	262.50	5411.26	-123.09	-1178.64	1185.05		1185.05	264.04	
5659		5.50	262.70	5504.66	-124.45	-1189.11	1195.61	2.02	1195.61	264.03	
5754	1.00	4.00	267.90	5599.33	-125.15	-1196.94	1203.46	1.64	1203.46	264.03	
5848		2.80	260.00	5693.16	-125.67	-1202.48	1209.03	1.37	1209.03	264.03	
5943		1.50	231.80	5788.10	-126.84	-1205.74	1212.39		1212.39	263.99	
6433		0.75	235.00	6278.00	-132.65	-1213.41	1220.63		1220.64	263.76	
8130		1.25	220.00	7974.74	-153.20	-1234.40	1243.65	0.03	1243.87	262.93	
8172	200	1.25	220.00	8016.73	-153.90	-1234.99	1244.31	0.00	1244.54	262.90	TD (Projected)

Division of Oil, Gas and Mining

OPERATOR CHANGE WORKSHEET

	ROUTING
	1. DJJ
ĺ	2. CDW

X - Change of (Operator ((Well	Sold)
-----------------	------------	-------	-------

X - Change of Operator (Well Sold)				Operator Name Change/Merger						
The operator of the well(s) listed below has changed, effective:				7/1/2007						
FROM: (Old Operator):				TO: (New Or	perator):					
N1095-Dominion Exploration & Production, Inc			N2615-XTO E							
14000 Quail Springs Parkway, Suite 600				uston St						
Oklahoma City, OK 73134				Fort Wo	orth, TX 76	5102				
Phone: 1 (405) 749-1300				Phone: 1 (817)	870-2800					
CA No.		·		<u> </u>	2, 2 2000	HILL CH	PEEK			
WELL NAME	SE/	TWN	DNC	Unit: API NO	ENTITY	LEASE TYPE		WELL		
A PPP MAINT	SEC	~ T AATA	MIG		NO	LEASE LIFE	TYPE	STATUS		
SEE ATTACHED LIST										
OPERATOR CHANGES DOCUMENT	ATI	ION								
Enter date after each listed item is completed										
1. (R649-8-10) Sundry or legal documentation wa				-		8/6/2007				
2. (R649-8-10) Sundry or legal documentation wa	as rec	ceived fi	rom the	NEW operator	on:	8/6/2007	_			
3. The new company was checked on the Depart	ment	of Con	nmerc	e, Division of Co	orporation	s Database on:	-	8/6/2007		
4a. Is the new operator registered in the State of U	Jtah:			Business Numb	er:	5655506-0143	_			
4b. If NO, the operator was contacted contacted of	n:			-			-			
5a. (R649-9-2)Waste Management Plan has been re	ceiv	ed on:		IN PLACE						
5b. Inspections of LA PA state/fee well sites comp	lete c	on:		n/a	-					
5c. Reports current for Production/Disposition & S	Sundr	ries on:		ok	-					
6. Federal and Indian Lease Wells: The BI	M a	nd or th	e BIA l	nas approved the	- e merger, na	me change.				
or operator change for all wells listed on Feder					BLM	g.,	BIA			
7. Federal and Indian Units:						-	<u>-i</u>	-		
The BLM or BIA has approved the successor	ofu	ınit oper	ator fo	r wells listed on:	:					
8. Federal and Indian Communization Ag		_					•			
The BLM or BIA has approved the operator										
9. Underground Injection Control ("UIC"					oved UIC F	orm 5, Transfer	of Auth	ority to		
Inject, for the enhanced/secondary recovery ur	it/pr	oject for	r the w	ater disposal wel	ll(s) listed o	n:		_		
DATA ENTRY:								_		
1. Changes entered in the Oil and Gas Database	on:			9/27/2007	_					
2. Changes have been entered on the Monthly O	pera	tor Cha	nge Sp			9/27/2007	_			
3. Bond information entered in RBDMS on:				9/27/2007	-					
4. Fee/State wells attached to bond in RBDMS or				9/27/2007	-					
5. Injection Projects to new operator in RBDMS6. Receipt of Acceptance of Drilling Procedures in		DI)/NIe	w on.	9/27/2007	9/27/2007					
6. Receipt of Acceptance of Drilling Procedures in BOND VERIFICATION:	oi A	ואוויתי	v UII.		312112001	-				
				UTB000138						
 Federal well(s) covered by Bond Number: Indian well(s) covered by Bond Number: 				n/a	-					
3a. (R649-3-1) The NEW operator of any state/fe	e we	ell(s) list	ted cov		- umber	104312762				
3b. The FORMER operator has requested a release				-	1/23/2008		-			
The Division sent response by letter on:										
LEASE INTEREST OWNER NOTIFIC	CAT	ION:	-	 						
4. (R649-2-10) The NEW operator of the fee wells			ntacteo	and informed b	y a letter fr	om the Division				
of their responsibility to notify all interest owner					-					
COMMENTS:										

STATE OF UTAHDEPARTMENT OF NATURAL RESOURCES

(5/2000)

DIVISION OF OIL, GAS AND MINING					5. LEASE DESIGNATION AND SERIAL NUMBER:
	SUNDRY	Y NOTICES AND REPO	RTS ON WEL	LS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:
Do	not use this form for proposals to drill I drill horizontal I	7. UNIT or CA AGREEMENT NAME:			
1. T	YPE OF WELL OIL WELL	8. WELL NAME and NUMBER:			
2. N	AME OF OPERATOR:				SEE ATTACHED 9. API NUMBER:
	XTO Energy Inc.	N2615			SEE ATTACHED
3. A		louston Street Y Fort Worth STATE TX	zip 76102	PHONE NUMBER: (817) 870-2800	10. FIELD AND POOL, OR WILDCAT: Natural Buttes
4. L	OCATION OF WELL	FI TOIL WOLLI S(A) E TX	230 10102	1(017) 870-2000	Tracarar Bacco
F	OOTAGES AT SURFACE: SEE A	ATTACHED			соинту: Uintah
Q	RTR/QTR, SECTION, TOWNSHIP, RAM	NGE, MERIDIAN:			STATE: UTAH
11.	CHECK APP	ROPRIATE BOXES TO INDI	CATE NATURE	OF NOTICE, REPO	RT, OR OTHER DATA
	TYPE OF SUBMISSION		Т	YPE OF ACTION	
\checkmark	NOTICE OF INTENT	ACIDIZE	DEEPEN		REPERFORATE CURRENT FORMATION
	(Submit in Duplicate)	ALTER CASING	FRACTURI	ETREAT	SIDETRACK TO REPAIR WELL
	Approximate date work will start:	CASING REPAIR		STRUCTION	TEMPORARILY ABANDON
	<u> </u>	CHANGE TO PREVIOUS PLANS	✓ OPERATOR		TUBING REPAIR
\Box	SUBSEQUENT REPORT	CHANGE TUBING CHANGE WELL NAME	PLUG AND	ABANDON	
	(Submit Original Form Only)	CHANGE WELL STATUS	_	ION (START/RESUME)	WATER SHUT-OFF
	Date of work completion:	COMMINGLE PRODUCING FORMAT		TION OF WELL SITE	OTHER:
		CONVERT WELL TYPE	RECOMPL	ETE - DIFFERENT FORMATION	
12.	DESCRIBE PROPOSED OR C	OMPLETED OPERATIONS. Clearly sho	w all pertinent details ir	cluding dates, depths, volume	es, etc.
	Effective July 1, 2007,	XTO Energy Inc. has purcha	sed the wells list	ed on the attachment	t from:
	Dominion Exploration a 14000 Quail Springs P Oklahoma City, OK 73	Parkway, Suite 600 🛚 🖊 🖊	095		
	Sr. Vice President, Ge Please be advised tha under the terms and c	e (#05) at ATO Energy Inc. is consider to the wide BLM Bond #104312750 at ATO Energy Inc.	siness Unit red to be the ope operations cond	ucted upon the lease	lands. Bond coverage
	ME (PLEASE PRINT) Edwin S. NATURE ECLIVION	Ryan, Jr.		LE <u>Sr. Vice Presider</u>	nt - Land Administration
This s	space for State use only)	- Quadina			RECEIVED
	APPROVE	D <u>9127107</u> Pussell			AUG 0 6 2007
5/2000	$^{\prime\prime}$ Division of Oil. 9	DIV. OF OIL, GAS & MINING			
	Eariene Kussell,	Engineering Technician			

7

N1095 DOMINION E and P, INC. to N2615 XTO ENERGY, INC.

api	well name	qtr_qtr	sec	twp	rng	lease num	entity	Lease	well	stat
4304731522	FEDERAL 1-29	SWNW	29			U-28203		Federal		
4304731601	HILLCREEK FED 1-30	NWSW	30			U-30693		Federal		
4304731675	HILL CREEK FED 1-27	SENW	27			U-29784		Federal		
4304733671	HCU 1-28F	NENE	28			14-20-H62-4783			GW	
4304733672	HCU 1-29F	NENE	29			U-28203		Federal		P
4304733673	HCU 2-30F	NWNE	30			UTU-29784		Federal		P
4304733688	HCU 3-28F	NENW	28			U-28203		Federal		
4304733689	HCU 3-29F	NENW	29			U-28203		Federal		
4304733713	HCU 3-30F	NWNW	30			UTU-30693		Federal		
4304733835	HCU 5-30F	SWNW	30			U-30693		Federal		
4304733836	HCU 6-30F	SENW	30			U-30693		Federal		
4304733964	HCU 8-30F	SENE	30			UTU-29784		Federal		
4304733965	HCU 11-30F	NESW	30	_		U-30693		Federal		
4304733966	HCU 13-30F	SWSW	30			U-30693		Federal		
4304734045	HCU 5-28F	SWNW	28			U-28203		Federal		
4304734046	HCU 7-29F	SWNE	29			U-28203		Federal		P
4304734223	HCU 9-29F	NESE	29			U-28203		Federal		P
4304734298	HCU 3-31F	NWNW	31			UTU-30693		Federal		P
4304734299	HCU 5-31F	SWNW	31			UTU-30693		Federal		
4304734300	HCU 7-31F	SENW	31			UTU-30693		Federal		1
4304734316	HCU 2-27F	NWNE	27			UTU-79130		Federal		P
4304734351	HCU 8-27F	SENE	27			UTU-79130		Federal		P
4304734352	HCU 11-31F	NWSW	31			UTU-30693		Federal		P
4304734353	HCU 13-31F	SWSW	31			UTU-30693	<u> </u>	Federal	-	P
4304734853	HCU 1-33F	NENE	33			14-20-H62-4782				P
4304734854	HCU 3-34F	NENW	34			U-28203		Federal		P
4304734913	HCU 1-27F	NENE	27			U-79130		Federal		P
4304734914	HCU 3-27F	NENW	27		_	U-79130		Federal		P
4304734915	HCU 7-27F	SWNE	27		_	U-79130		Federal		S
4304734916	HCU 10-27F	NWSE	27		_	U-79130		Federal		P
4304734917	HCU 14-30F	SWSW	30	1		U-30693		Federal		P
4304734918	HCU 15-30F	SWSE	30			U-29784		Federal		P
4304734919	HCU 2-31F	NWNE	31	1		U-30693		Federal		
4304734920	HCU 6-31F	SWNW	31			U-30693		Federal		
4304734921	HCU 4-31F	NWNW	31		-	U-30693		Federal		
4304735130	HCU 11-27F	NESW	27			U-29784		Federal		
4304735131	HCU 2-29F	NWNE	29	 	+	U-28203		Federal		P
4304735132	HCU 9-30F	NESE	30			U-29784		Federal		
4304735133	HCU 10-30F	NWSE	30			U-29784		Federal		
4304735134	HCU 1-31F	NENE	31			U-36903		Federal		
4304735135	HCU 12-31F	NWSW	31			U-30693		Federal		
4304735137	HCU 2-33F	NENE	33			U-28203		Federal		
4304735139	HCU 5-34F	NENW	34	-	+	U-28203		Federal		
4304735154	HCU 13-27F	NESW	27		-	U-29784		Federal		
4304735230	HCU 8-33F	SENE	33			14-20-H62-4782		-	GW	
4304735307	HCU 6-29F	SENW	29			U-28203		Federal		
4304735470	HCU 11-29F	NESW	29			U-28203		Federal		
4304735471	HCU 10-29F	NWSE	29			U-28203		Federal		

1

09/27/2007

N1095 DOMINION E and P, INC. to N2615 XTO ENERGY, INC.

oni	vvol1 nome	orter orter		4	\	1	4:4	Υ		-4-4
api 4304735507	well_name HCU 12-29FA	qtr_qtr NESW	sec	twp	rng	lease_num	entity	Lease	well	stat
4304735724	HCU 16-27F		29			U-28203		Federal		
4304735725	HCU 16-27F	SESE	27	·		U-79130		Federal		P
	HCU 9-27F HCU 15-27F	NESE	27			U-79130		Federal		
4304735726		SWSE	27			U-79130		Federal		
4304735727	HCU 9-34F	NESE	34			U-79130		Federal	1	
4304735728	HCU 7-34F	SWNE	34			U-79130		Federal		
4304735832	HCU 9-33F	NESE	33			U-28203		Federal		
4304735833	HCU 16-33F	SESE	33			U-28203		Federal		
4304735835	HCU 11-34F	NESW	34			U-28203		Federal		
4304735836	HCU 12-34F	NWSW	34			U-28203		Federal		
4304735837	HCU 13-34F	SWSW	34			U-28203		Federal		
4304735838	HCU 15-34F	SWSE	34			U-79130		Federal		
4304735875	HCU 14-34F	SWSE	34			U-79130		Federal		P
4304735934	HCU 8-31F	SENE	31			U-30693		Federal		
4304735935	HCU 10-31F	NWSE	31			U-30693		Federal		
4304735936	HCU 9-31F	NWSE	31			U-30693		Federal		
4304735939	HCU 16-28F	SESE	28			U-28203		Federal		
4304735940	HCU 6-34F	SENW	34			U-28203		Federal		
4304735996	HCU 16-34F	SESE	34			U-79130		Federal		ļ
4304736046	HCU 14-31F	SWSW	31			U-30693		Federal		
4304736251	HCU 16-30F	NESE	30	 		U-29784	1	Federal		
4304736319	HCU 10-28F	NWSE	28			U-28203	1	Federal		
4304736320	HCU 13-28F	SWSW	28	1	!	U-28203		Federal		
4304736321	HCU 14-28F	SESW	28			U-28203	-	Federal		.
4304736437	HCU 5-27F	SWNW	27		1.	U-29784	-	Federal		
4304736438	HCU 4-27F	SWNW	27			U-29784		Federal		-
4304736439	HCU 11-28F	NESW	28			U-28203		Federal		
4304736440	HCU 5-30F2	SWNW	30			U-30693		Federal		·
4304736601	HCU 5-33F	SWNW	33			U-28203		Federal		
4304736602	HCU 12-33F	NWSW	33			U-28203		Federal		
4304736603	HCU 6-28F	SENW	28	 		U-28203		Federal		
4304736604	HCU 12-28F	NWSW	28			U-28203		Federal		
4304736685	HCU 13-33F	SWSW	33	100S	200E	U-28203	12829	Federal		
4304736846	HCU 9-28F	NESE	28			14-20-H62-4781			GW	P
4304736847	HCU 8-28F	SENE	28			14-20-H62-4783			GW	
4304736848	HCU 7-28F	SWNE	28			U-28203		Federal		
4304736849	HCU 1-34F	NENE	34	100S	200E	U-79130	12829	Federal	GW	P
4304736852	HCU 14-27F	NESW	27			U-29784	12829	Federal	GW	DRL
4304736853	HCU 16-29F	SESE	29			U-28203	12829	Federal	GW	P
4304737060	HCU 4-33F	NWNW	33	100S	200E	U-28203	12829	Federal	GW	P
4304737202	HCU 6-33F	SENW	33	100S	200E	U-28203	12829	Federal	GW	P
4304737203	HCU 3-33F	NWNE	33		<u> </u>	U-28203		Federal		
4304737204	HCU 15-28F	NWNE	33	100S	200E	14-20-H62-4781	12829	Indian	OW	P
4304737284	HCU 7-30F	SENE	30	100S	200E	U-29784	99999	Federal	OW	DRL
4304737340	HCU 5-29F	SWNW	29	100S	200E	U-28203	12829	Federal	GW	P
4304737360	HCU 11-33F	NWSW	33	100S	200E	U-28203	12829	Federal	GW	P
4304737424	HCU 12-27F	NESW	27	100S	200E	U-29784	12829	Federal	OW	DRL
4304737425	HCU 14-29F	SWSW	29			U-28203	12829	Federal	GW	P

2 09/27/2007

N1095 DOMINION E and P, INC. to N2615 XTO ENERGY, INC.

api	well_name	qtr_qtr	sec	twp	rng	lease num	entity	Lease	well	stat
4304737426	HCU 13-29F	SWSW	29	100S	200E	U-28203	12829	Federal	GW	P
4304737427	HCU 8-29F	NESE	29	100S	200E	U-28203	12829	Federal	GW	P
4304737445	HCU 8-34F	SENE	34	100S	200E	U-79130	12829	Federal	OW	S
4304737446	HCU 2-34F	NWNE	34	100S	200E	U-79130	12829	Federal	OW	DRL
4304737447	HCU 7-33F	SENE	33	100S	200E	U-28203	12829	Federal	OW	DRL
4304737570	HCU 10-33F	NWSE	33	100S	200E	14-20-H62-4782	12829	Indian	GW	P
4304737749	HCU 4-28F	NENW	28	100S	200E	U-28203	99999	Federal	GW	DRL
4304737750	HCU 14-33F	SWSE	33	100S	200E	U-028203	12829	Federal	GW	DRL
4304731560	HILL CREEK ST 1-32	SENW	32	100S	200E	ML-22313	12829	State	GW	P
4304734852	HCU 4-32F	NWNW	32	100S	200E	ML-22313-2	12829	State	GW	P
4304735136	HCU 5-32F	SWNW	32	100S	200E	ML-22313-2	12829	State	GW	P
4304735870	HCU 13-32F	NESE	31	100S	200E	ML-22313-2		State	GW	LA
4304735871	HCU 12-32F	NESE	31	100S	200E	ML-22313-2		State	GW	LA
4304735872	HCU 14-32F	SESW	32	100S	200E	ML-22313-2	12829	State	GW	P
4304735873	HCU 3-32F	NENW	32	100S	200E	ML-22313-2	12829	State	GW	DRL
4304735874	HCU 11-32F	SENW	32	100S	200E	ML-22313-2	12829	State	D	PA
4304736322	HCU 16-32F	SESE	32	100S	200E	ML-22313-2	12829	State	GW	P
4304736323	HCU 9-32F	NESE	32	100S	200E	ML-22313-2	12829	State	GW	P
4304736324	HCU 8-32F	SENE	32	100S	200E	ML-22313-2	12829	State	GW	P
4304736441	HCU 1-32F2	NENE	32	100S	200E	ML-22313-2	12829	State	GW	P
4304736684	HCU 7-32F	SENE	32	100S	200E	ML-22313-2	12829	State	GW	P

3 09/27/2007



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Utah State Office P.O. Box 45155 Salt Lake City, UT 84145-0155



IN REPLY REFER TO 3180 UT-922

Dominion Exploration & Production, Inc. Attn: James D. Abercrombie 14000 Quail Springs Parkway, #600 Oklahoma City, OK 73134-2600

August 10, 2007

Re:

Hill Creek Unit Uintah County, Utah

Gentlemen:

On August 8, 2007, we received an indenture dated June 30, 2007, whereby Dominion Exploration & Production, Inc. resigned as Unit Operator and XTO Energy Inc. was designated as Successor Unit Operator for the Hill Creek Unit, Uintah County, Utah.

This indenture was executed by all required parties and the signatory parties have complied with Sections 5 and 6 of the unit agreement. The instrument is hereby approved effective August 15, 2007. In approving this designation, the Authorized Officer neither warrants nor certifies that the designated party has obtained all required approval that would entitle it to conduct operations under the Hill Creek Unit Agreement.

Your statewide oil and gas Bond No. UTB000138 will be used to cover all operations within the River Bend Unit.

It is requested that you notify all interested parties of the change in unit operator. Copies of the approved instruments are being distributed to the appropriate federal offices, with one copy returned herewith.

Sincerely,

/s/ Greg J. Noble

Greg J. Noble Acting Chief, Branch of Fluid Minerals

Enclosure

AUG 1 6 2007

	FORM 9						
	DEPARTMENT OF NATURAL RESOURCE DIVISION OF OIL, GAS, AND MI		5.LEASE DESIGNATION AND SERIAL NUMBER: U-79130				
SUNDE	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE						
bottom-hole depth, reenter plu DRILL form for such proposals.	sals to drill new wells, significantly deeper igged wells, or to drill horizontal laterals.	n existing wells below current Use APPLICATION FOR PERMIT TO	7.UNIT or CA AGREEMENT NAME: HILL CREEK				
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: HCU 14-34F				
2. NAME OF OPERATOR: XTO ENERGY INC			9. API NUMBER: 43047358750000				
3. ADDRESS OF OPERATOR: 382 Road 3100 , Aztec, NM, 8		HONE NUMBER: t	9. FIELD and POOL or WILDCAT: NATURAL BUTTES				
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0829 FSL 1958 FEL QTR/QTR, SECTION, TOWNSHI	D DANCE MEDIDIAN.		COUNTY: UINTAH				
	Township: 10.0S Range: 20.0E Meridian:	S	STATE: UTAH				
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPORT,	OR OTHER DATA				
TYPE OF SUBMISSION		TYPE OF ACTION					
	ACIDIZE	ALTER CASING	☐ CASING REPAIR				
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME				
✓ SUBSEQUENT REPORT	☐ CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE				
Date of Work Completion:	L DEEPEN	FRACTURE TREAT	☐ NEW CONSTRUCTION				
2, 13, 2010	OPERATOR CHANGE	PLUG AND ABANDON	L PLUG BACK				
SPUD REPORT Date of Spud:	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION				
	☐ REPERFORATE CURRENT FORMATION ☐ TUBING REPAIR	□ SIDETRACK TO REPAIR WELL □ VENT OR FLARE					
☐ DRILLING REPORT	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION				
Report Date:		✓ OTHER					
	☐ WILDCAT WELL DETERMINATION		OTHER: CLEANOUT				
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. XTO Energy Inc. has cleaned out this well per the attached summary report. Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY 1. Contact of Complete Proposed							
NAME (PLEASE PRINT) Barbara Nicol	PHONE NUMBER 505 333-3642	R TITLE Regulatory Compliance Tech					
SIGNATURE N/A		DATE 2/22/2010					

EXECUTIVE SUMMARY REPORT

 $\frac{1/1/2010 \ - \ 2/22/2010}{\text{Report run on } 2/22/2010 \ \text{at } 2:24 \ \text{PM}}$

Hill Creek Unit 14-34F

Section 34-10S-20E, Uintah, Utah, Roosevelt

2/15/2010	First rpt for Well Maintenance /Clean out. MIRU Key Energy rig #6013. Bd
	well. ND WH. NU BOP. Unable to unlnd hngr. PU Hyd jarsw/ Acc sub, Wkd jars
	jarred hngr free (1 hit). LD hngr. TIH $w/$ 6 jt's 2.375'', 4.7 $\#$, N-80 eue tbg.
	No tg. TOH w/200 jts 2.375'', 4.7#, N-80 EUE tbg. LD 40jt's 2-3/8'', N-80,
	4.7#, eue tbg due to BAD EXT corrosion. SN & BRS. TIH $w/4.75$ '' bit, 5.5''
	csg scr & 145 jts 2-3/8'' tbg. EOT @ 4500'. SWI & SDFWE. NOTE: Tbg EOT @
	7600' +/- Not 8029' as reported.

2/16/2010 Bd well. Contd TIH w/4.75'' bit, 5.5'' csg scr & 253 ttl jts tbg. Tgd 121' fill @ 8050'. RU pwr swivel & AFU. Estab circion & CO to BRS @ 8115', PBTD @ 8171'. TOH w/257 jts tbg. LD bit & scr. TIH w/mule shoe col, 2-3/8" SN & 100 jts 2-3/8'', 4.7#, L-80, EUE tbg. SWI & SDFN.

2/17/2010 Contd TIH w/mule shoe col, 2-3/8" SN & 250 ttl jts 2-3/8'', 4.7#, L-80, EUE tbg. Ld on hgr, EOT @ 7987. SN @ 7986'. WA/MV perfs fr/6207 - 8086'. RU & RIH w/1.91 tbg broach to SN @ 7986'. No ti spots. POH & LD broach. Pmp 10 bls TFW, dropd SV. Fill & PT tbg w/17 bbls to 2000 psig, 30", tstd gd. Rlsd press. RU & RIH w/on-off tls. Made 3 runs & retrv SV. POH & LD SV & tls. SWI & SDFN.

2/18/2010 EOT @ 7987'. SN @ 7986'. WA/MV perfs fr/6207 - 8086'. RU & RIH w/swb tls.
BFL @ 5,400' FS. S. 0 BO, 10 BLW, 3 runs, 2 hrs. KO well flwg to tst tnk.
F. 15 BLW. 1.5 hrs. FTP 250 - 0 psig. SICP 650 - 400 psig. Well died.
Dropd BHBS w/SV. RIH w/sbs & seat BHBS @ 7986'. POH w/sd ln. RU & RIH
w/swb tls. BFL @ 6,600' FS. S. 0 BO, 2 BLW, 1 run. KO well flwg to tst tnk.
F. 8 BLW. 1.5 hrs. FTP 50 - 0 psig. SICP 400-350 psig. Well died. SWIFPBU & SDFN.

2/19/2010 OWU & Bd tbg. KO well flwg to test tnk 1 hr, recd 5 BLW. Cycle plngr 2x's to surf. RDMO Key Energy #6013. RWTP @ 10:00 a.m. Turn well over to prod. dept, begin tst data.

Sundry Number: 26268 API Well Number: 43047358750000

	STATE OF UTAH			FORM 9
ι	DEPARTMENT OF NATURAL RESOUR DIVISION OF OIL, GAS, AND MI			5.LEASE DESIGNATION AND SERIAL NUMBER: U-79130
SUNDR	Y NOTICES AND REPORTS	ON V	VELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME: UTE
	posals to drill new wells, significantly reenter plugged wells, or to drill horizon n for such proposals.			7.UNIT or CA AGREEMENT NAME: HILL CREEK
1. TYPE OF WELL Gas Well				8. WELL NAME and NUMBER: HCU 14-34F
2. NAME OF OPERATOR: XTO ENERGY INC				9. API NUMBER: 43047358750000
3. ADDRESS OF OPERATOR: 382 Road 3100, Aztec, NM	M, 87410 505 333-31		IE NUMBER: t	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0829 FSL 1958 FEL				COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSH	IIP, RANGE, MERIDIAN: 4 Township: 10.0S Range: 20.0E Meri	idian: S		STATE: UTAH
11. CHECK	K APPROPRIATE BOXES TO INDICA	ATE NA	TURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION			TYPE OF ACTION	
	✓ ACIDIZE		TER CASING	CASING REPAIR
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	Сн	HANGE TUBING	CHANGE WELL NAME
Approximate date work will start.	CHANGE WELL STATUS	□ cc	DMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	☐ FR	ACTURE TREAT	NEW CONSTRUCTION
5/4/2012	OPERATOR CHANGE	Пы	UG AND ABANDON	PLUG BACK
 	PRODUCTION START OR RESUME		CLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION		DETRACK TO REPAIR WELL	TEMPORARY ABANDON
DRILLING REPORT	☐ TUBING REPAIR		INT OR FLARE	☐ WATER DISPOSAL
Report Date:	☐ WATER SHUTOFF	∟ sı	TA STATUS EXTENSION	APD EXTENSION
	WILDCAT WELL DETERMINATION	√ от	THER	OTHER: CHEMICAL TREATMENT
XTO Energy Inc. has	COMPLETED OPERATIONS. Clearly showns acidized & performed a chall per the attached summary	nemic	al treatment on this	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY June 01, 2012
NAME (PLEASE PRINT)	PHONE NUMI	BER	TITLE	
Barbara Nicol	505 333-3642		Regulatory Compliance Tec	h
SIGNATURE N/A			DATE 6/1/2012	

Sundry Number: 26268 API Well Number: 43047358750000

Hill Creek Unit 14-34F

4/25/2012: MIRU Nalco. Pump 5 gal of EC9573A (mutual solvent), 5 gal of EC6652A (scale Inhibitor) & 130 gal of 10% HCL with 130 gal of fresh water down the tbg. Displace tbg with 35 bbls of 2% KCL. Pump 5 gal of EC9573A (mutual solvent), 5 gal of EC6652A (scale inhibitor) & 130 gal of 10% HCL with 130 gal of fresh water down the CSG. Displace CSG with 95 bbls of 2% KCL. SWI for 12 hrs. RDMO Nalco.

4/26/2012: MIRU SWU. BD tbg to prod tk. RU swb tls & RIH. Swab.

4/27/2012: RU swb tls & RIH. Swab.

4/30/2012: RU swb tls & RIH. Swab.

5/1/2012: RU swb tls & RIH. Swab. Drop dual pad plngr & SWI for 1 hr.

5/2/2012: RU swb tls & RIH. Swab.

5/3/2012: RU swb tls & RIH. Swab.

5/4/2012: RU swb tls & RIH. Swab. Drop dual pad plngr. Cycld plngr to surf & RWTP. RDMO SWU.

RECEIVED: Jun. 01, 2012